

## 4 PC. X-TRAX SCREW REMOVER SET



## M2 6542 TUNGSTEN ALLOY

Harder than most extractors

Item #	Inner	Master	UPC	Packaging	
W491	20	80	039564148750	Carded	Performa
quickly rem screws and damaging s Upgraded o alloy is har allowing re fasteners in hardened s tensile stre 1/4 in. and	<ul> <li>Reverse thread design with dual tips quickly remove stripped or broken screws and broken off bolts without damaging surrounding area</li> <li>Upgraded quality M2 6542 tungsten alloy is harder than most extractors, allowing removal of far more fasteners including stainless, hardened steel and brass up to 12.9 tensile strength</li> <li>1/4 in. and 5/16 in. hex shank screw extractors work with any adjustable</li> </ul>		the proper size a hole with the Flip the bit to th end, and slowly fastener out Sizes included following size d #1 (#4-7 screws (#8-10 screws; (#11-14 screws;	operation: determine bit to use, and drill fluted cutting end. the tapered threaded reverse the damaged	REMOVED

 Designed to drill out and remove even the most stubborn stripped, damaged, embedded, rusted or

performancetool.com

P.O. Box 88259 Tukwila, WA. 98138 1-800-426-1262 (USA & Canada) 1-800-352-9185 (Fax)

1/4 5/16

00000

· IRAX