



# P704T

## HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The Home Office Surge Protector P704T from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The P704T provides 2,250 joules of protection and 7 surge-protected outlets (6 standard and 1 widely-spaced). Data line protection occurs with RJ11 ports for telecommunication devices (phones, faxes, modems, and DSL lines).

Features of the P704T include automatic shutdown, an On/Off switch with integrated 15-Amp circuit breaker, metal oxide varistor (MOV) technology, an EMI/RFI noise filter, power cord (4 ft.) with a right-angle plug, safety outlet covers, keyhole slots, and impact-resistant casing. The P704T comes with a Limited Lifetime Warranty and a \$175,000 Connected Equipment Guarantee.

### TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Consumer Electronics

### FEATURES

- Surge suppression: 2,250 J
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P
- Outlet type: NEMA 5-15R
- Outlets: 7 surge-protected (6 standard + 1 widely-spaced)
- Power cord: 4 ft
- Data line protection: Telephone, DSL, Fax
- Color: Black
- EMI/RFI Filtration: Yes
- Warranty: Limited Lifetime
- Connected Equipment Guarantee: \$175,000



## SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Rotating Power Cord	No
OUTPUT	
Outlet Type	8 - NEMA 5-15R
Outlets - Total	8
Outlets - Widely-spaced	4

SURGE PROTECTION & FILTERING	
Attenuation	43 dB
Clamping Voltage	400V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	120,000 A
Maximum Surge Current H-G	30,000 A
Maximum Surge Current H-N	60,000 A
Maximum Surge Current N-G	30,000 A
Maximum Surge Voltage	6,000 V
Phone Protection RJ11	1-In / 1-Out
Response Time	<1 Nanosecond
Surge Suppression (Joules)	2,250 J

# P704T

## HOME OFFICE SURGE PROTECTION

### SPECIFICATIONS CONT.

#### PHYSICAL

Color	Black
Cord Management	Yes
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Keyhole Mounting Slots	Yes
Material of Construction	Plastic
Safety Covers	Yes

#### PHYSICAL DIMENSIONS

Physical Dimensions - WxHxD (cm)	7.01 x 3.4 x 30.71 cm
Physical Dimensions - WxHxD (mm)	70 x 34 x 307 mm
Physical Dimensions - WxHxD (in.)	2.76 x 1.34 x 12.09 in.
Weight (kg)	0.41 kg
Weight (lb)	0.90 lbs.

#### SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm)	3.51 x 36.2 x 12.07 cm
Shipping Dimensions - WxHxD (mm)	35.05 x 361.95 x 120.65 mm
Shipping Dimensions - WxHxD (in)	1.38 x 14.25 x 4.75 in.
Weight (kg)	6.64 kg
Weight (lb)	14.63 lbs.

#### CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1363 UL1449 3rd Edition cUL

#### WARRANTY

CEG Amount	\$175,000
Connected Equipment Guarantee	Lifetime
Product Warranty	Limited Lifetime Warranty