



CPS1215RM RACKMOUNT SURGE PROTECTOR



Industrial rack mount surge protectors designed to safeguard computer systems and networking equipment.

The CyberPower CPS1215RM, a 10-outlet (rear) rackmount power distribution unit (PDU), provides 100-125V 15A output. It distributes power to 10 NEMA 5-15R receptacles from a single NEMA 5-15P input with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, the CPS1215RM has durable metal housing and a 15-foot AC power cord. It can be mounted horizontally, includes a cord retention tray, and is UL Recognized. The CPS1215RM comes with a three-year limited warranty and covers defects in materials and workmanship in the product under normal use and conditions within three years of the purchase date.

TYPICAL APPLICATIONS

- VoIP Phone Systems
- Network Closets
- Data Centers
- Industrial Environments

FEATURES

- Phase: Single
- Amps: 15A
- Volts: 100-125 V
- Frequency: 60Hz
- Plug type: NEMA 5-15P
- Outlets: 10 NEMA 5-15R
- Outlet location: 10 Rear
- Size: 1U Rackmount
- Dimensions W x H x D: 17.25 x 1.75 x 4.75 in.
- Cord length (ft.): 15 ft.
- Warranty: Three-Year

SPECIFICATIONS

INPUT	
Circuit Breaker	15A
Cord Length	15 ft. (4.6 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15A
Nominal Input Voltage	100 - 125 VAC
Phase	Single Phase
Plug Style	Straight
Switch	Lighted On / Off

OUTPUT	
Nominal Output Voltage	100 - 120 VAC
Outlet Type	10 x NEMA 5-15R
Outlets - Number of Banks	1
Outlets - Front	0
Outlets - Rear	10
Outlets - Total	10
Overload Protection	15A

SURGE PROTECTION & FILTERING	
Clamping Voltage	800V (H-N)

CPS1215RM RACKMOUNT SURGE PROTECTOR



SPECIFICATIONS CONT.

PHYSICAL

Color	Black
Cord Retention Tray Cord Organizers	Yes
Form Factor Supported	1U Rackmount
Material of Construction	Metal
Rack Height	1U

DIMENSIONS

Physical Dimensions - Width/Height/Depth (cm)	43.82 x 4.45 x 12.07 cm
Physical Dimensions - Width/Height/Depth (mm)	438 x 44 x 121 mm
Physical Dimensions - Width/Height/Depth (in.)	17.25 x 1.75 x 4.75 in.
Weight (kg)	2.27 kg
Weight (lbs.)	5.0 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - Width/Height/Depth (cm)	5.84 x 25.15 x 51.74 cm
Shipping Dimensions - Width/Height/Depth (mm)	58.42 x 251.46 x 517.4 mm
Shipping Dimensions - Width/Height/Depth (in.)	2.3 x 9.9 x 20.37 in.
Shipping Weight (kg)	2.64 kg
Shipping Weight (lbs.)	5.83 lbs.

ENVIRONMENTAL

Operating Elevation	0 to 10,000 ft / 3,048 m
Operating Relative Humidity	0% - 95% non-condensing
Operating Temperature	32°F - 104°F / 0°C - 40°C
Storage Elevation	0 to 50,000 ft / 15,239 m
Storage Temperature	5°F - 113°F / -15°C - 45°C

CERTIFICATIONS

Safety	UL Recognized
--------	---------------

WARRANTY

Product Warranty	3-Year Limited
------------------	----------------