



HT705UC

PREMIUM SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower Premium Surge Protector HT705UC is ideal for the home, office, or home theater because it is designed to provide maximum protection and convenience to a number of devices where wall receptacles are out of reach. The Premium Surge Protector prevents damaging spikes in energy caused by storms and electrical power from reaching your electronic equipment. The HT705UC provides 3,480 joules of protection, 7 outlets (1 widely-spaced for a transformer plug), 2 USB charging ports, and a right-angle, 5-foot braided power cord.

Features of the HT705UC include safe-fail notification and fireproof technology. This surge suppressor comes with a One-Year Limited warranty and a connected equipment guarantee.

TYPICAL APPLICATIONS

- Mobile Devices
- Personal Electronics
- Cell Phones
- Personal Computers

FEATURES

- Surge suppression: 3,480 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 7 x NEMA 5-15R (surge-protected)
- Power cord: 5 ft.
- Data line protection: Coaxial
- Cable/Satellite protection: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$800,000



SPECIFICATIONS

INPUT		OUTPUT	
Circuit Breaker	15 A	Outlet Type	7 NEMA 5-15R
Cord Length	5 ft (1.5 m)	Outlets - Total	7
Input Plug Type	NEMA 5-15P	Outlets - Widely Spaced	1 
Maximum Input Current	15 A	USB Charge Port	Yes
		USB Charge Port Amperage	3.1 Amps (Shared)
		USB Charge Port Quantity	2
		USB Charge Port Type	Type A
		USB Charge Port Voltage	5 VDC

HT705UC

PREMIUM SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING		DIMENSIONS	
Attenuation	43 dB	Physical Dimensions - Width/Height/Depth (cm)	6.4 x 3.15 x 40.13 cm
Clamping Voltage	500V (H-N, H-G, N-G)	Physical Dimensions - Width/Height/Depth (mm)	64 x 31 x 401 mm
Coax Protection RG6	1 in 1 out	Physical Dimensions - Width/Height/Depth (in.)	2.52 x 1.24 x 15.8 in.
EMI/RFI Filtration	150 KHz 100 MHz Yes	Weight (kg)	0.69 kg
Maximum Surge Current	105,000 A	Weight (lb)	1.52 lbs.
Maximum Surge Current H-G	15,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current H-N	75,000 A	Shipping Dimensions - Width/Height/Depth (cm)	17.17 x 50.8 x 3.2 cm
Maximum Surge Current N-G	15,000 A	Shipping Dimensions - Width/Height/Depth (mm)	171.7 x 508.0 x 32.0 mm
Maximum Surge Voltage	6,000 V	Shipping Dimensions - Width/Height/Depth (in.)	6.76 x 20 x 1.26 in.
Network Protection RJ45	1 in / 1 out	Shipping Weight (kg)	0.95 kg
Response Time	<1 Nanosecond	Shipping Weight (lbs.)	2.10 lbs.
Surge Suppression (Joules)	3,480 J	CERTIFICATIONS	
MANAGEMENT & COMMUNICATIONS		Environmental	RoHS Compliant
LED Indicators	Clean Power Ground LED	Safety	UL1363 UL1310 UL1449 3rd Edition cUL FCC DOE VI
PHYSICAL		WARRANTY	
Color	Black	CEG Amount	\$800,000
Form Factor	Strip	Connected Equipment Guarantee	Lifetime
Form Factors Supported	Horizontal Mount in Variety of Other Applications	Product Warranty	1-Year Limited
Material of Construction	Plastic		
Safety Covers	No		