



# P405UC HOME OFFICE SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower P405UC Surge Protector Strip prevents spikes caused by storms and electrical power surges from reaching your home electronics such as home entertainment equipment, computers, household appliances and small electronics. The P405UC provides 1,500 joules of surge protection, four AC outlets, one USB-C charging port, two USB-A charging ports, and a braided 5-foot power cord with a right-angle plug.

## TYPICAL APPLICATIONS

- Gaming Systems
- Consumer Electronics
- Chargers
- Laptop Computers

## FEATURES

- Surge suppression: 1,500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 4
- Total USB Output: 18W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 2
- USB charge output: 3.6A (shared)
- Power cord length: 5 ft
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Circuit breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$100,000



## SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	5 ft (1.5 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Low Profile
OUTPUT	
Outlet Type	4 - NEMA 5-15R
Outlets - Total	4
USB Charge Port	Yes
USB Charge Port Amperage	3.6 Amps (Shared)
USB Charge Port Quantity	3
USB Charge Port Type	2 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	18 Watts

SURGE PROTECTION AND FILTERING	
Clamping Voltage	600V (H-N, H-G, N-G)
Coax Protection RG6	None
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	45,000 A
Maximum Surge Current H-G	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Current N-G	15,000 A
Maximum Surge Voltage	6,000 V
Surge Suppression (Joules)	1,500 J

P405UC

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS CONT.

PHYSICAL	
Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic
PHYSICAL DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	4.72 x 3.45 x 24.99 cm
Physical Dimensions - Width/Height/Depth (mm)	47 x 35 x 250 mm
Physical Dimensions - Width/Height/Depth (in.)	1.86 x 1.36 x 9.84 in.
Weight (kg)	0.36 kg
Weight (lb)	0.8 lbs.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	4.45 x 30.48 x 10.16 cm
Shipping Dimensions - Width/Height/Depth (mm)	44.45 x 304.8 x 101.6 mm
Shipping Dimensions - Width/Height/Depth (in)	1.75 x 12.0 x 4.0 in.
Weight (kg)	0.53 kg
Weight (lb)	1.17 lbs.

CERTIFICATIONS	
Environmental	RoHS Compliant
Safety	UL1449 3rd Edition UL1363 UL1310 FCC cUL DOE VI
WARRANTY	
CEG Amount	\$100,000
Connected Equipment Guarantee	Lifetime
Product Warranty	1-Year Limited Warranty