



SE450B STANDBY UPS SYSTEM

Offers significant energy savings, battery backup and surge protection.

The CyberPower SE450B uninterruptible power supply (UPS) system provides surge protection for lightning-induced surges and other power events that can damage electronic equipment. This unit delivers enough battery backup to connected electronics during a utility power failure, so you can perform a proper shutdown to protect against the loss of data and damage to valuable electronics including computers, gaming consoles, and broadband routers. Including a sleek new design, this UPS is perfect for all your home office and entertainment needs.

With a \$100,000 connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to the quality of this Battery Backup with Surge Protection.



TYPICAL APPLICATIONS

- Desktop Computers
- Personal Electronics

FEATURES

- 450 VA / 260 W
- 8 Standard Outlets
- Standby Topology
- Full-time Surge Protection and Battery Backup
- Three-Year Warranty

SPECIFICATIONS

GENERAL

UPS Topology	Standby
Energy Saving	Yes

INPUT

Nominal Input Voltage	120Vac
Frequency	50/60Hz \pm 3Hz
Circuit Breaker	7A
Plug Type	NEMA 5-15P
Cord Length (ft)	5

OUTPUT

VA	450
Watts	260
On Battery Voltage	120Vac \pm 5%
On Battery Frequency	50/60Hz \pm 1%
On Battery Waveform	Simulated Sine Wave

OUTPUT CONT.

Outlet Type	NEMA 5-15R
Outlets - Total	8
Outlets - Battery & Surge Protected	4
Outlets - Surge-Only Protect	4
Outlets - Widely Spaced	2
Overload Protection	Circuit Breaker

BATTERY

Battery Type	Sealed Lead-Acid
Battery Quantity	1
Runtime at Half Load (min)	6
Runtime at Full Load (min)	1.5
Typical Recharge Time	8 Hours

SE450B STANDBY UPS SYSTEM



SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING

Surge Suppression	890
-------------------	-----

EMI/RFI Filtration	Yes
--------------------	-----

MANAGEMENT & COMMUNICATIONS

LED Indicators	Power On
----------------	----------

Audible Alarms	On Battery, Low Battery, Overload, Fault
----------------	--

PHYSICAL

Dimensions (WxHxD) (in.)	8.3 x 4.5 x 3.2
--------------------------	-----------------

Weight (lbs.)	3.8
---------------	-----

ENVIRONMENTAL

Operating Temperature	32-104°F (0-40°C)
-----------------------	-------------------

Operating Humidity	0-95% (non-condensing)
--------------------	------------------------

CERTIFICATIONS

Safety	UL1778, cUL, FCC DOC Class B, ENERGY STAR (USA), CEC
--------	--

Environmental	RoHS Compliant
---------------	----------------

WARRANTY

Product Warranty	Three-Years Limited
------------------	---------------------

Connected Equipment Guarantee	Lifetime
-------------------------------	----------

CEG Amount	\$100,000
------------	-----------