



CRC Industries NZ, Auckland NZ

I. Product Description

CRC Garage Door Lube is a high performance synthetic lubricant specifically formulated for use on all garage doors and components. It makes regular maintenance an easy no-mess task. It does not attract dust or clog up tracks and will not freeze in any weather conditions all year round.

CRC Garage Door Lube eliminates annoying squeaks and noises by reducing stress on components, extends the operational life span of any garage door system and reduces the need for expensive repairs. Regular use ensures smooth operation and protects from wear and corrosion.

II. Application and Directions

Preparation:

- Always comply with your garage door manufacturer's instructions.
- Ensure components are clean before applying *CRC Garage Door Lube*.
- Shake can well before use.

Application:

- Use sparingly on all components of your garage door system that require lubrication.

Clean Up:

- Wipe any excess with a cloth.

III. Features & Benefits

- **Suitable for all garage door designs and components** – Rolling doors, tilting doors, sectional doors, industrial rolling doors
- **Eliminates squeaking and sticking** – For smooth operation
- **Does not attract dust or clog up tracks**
- **Leaves no mess** – No clean up required
- **Corrosion protection** – For a long life span
- **Safe for use on all metal and plastic components**
- **Suitable in all weather conditions**

IV. Typical Properties and Characteristics

Physical Properties:

Odour	None
Appearance	Colourless liquid
Solubility	Neg. in water
% Volatile	Nil
Specific Gravity	0.88
Propellant	Hydrocarbon
Flash Point	> 350°C TCC



CRC Industries NZ, Auckland NZ

Technical Data Sheet – 5015

CRC Garage Door Lube

Performance Characteristics:

Type of film	Thin, oily film
Dry Time	Non-drying, wet
Timken OK Load	40lb
Temperature Range	-40°C to +300°C (continuous) +350°C (intermittent)

V. Package Description

Part Number	Size
5015	400ml Aerosol

VI. Special Precautions

General:

Avoid breathing dust, fume, gas, mist, vapours, spray. Use only outdoors or in a well-ventilated area. Store in a well-ventilated place. Keep container tightly closed. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Not considered a normal route of entry.

Skin – Flush skin and hair with running water (and soap if available). Remove any adhering solids with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation.

Eyes – Immediately hold eyelids apart and flush continuously for at least 15 minutes with fresh running water. Ensure complete irrigation by keeping eyelids apart and away from eye and moving eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay.

Inhalation – Remove to fresh air. If breathing with difficulty, get medical attention immediately.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 07/2015

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.