

Carpet Extraction is a restorative process intended for removal of built-up soil from the carpet fiber and carpet backing. When incorporated with a proper interim maintenance schedule, carpet extraction should be preformed once or twice a year.



People

- Team: 1 2 People
- Safety Equipment Gloves, eye protection, please refer to product Safety Data Sheets. Wet Floor Signs.
- Pre-Training Since carpet renovation (extraction) is performed at a very low frequency and can involve the moving of heavy furniture, it is important to review the proper procedures and safety measures before proceeding with this maintenance activity.



Product and/or Equipment

- Vacuum Upright vacuum preferred
- Vacuum Detail Tool
- Wet Floor Signs
- Trident Carpet Extractor
- Trident Carpet Fan(s)
- Hillyard Spotting Kit
- Hillyard HD Extraction
- Hillyard Carpet Booster (optional)
- Hillyard Defoamer II



Procedures

Remove furniture and walk-off mats.

Vacuum carpet thoroughly, preferably with an upright vacuum. the detail tool to vacuum all floor to wall junctions.

Place Wet Floor Signs at all carpet to hard floor junctions.











Use the Hillyard Spotting kit and Spotting chart to address any obvious discolored stains in the carpet.

Dilute Hillyard HD Extraction into the extractor solution tank at a rate of 2 oz. / gallon of water.

For enhanced results add one scoop of Hillyard Carpet Booster for each gallon of water in the solution tank.

Dispense 4 – 6 oz of Hillyard Defoamer II into the recovery tank.

Run extractor over carpet, engaging the solution supply, brushes and vacuum; use a 25 – 50% overlap with each pass of the extractor.

Position carpet fan(s) to allow sufficient airflow to promote quick drying of carpet.

Empty solution tank and recovery tanks, thoroughly rinse out recovery, also remove and rinse extractor spray nozzles.

Once carpet is dry, remove wet floor signs.







