

RT 700



T-REX® CLEAR REPAIR TAPE WITH ALL-WEATHER CRYSTAL CLEAR CONSTRUCTION

TYPICAL APPLICATIONS

- For quick and discreet repairs to a variety of surfaces, including those that require a water-resistant seal
- Can be applied to wet* or dry surfaces
- Can also be applied to rough surfaces and at below freezing temperatures
- For indoor and outdoor use
- *Follow recommended usage instructions for best results in wet-stick applications.

PRODUCT FEATURES

- Clear Repair Tape
- UV-resistant to prevent yellowing and maintain product performance and integrity
- Pinned edge for hand-tearability with clean edge
- Waterproof and water-resistant (after application to surface)
- Puncture-resistant, crystal clear backing

CONSTRUCTION

Backing: Ionomer film

Adhesive: Solvent acrylic-based

STANDARD WIDTH

1.88 in

48 mm

STANDARD LENGTH

9 yd

8.22 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

NA

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES	STANDARD	METRIC
Adhesion to Stainless Steel	100 oz/in width	10.95 N/10 mm
Elongation	430%	430%
Holding Power to Steel	1,800+ minutes	1,800+ minutes
Service Temperature Range	-5 F to 150 F	-20 C to 66 C
Tensile	23.5 lbs/in width	41.2 N/10 mm
Thickness	6.8 mils	0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



*Follow recommended usage instructions for best results in wet-stick applications.