

Jones Stephens' PlumBite® **Push On Tee**

Location Engineer	
-	PO#

Specifications

Jones Stephens' PlumBite® Push On Tees are a heat-free method of joining Copper, CPVC, PE-RT or PEX tubing, designed to save time on installation and to connect piping with relative ease and confidence. No soldering, glue, heat or external tools are required to join the pipe. Just insert the pipe and the stainless steel gripper ring, bite down, and hold the pipe tightly while the EPDM o-ring seals against leakage. Disassembly is just as fast using the optional disassembly tool, so fittings can be easily removed and re-used.

Applications

Jones Stephens' Push On Tees are approved for use with commercial and residential potable and non-potable water applications.

Materials

Body-DZR Brass O-Ring- EPDM, Peroxide Cured Gripper Ring-Stainless Steel

Dimensions and Product Offering

	PART NO. INDIVIDUAL	PART NO. BULK	A NOMINAL (IN.)	B NOMINAL (IN.)	C NOMINAL (IN.)	D (IN.)	D TOLERANCE +/- (IN.)
	C77440LF	C76510LF	0.50	0.50	0.50	2.68	0.08
	C77441LF	C76511LF	0.75	0.75	0.75	3.11	0.14
	C77442LF	-	1.00	1.00	1.00	1.62	0.08

Performance Specifications

Maximum Temperature: 180°F Maximum Pressure: 200 PSI Service: Potable Water

Exposure to water with elevated levels of inorganic materials (including but not limited to: Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

NSF/ANSI/CAN 61 NSF/ANSI/CAN 372 NSF/ANSI 14 IAPMO listed

IAPMO certified for use in manufactured joints without access panels ASSE 1061





