# **CyberPower**

## P600WUCHD 6-OUTLET WALL-TAP WITH USB

## Wall-tap surge protector with USB charging

The P600WUCHD Wall-tap Surge Protector with USB safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. It provides 500 joules of protection, has 6 surge-protected outlets and a wall-tap plug. One USB-A port (2.4 Amp) and one USB-C port (15W) charge mobile, USB enabled devices. The P600WUCHD also features EMI/RFI noise filtering, an impact-resistant casing, and an integrated device shelf on top of the unit for convenient charging and cord management.

The P600WUCHD also features metal oxide varistor (MOV) technology, an EMI/RFI noise filter, and impact-resistant casing. This surge protector wall-tap comes with a One Year Limited Warranty and a Connected Equipment Guarantee.

### **TYPICAL APPLICATIONS**

- Mobile Devices
- · Personal Electronics
- Cell Phones
- Consumer Electronics

#### **FEATURES**

- Surge suppression: 500 J
- Volts: 125 V
- Circuit breaker: 15A
- Plug type: NEMA 5-15P
- · AC Outlets: 6
- Outlet type: NEMA 5-15R
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- USB-C charge ports: 1
- USB-C charge output: 15W
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$25,000



### **SPECIFICATIONS**

INPUT		
Cord Length	Wall-tap	
Plug Style	Wall-tap	
ОИТРИТ		
Outlet Type	6 NEMA 5-15R	
Outlets - Total	6	
USB Charge Port	Yes	
USB Charge Port Amperage	2.4 Amps (Shared)	
USB Charge Port Quantity	2	
USB Charge Port Type	1 Type A 1 Type C	
USB Charge Port Voltage	5 VDC	
USB Charge Port Watts	15 Watts	

SURGE PROTECTION AND FILTERING		
Attenuation	32 dB	
Coax Protection RG6	None	
EMI/RFI Filtration	150 KHz 100 MHz	
Maximum Surge Current H-N	800 A	
Response Time	<1 Nanosecond	
Surge Suppression (Joules)	500 J	
PHYSICAL		
Color	White	
Form Factor	Wall-tap	
Material of Construction	Plastic	

## P600WUCHD 6-OUTLET WALL-TAP WITH USB

## SPECIFICATIONS CONT.

DIMENSIONS	
Physical Dimensions - Width/Height/Depth (cm)	10.16 x 17.46 x 3.49 cm
Physical Dimensions - Width/Height/Depth (mm)	102 x 175 x 35 mm
Physical Dimensions - Width/Height/Depth (in.)	4 x 6.875 x 1.375 in.
Weight (kg)	0.27 kg
Weight (lb)	0.60 lbs.

Weight (ID)	0.00 105.
SHIPPING DIMENSIONS	
Shipping Dimensions - Width/Height/Depth (cm)	10.16 x 17.46 x 5.59 cm
Shipping Dimensions - Width/Height/Depth (mm)	101.6 x 174.63 x 55.88 mm
Shipping Dimensions - Width/Height/Depth (in)	4 x 6.875 x 2.2 in.
Shipping Weight (kg)	0.28 kg
Shipping Weight (lbs.)	0.61 lbs.

CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1449 3rd Edition	
WARRANTY		
CEG Amount	\$25,000	
Connected Equipment Guarantee	Lifetime	
Product Warranty	1-Year Limited Warranty	