SEKONIC Light Meter

SPEEDMASTER L-858D L-858D-U Operating Manual



Thank you for purchasing our product.

Please read the "Operating Manual" and "Safety Precaution" so that you will fully understand the features and operation of this product.

Then keep the operating manual in a safe place for future use.

Please see the Startup Guide for information about the basic operations.

Please read this operating manual thoroughly to gain a full understanding of the contents and ensure safe and correct use of this product.

The SPEEDMASTER L-858D is a photographic light meter with the following features:

- World's first^{*1} HSS (High Speed Sync) flash measurement
- Flash duration measurement
- Multi-brand wireless triggering & control (with optional transmitter)

The multi-function SPEEDMASTER L-858D is the flagship of the Sekonic family of light meters. Offering reflected-spot and incident light measurement of ambient and flash light sources, the L-858D features a host of new functions and operations to make it the perfect tool for all light measurement needs.

The color touch-screen panel is the control center of the ergonomic, rubber-cushioned body. Weatherproofing seals enable using the L-858D in all shooting conditions. Increased sensitivity and wide measuring range provide the high level of accuracy demanded for today's digital imaging.

Using the Sekonic-developed Data Transfer Software ² enables mapping your camera's exposure profile and tuning the L-858D to your shooting style. Up to 10 Exposure Profiles and tuning the L-858D to your shooting style. Up to 10 Exposure Profiles and tuning of the L-858D enables instant check scene and subject brightness against dynamic range of your camera for the very best exposure decisions. The Data Transfer Software also allows customizing the L-858D to your operating preferences.

URL: www.sekonic.com/support/downloads/dtssoftwareformacandwindows.aspx To use this software, connect your computer to the L-858D using a USB cable (micro-B type, available commercially).

An exposure profile contains information that indicates each characteristic feature (exposure compensation amount between the camera and light meter, clipping point, and dynamic range) of the digital camera you are using. To create the exposure profile, it is necessary to do shooting in advance, and use the Data Transfer Software.

World's first as a hand-held light meter (As of September, 2016, Investigated by SEKONIC.)

Download the Data Transfer Software from www.sekonic.com, and install it on your computer.

Terms and Trademarks

- Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.
- The official name of Windows is "Microsoft® Windows® Operating System".
- Macintosh and Mac OS are registered trademarks of Apple Computer, Inc. in the United States and/or other countries.
- Adobe Reader is a registered trademark of Adobe Systems Inc.
- broncolor[®] is the registered trademark of Bron Elektronik AG.
- Elinchrom is the registered trademark of Elinchrom SA.
- Godox[®] is the registered trademark of Godox Photo Equipment Co. Ltd.
- Phottix[®] is the registered trademark and Strato[™] is the trademark of Phottix Hong Kong Ltd.
- PocketWizard[®] is the registered trademark of LPA Design.

NOTICE

- The reproduction of all or any part of this document without permission is strictly forbidden.
- The product concerned and/or this manual may be subject to changes without prior notification
- The screens in this operating manual may differ from the actual displays of the meter you are using. (Colors, letters, etc.)
- The screens may differ depending on the setting of meter or optional accessory installed.

Safety Precautions

Before using this product, please read this "Safety Precautions" for proper operation.

⚠ WARNING	The WARNING symbol indicates the possibility of death or serious injury if the product is not used properly.
⚠ CAUTION	The CAUTION symbol indicates the possibility of minor to moderate personal injury or product damage if the product is not used properly.
NOTICE	The NOTICE symbol indicates cautions or restrictions when using the product. Please read all notes to avoid errors in operation.
NOTE	The reference symbol indicates additional information about the controls or related functions. Reading these is recommended.
→	The arrow indicates reference pages.



WARNING

- Infants or toddlers may accidentally wrap the strap around their neck, so please place it in a location out of their reach. There is a danger of suffocation.
- Infants or toddlers may accidentally swallow the lens cap, so please place it in a location out of their reach. There is a danger of suffocation.
- Do not look directly at the sun or an intense light source via the viewfinder. Doing so may damage your eyesight.
- Do not place batteries in open flames, attempt to short, disassemble or apply heat to them, use unspecified batteries, or recharge them (except rechargeable batteries). They may burst and cause fires, serious injury, or damage to the environment.

Polyvinyl Chloride (PVC) cable and cord notice

 Handling the cord on this product or cords associated with accessories sold with this product will expose you to lead, a chemical known to the State of California to cause cancer, and birth defects or other reproductive harm. Wash hands after handling.

CAUTION

- Do not handle this product with wet hands, or leave it in the rain or in a location where it may be splashed with water, submerged, or come into contact with moisture. There is a danger of electric shock if the "Cord Flash Mode" is used. This may also result in damage to the product.
- Make sure the Synchro terminal cover (1) and USB connector cover (1) are firmly in place when not using the meter in Cord Flash Mode or it is not connected to a computer. If not sealed by the covers, the meter is no longer water-resistant and moisture could damage the circuitry of the meter.
- Do not attempt to disassemble the product for modification or parts replacement. It may affect measurement results or damage the meter.
- Gently tap the meter's LED panel when changing modes or making selections. Using pointed pens or pencils may scratch the LCD screen or damage the product.
- Infants or toddlers may accidentally grab the strap and swing the product, so
 please place it in a location out of their reach, as the meter may be damaged
 by impacts.
- Be careful that the neck strap does not come loose when carrying the product, as the meter may be damaged when dropped.
- This neck strap is made of polyester fiber.
 Please refrain from using the product if synthetic fibers cause your skin to become irritated, inflamed or itchy in order to prevent worsening your symptoms.



Precautions for Operating

- A protective sheet is attached to the LCD. Peel it off before use.
- Although the LCD monitor is manufactured to very high standards with effective dots of 99.9%, it is possible to observe a few dead pixels on the screen. This is normal and not a malfunction of the meter.
- Do not use the meter in Cord Flash Mode at altitudes above 2,000m (6,561 feet).
- Our company shall not be liable for any data loss caused by, but not limited to, malicious acts and control errors.
- Be sure not to drop the meter or subject it to sudden impacts, as the meter will be damaged.
- Be careful not to transport the meter from cold to warm moist conditions as condensation will form on the meter and may damage it.
- If the meter is operated in temperatures below -10°C, the response of the LCD will
 greatly slow down and the display may be difficult to view and read. This will not harm
 the meter. Also, if the temperature exceeds 50°C, the liquid crystal display will darken
 and become difficult to read, but when it returns to room temperature it will return to its
 normal condition.

Precautions for Storage

- Do not store the meter in areas of high temperature of high humidity, as the meter will be damaged.
- If the meter is left in direct sunlight, a vehicle, or near a heater, the unit's temperature will
 rise and may result in damage. Please be careful when using the meter in these types of
 locations.
- If the meter is left where corrosive gases may be generated, the gases may affect the product and may result in damage. Please be careful when using the meter in these types of locations.
- In case of disposing the meter, follow the rules of disposal in your area.

Maintenance Notes

- Be careful not to let the Light Receptor become dusty, dirty, or scratched as this may
 affect the precision of the measurement.
- If the meter becomes dirty, wipe it with a dry, soft cloth. Never use organic solvents such as thinner or benzine.



- For used batteries, dispose of them according to the rules of your area, or bring them to a battery recycling shop near you.
- Insulate plus and minus terminals with tape or other insulation material.
- Do not disassemble the batteries.

Intended Usage

The meter is designed for:

- Measurement of artificial light sources or natural light for photo, video, or movie
- Display of latitude (dynamic range) from the shadow to the highlight of a digital camera
- Measurement of the flash high-speed synchro exposure or flash duration time for diversifying flash shooting
- Flash unit triggering and power control functions with the transmitter (sold separately)
- Measurement for all shooting situations from outdoor to indoor with all weather design.

Features of the L-858D

[Basic functions and performance]

- 1 Model with incident light and reflected light (spot photometry 1 degree) systems
- ② One-touch switching between extended lumisphere and retracted lumisphere (Light receiving part up-down mechanism)
- ③ Flash Analyzing Function which provides the percentage of flash in total exposure as well as ambient and flash components.
- Exposure Profile Function (using the Data Transfer Software application software)
- (s) Simplified luminance measurement (cd/m², Foot-lambert) and simplified illuminance measurement (Lux, Foot-candle)

[New functions and performance]

- ① 2.7-inch liquid-crystal color touch panel

 The operability is enhanced by assigning frequently used functions to Function Buttons at the bottom of the screen.
- ② Flash duration analysis (1/40 to 1/55,500 sec., t0.1 to t0.9, which can be changed in 0.1 steps)
- 3 Exposure measurement in HSS (High Speed Synchro) Mode
- ④ Improvement of lower light measurement performance (from -5 EV in incident light measuring, from -1 EV in reflected light measuring) (based on ISO100).
- (s) Flash units triggering and power control functions with multi-brands of the transmitter (sold separately)
- ⑤ Enhancement of video/cine functions such as frame rate setting (1 to 1,000 f/s), shutter angle setting (1 to 358 degrees), and filter compensation is possible. (+/-20 EV value, or select the desired option from the registered filter names.)

Intended Users

The intended users of this product are the following.

Those working in the areas of photography, filming, etc. such as photographers, videographers, and movie camera operators, gaffers, and cinematographers

Disclaimer

The Company shall not be liable for any direct or indirect damage resulting from the failure of this product or its use.

Restrictions

There are some cautions and restrictions regarding the use of this product. Please read and understand the following before using the meter.



- The contents of this manual may be subject to change for the product's specification
 modifications and other reasons without prior notice.
 We recommend that you download the latest operating manual from our website and use
 this product.
 - URL: https://sekonic.com/downloads/
- The safety-related precautions such as "Safety Guide and Maintenance" and "Safety Precautions" conform to the legal and industry standards that were applicable at the time this operating manual was created. Therefore, this manual may not contain the latest information. If you are using the previous operating manual, please download and refer to the latest operating manual.
- The product may contain printing materials such as cautions related to safety and/or printing errors as a supplement to the operating manual.
- The contents of this operating manual may be reproduced for non-commercial purposes and for personal use only. However, the reproduced material must contain the copyright notice of our company.
- The screens in this operating manual may differ from the actual displays of the meter you are using. (Colors, letters, etc.)

Accompanying Accessories

The following items are included with the meter in the package. Please be sure to check that all noted items are included.

- * If any items are missing, please contact the distributor or the reseller you purchased the meter from.
- * The USB cable (that has the A connector and Micro-B connector) is not included in the package. Please obtain this separately.
- * Batteries (two AA, Alkaline and manganese batteries are recommended) are not included in the package. Please obtain these separately.




Table of Contents

		l Trademarks	
	Safety Pre	cautions	ii
	• WARNI	NG	ii
	CAUTIO	ON	iii
	NOTICE		iv
	Intended U	Jsage	V
	Features of	of the L-858D	V
	Intended U	Jsers	vi
		T	
		18	
	Accompar	nying Accessories	vii
1.	Names a	and Functions of Parts	1
	1-1	Names of Parts	1
	1-2	Functions of Parts	2
2.	Before U	Jse	3
	2-1	Attaching the Strap	3
	2-2	Inserting the Batteries	4
	2-3	Power ON/OFF	5
	2-4	Auto Power Off Function	7
	2-5	Checking the Battery Capacity	8
	2-6	Replacing Batteries	8
3.	Screen	Operations	9
	3-1	Basic Operations	9
	3-2	Locking and Unlocking the Screen	13
	3-3	Screen Transition	14
	3-4	Screen Display	15
	3-4-1	Measuring Screen	15
	3-4-2	Measuring Operation/Display Area	18
	3-4-3	USB Connection Screen	23
	3-4-4	Viewfinder Display	24
	3-4-5	Tool Box Screen	26
	3-4-6	Menu Screen	29

4.	Basic O	perations	31
	4-1	Basic Measurement Workflow	31
	4-2	Switch the Light Receiving Method	32
	4-2-1	Incident Light System	32
		Using the Function Button for Setting	32
		2) Setting on the Tool Box Screen	34
		3) Interchanging the Extended Lumisphere and Retracted Lumisphere	35
	4-2-2	Reflected Light System	37
		1) Using the Function Button for Setting	37
		2) Setting on the Tool Box Screen	39
		3) Measuring Area	
		4) Diopter Scale Compensation	
		Setting the Measuring Button 3 and Memory Button 2	
	4-3	Selecting the Measuring Mode	44
5.	Measuri	ng	48
	5-1	Measuring in Ambient Light Mode	48
	5-1-1	T (shutter speed) Priority Mode	49
	5-1-2	F (Aperture) Priority Mode	51
	5-1-3	T+F (Shutter Speed/F-stop) Priority Mode	53
	5-1-4	HD CINE Mode	55
		1) Measuring	55
		2) Frame Rate Editing	58
	5-1-5	CINE Mode	61
		1) Measuring	61
		2) Frame Rate Editing	64
		3) Shutter Angle Editing	67
	5-1-6	Illuminance/Luminance Mode	70
		1) Illumination Measuring	70
		2) Luminance Measuring	72
	5-2	Measuring in Flash Light Mode	74
	5-2-1	Cordless Flash Mode	75
		1) Measuring	75
		2) Number of Pre-flash	78

	5-2-2	Cordiess Multiple (Cumulative) Flash Mode	80
		1) Measuring	80
		2) Multi Clear	84
		3) Number of Pre-flash	85
	5-2-3	Cord Flash Mode	87
	5-2-4	Cord Multiple (Cumulative) Flash Mode	89
		1) Measuring	89
		2) Multi Clear	91
	5-2-5	Radio Triggering Flash Mode	92
	5-2-6	Radio Triggering Multiple (Cumulative) Flash Mode	93
	5-3	HSS (High Speed Synchro) Flash Cordless Mode	94
	5-3-1	HSS (High Speed Synchro) Flash Cordless Mode	94
		1) Measuring	94
		2) Number of Pre-flash	96
	5-3-2	HSS (High Speed Synchro) Flash Radio Triggering Mode (for RT-GX only)	98
	5-4	Measuring in Flash Duration Analysis Mode	99
	5-4-1	Flash Duration Analysis Cordless Mode	99
		1) Measuring	99
		2) Number of Pre-flash	102
		3) Flash Duration Analysis t Value	104
	5-4-2	Flash Duration Analysis Code Mode	106
		1) Measuring	106
		2) Flash Duration Analysis t Value	109
	5-4-3	Flash Duration Analysis Radio Triggering Mode	111
	5-5	Out of Displayed Range or Measuring Range	112
	5-5-1	When Displayed Range Is Exceeded	112
		1) When Under Exposure "Under" Is Displayed:	112
		2) When Over Exposure "Over" Is Displayed:	112
	5-5-2	When Measuring Range Is Exceeded	113
3. F	unction	18	114
	6-1	Memory Function	114
		How to Save Values in the Memory	
		Memory Clear	
		Individual Clear	
		Collective Clear	
		_,	

6-1-3	Memory Recall	120
6-2	Average/Contrast Function	122
	1) Average Function	122
	2) Contrast Function	125
	3) Average/Contrast Function Setting on the Tool Box Screen	128
6-3	Exposure Compensation Function Minus Compensation	
	Plus Compensation	129
6-4	Filter Compensation Function	132
6-4-1	Input Filter Comp. Value	133
6-4-2	Selecting a Filter	135
6-4-3	User-defined Filter Compensation Settings	138
6-4-4	Deselecting a Filter	143
6-5	Mid. Tone Function	144
6-5-1	Mid. Tone Setting	144
	Set from Current Measurement	144
	2) Set from Memory	145
	3) Modify Current Mid. Tone	147
6-5-2	Mid. Tone Recall	149
6-5-3	Mid. Tone Clear	150
6-6	Exposure Profile Function	151
6-6-1	Overview of Exposure Profile Function	151
6-6-2	Set Exposure Profile	152
6-6-3	Edit Exposure Profile	153
	Display or not on the Set Exposure Profile Screen (Tool Box)	154
	2) Edit Exposure Profile	155
6-7	Custom Setting	161
6-7-1	Custom Setting List	162


	6-7-2	Custom Setting Procedure	165
		1) Function Button -1 Setting	166
		2) Function Button -2 Setting	168
		3) "Increments of T+F" Setting	169
		4) "Display of 1/10 Step Increments" Setting	171
		5) Compensation +/- Preference	172
		6) Setting for Switching the Measuring Button 3 and Memory Button 7	174
		7) Ambient Mode Setting	176
		8) Flash Mode Setting	178
		9) HSS Flash Mode Setting	180
		10) Flash Duration Analysis Mode Setting	182
		11) Additional Data Setting	184
		12) Illuminance/Luminance Unit SettingColor Theme Setting	186
		13) Color Theme Setting	188
		14) Auto Power Off Time Setting	190
		15) Backlight Brightness Setting	191
		16) Auto Dimmer Setting	192
		17) Memory Button	194
		18) Radio System Preference Setting	195
		19) Reset Custom Setting	196
7.	Hardwai	re Setting	198
		Hardware Setting Screen	
		User Calibration	
		Adjust Touch Panel	
		Factory Setting.	
		Edit User Information	
8.	Optiona	I Accessories	
		Synchro Cord	
		Exposure Profile Target II	
		Exposure Profile Target	
		Step-up Ring	
		RT-20PW	
		RT-3PW	
		RT-BR	
		■ RT-EL/PX	
		■ RT-GX	207


9. Various Setting Values	208	
9-1 ISO Sensitivity	208	
9-2 Shutter Speed	208	
9-3 F-stop (Aperture)	209	
9-4 Frame Rate	209	
9-5 Shutter Angle	209	
9-6 Filter Names and Compensation Values	210	
10.Specifications	211	
11.Legal Requirement	215	
12.Troubleshooting		
13.After-sales Services		

Retracted Mark

1. Names and Functions of Parts

1-1 Names of Parts





Functions of Parts 1-2

The following table lists the functions of each part.


No.	Part Name	Function
0	Lumisphere Retracting Ring	Turn this to switch between the extended lumisphere and retracted lumisphere. (→ P35)
2	Lumisphere	Position the meter at subject with Lumisphere facing toward camera or light source during measurement. Can be freely rotated through 270° to receive light. (▶ P32)
3	Objective Lens	For viewing reflected-light spot measurements of subjects or scenes. Attach the Step-up ring (sold separately) to mount a filter. (▶ P206)
4	Viewfinder Eyepiece (with diopter adjustment)	Turn the viewfinder eyepiece to adjust the diopter scale. (→ P40)
5	Power Button	Press to turn ON/OFF. (⇒P5)
6	Measuring Button*1	Press for measurement.
7	Memory Button ^{∸1}	Press after measuring to record the measured value. Press in Multiple (Cumulative) Flash Mode to clear the number of cumulative flashes.
8	Touch Panel LCD	Displays the setting screens and measurement screens. The built-in touch panel function enables setting, selection or operation by touching the displayed screens. (▶ P9)
9	Menu Button	Press to enter the Menu list from any of the screens. Press again to return to the previous screen. (▶ P29)
9	USB Connector	The USB connector for connecting to the computer with the installed Data Transfer Software. (Terminal shape: Micro B type)
0	USB Connector Cover	Protects USB terminal when not in use.
12	Synchro Terminal	Accepts an optional synchro cord when using meter in Cord Flash Mode.
B	Synchro Terminal Cover	Protects synchro terminal when not in use.
14	Battery Cover	Secures the batteries.
15	Battery Cover Latch	Pull out and rotate down to open battery cover.
16	Strap Eyelet	Attach the accessory strap here. (⇒ P3)
1	Tripod Socket Hole	Used to attach the meter to a tripod. (1/4 inch, 20 threads)
18	Transmitter (sold separately) Compartment	Install radio transmitter (sold separately) for the radio triggering of flash units. (▶ P92, P93, P111)
19	Transmitter Connector Cover	Protect the transmitter connector.*2
20	Battery Compartment	Hold 2x AA batteries. Insert as indicated in compartment. (⇒P4)
21	Lumisphere Lock Lever	Use this lever to replace the lumisphere (when it is damaged or contaminated).

The function of the Measuring Button of and that of the Memory Button of can be changed using Custom Setting. (→ P41, P174)
 Be sure to reattach the Transmitter Connector Cover of the Transmitter is removed.

2. Before Use

Attaching the Strap 2-1

- 1. Pass the strap (included) through the outer hole of the Strap Eyelet 66.
- 2. Pass the opposite end of the strap through the loop at the end of the strap.



WARNING


Infants or toddlers may accidentally wrap the strap around their neck, so please place it in a location out of their reach. There is a danger of suffocation.

CAUTION

- Infants or toddlers may accidentally grasp and swing the strap, so please place it in a location out of their reach. Otherwise, the meter may be damaged due to an impact shock.
- Be careful not to let the strap become entangled when carrying the meter. Otherwise, the meter may be damaged due to an impact shock that may occur when the meter is dropped, etc.
- This strap is made of polyester fiber. The synthetic fabric has caused skin irritation, redness, or itching. If you experience this, discontinue using strap.

2-2 **Inserting the Batteries**

- 1. Prepare two AA batteries.
- 2. Unlock the Battery Cover Latch (6), and remove the Battery Cover (6).
- 3. Insert the batteries according to the "+" and "-" symbols in the Battery Compartment 20.
- 4. Align the tabs (three locations) of the Battery Cover (1) to the holes of the meter. While pressing down the Battery Cover 4, use the Battery Cover Latch (5) to lock the Battery Cover (4).





WARNING

Do not place batteries in open flames, attempt to short, disassemble, apply heat to, or recharge them (except rechargeable batteries). They may burst and cause fires, serious injury, or damage to the environment.



CAUTION

- Use the manganese or alkaline batteries.
- Do not use batteries with any other rating than the one specified. Also, do not mix old and new batteries.
- To prevent corrosion of battery contact pieces or deterioration of the waterproof feature, exercise care to ensure that the rubber packing of the Battery Cover (1) is not contaminated with dust or sand.
- Please insert the batteries minus "-" side first. When removing the batteries, remove them plus "+" side first.
- If the meter will not be used for an extended period of time, it is recommended to remove the batteries to avoid possible damage caused by battery leaking.

2-3

Power ON/OFF


Power ON


1. Press the Power Button 5.

The meter turns on.

The Startup Screen appears on the LCD for one second.

Then operating assignment for the Measuring Button (3 (MEASURE) and Memory Button (7) (MEMORY) are displayed on the Measuring Screen for two seconds.





* Radio system brand of transmitter (sold separately) is displayed.



- The blue lettered "SEKONIC" Logo Screen is displayed after battery replacement and 24 hours after power OFF.
- The L-858D is executing a memory check while the blue progress bar is moving on the Logo Screen, so please do not turn OFF the power, as doing so may lead to damage.

SEKONIC

Progress Bar

 If the specifications of the transmitter (sold separately) are not compatible, the "Radio transmitter installed cannot be used in this meter." message is displayed.
 Check that the specifications of the transmitter are compatible with the meter before turning the power ON.
 See the manual for the transmitter (sold separately) for details.






- If the LCD screen shows no display, check if the batteries are installed properly (Pos/Neg positioning) and have enough capacity.
- The Startup display can be skipped by touching the screen when it appears.

Power OFF

1. Press the Power Button 5.

The meter will turn off and the display disappears.

The meter power turns off after the display disappears.





- Please wait 3 seconds between repeated power on and power off sessions.
- If the power is turned off, graphs displayed during the Flash Duration Analysis Mode will be erased.




When the batteries are removed or the meter is turned off, the stored settings and measured values are saved and will be displayed when batteries are installed and the meter is switched ON.

2-4 Auto Power Off Function

To save battery capacity, the meter will automatically turn off 5 minutes after the last button is pressed.




- All settings and measurements are saved in memory even after the meter has automatically turned off. When the power is turned ON, they will be displayed again.
- The graph displayed during the Flash Duration Analysis Mode will be erased at Auto power off or when the Power Button is used to turn the power off.
- Default Auto Power OFF is 5 minutes. Select longer time or No Auto Power OFF in Custom Setting. (→ P190)
- If, while in transport, the Power Button (5) is inadvertently and continually pressed in, the meter will turn ON for about 1 minute and then automatically turn OFF to save battery power.



2-5 Checking the Battery Capacity

When the power is turned ON, the LCD screen will show the battery capacity indicator.





- When battery power is low and the meter is turned ON, the LCD screen will appear, then
 turn off immediately. This is an indication that the batteries have been depleted and they
 should be replaced immediately.
 - It is recommended that spare batteries be kept on hand.
- When the meter is continuously used at room temperature, the battery should last 15 hours (based on Sekonic testing methods).

2-6 Replacing Batteries

- Always turn off the power before replacing batteries.
 If you replace batteries while the power is turned on, the measured values that are obtained during operations are not saved. Also, this may cause a failure.
- If an unexpected display appears on the LCD during battery replacement or measurement, i.e. settings other than selected, or if the meter does not respond when a button is pressed, remove the batteries, wait at least 10 seconds, and then re-install them.

3. Screen Operations

3-1 Basic Operations

The screen, which is based on the touch panel system, allows you to select a target menu or item by touching the icon with your fingertip.

- The LCD backlight is lit when the meter is turned on.
- The screen dims during measuring or cordless flash standby to eliminate its influence on measured values, with the exception of the case when measuring is carried out by the Contrast Function.
- The brightness of the LCD backlight is set to "Bright" by factory default to enhance the visibility for outdoor use. To reduce power consumption, specify "Standard" or "Dark" in Custom Setting. (⇒ P191)
- By factory default, the screen dims if the touch panel is not operated for approximately 20 seconds. (time can be adjusted in Custom Functions. (⇒ P192))

Touch operations

Touch each icon to change the display to a desired screen. (⇒ P44)

Measuring Screen



Measuring Mode Screen



* The screens may differ depending on the setting of meter or optional accessory installed.

If you touch the arrow icon (), you can increase the setting value or change to an item above.

If you touch the arrow icon (), you can decrease the setting value or change to an item below. Continuing touch of Setting Icon will successively change the setting value.

Measuring Screen



Slide operations

Slide a finger up or down on the setting value areas at any time to change setting values.

If a scroll bar is displayed on the screen, you can slide it to change the setting value.

Touch and move the slider to change the setting value on the scale.


Setting Value Areas 125 100 Scroll Bar | S0 80 | 3.5 | 2.5 | +0.0 | +2.5 | +3.5 | | ISO 100 | 3.5 | 2.5 | +0.0 | +2.5 | +3.5 | | ISO 125 | 3.5 | 2.5 | +0.0 | +2.5 | +3.5 | | Slider

Radio button operations

Touching a Radio button selects the item to the right of it.

Only one selection can be made at one time.

Set Filter Compensation Screen



Check box operations

Check boxes are displayed when multiple selections are available.

Touch the boxes for the desired items to select them.

Flash Mode Screen




Ambient Mode Screen



Numeric Value Input Screen

Numeric Value Input Screen



^{*} The Filter Compensation Value Input Screen is used as an example.

How to input a numeric value (Numeric Value Input Screen)

No.	Key	Description
1)	0-9, Decimal point, Sign (+/-)	Inputs a numeric value. When a key is touched, the input value is displayed at the top of the screen.
2	DEL	Deletes the input value.
3	ок	Confirms the input value, and returns to the previous screen.
4	Cancel	Cancels the input value, and returns to the previous screen.

Character Input Screen

Upper Case Input Screen



Lower Case Input Screen



Numeric Value Input Screen



How to input characters and numbers (Alphabet Input Screen and Number Input Screen)

No.	Key	Description
1	-	The cursor indicates the location at which to input a value.
2	ABC, abc, 0-9, Decimal point, Space, Hyphen	When touched, the input value is displayed at the top of the screen. Repeated touching of the same button for alphabet (ABC/abc) will change the alphabet character in order.
3	1/A/a	Shifts between numbers/upper case letters/lower case letters.
4	← →	Moves input position.
(5)	DEL	Deletes the character at the cursored position.
6	ОК	Confirms the input value, and returns to the previous screen.
7	Cancel	Cancels the input value, and returns to the previous screen.

3-2 Locking and Unlocking the Screen

You can lock the screen to prevent misoperation.

When the screen is locked, touch operation is disabled.

However, the Power Button **⑤** , Measuring Button **⑥** , and Memory Button **⑦** are still operational.

The screen will stay locked even when power is turned OFF and ON.

Measuring Screen (Lock)



Measuring Screen (For screen operations in locked state)



Measuring Screen (Unlock)




Lock

Press and hold down the Menu Button ② on the Measuring Screen to lock the screen (the [Locked] Icon will be displayed at the top right of the LCD screen).

Buttons and icons on the LCD (touch panel) cannot be operated while the lock is ON. If you touch the screen, the Screen Locked Icon appears. (at the center of screen)

Moreover, it is not possible to open the Menu Function by pressing the Menu Button 9.



Unlock

Press and hold down the Menu Button 9 again to release the locked screen (the [Locked] lcon will disappear).

Screen Transition 3-3

The basic screen transition is as follows.

A change in the Measuring Mode or settings can be made on the Measuring Screen.

Power ON

Startup Screen

Measuring Screen



Measuring Mode

The modes displayed can be selected in Custom Setting. (⇒ P176)

Set the Measuring Mode that matches your intended

- Ambient light
- Flash light
- HSS flash light
- · Flash duration analysis



Tool Box

Set, recall and clear meter/measuring functions to fit your needs.

- Set Average/Contrast Function
 Select Incident/Spot
- Set Exposure Compensation Set Filter Compensation
- Set Mid. Tone
- Mid Tone Recall
- Memory Clear
- Number of Pre-flash
- Flash Duration Analysis t Value
 Radio CH/Zone/Group

- · Mid. Tone Clear
- Set Exposure Profile
- Memory Recall
- Multi Clear



Menu



Menu Button 9

Menu Function

Select, edit, and customize meter operations and displayed measuring functions.

- Set Analog Scale
- Custom Setting
- Edit Exposure Profile
- Edit Frame Rate
- Edit Shutter Angle
- Edit Filter

View information about your meter.

- Product Information
- Regulation






While the meter's power is off, hold down the Menu Button (2), then press the Power Button (5) to display the Hardware Setting Screen.

- · User calibration of measured value
- Touch panel display position adjustment
- Reset to Factory settings (default settings)
- User information editing





3-4	Screen Display	
3-4-1	Measuring Screen	

When the power is turned on, the Measuring Screen is displayed after the Startup Screen has been displayed for one second.

Measuring Screen (Example in Radio Triggering Mode)



- * This example of the Measuring Screen shows all the items for explanation purposes. The values shown are not defaults.
- * The screens may differ depending on the setting of meter or optional accessory installed.

Measuring Screen item list


No.	Name	Description
1	Status Bar	Displays settings. (➡ P17)
2	[Measuring Mode] Icon	The Measuring Mode is displayed. (▶ P44) The display changes to the Measuring Mode Screen.
3	[Flash Control] Icon	Displayed when a transmitter (sold separately) is installed. (⇒ P92)
4	[Setting Value] Icon	You can specify the ISO sensitivity, shutter speed, aperture, etc. The setting value is displayed in the icon. The displayed icon varies depending on the Measuring Mode. (→ P19)
5	Radio Triggering Setting Display	Displays the channel or zone/group setting when a transmitter (sold separately) is installed. (▶P92)
6	Set Average/ Contrast Function Display	Displayed when the Set Average/Contrast Function is activated. (⇒ P122)
7	Flash Component	The percentage of flash light in the total exposure is displayed (in steps of 10%) (⇒ P74)

No.	Name	Description	
8	Measured Value/ Measuring Unit Display Area	Displays information such as measured values and measuring units. (⇒ P20)	
9	Measured Value (Additional Data) Displays the additional data for the measured value. (▶ P184)		
10	Display Incident/ Spot Displayed when "Select Incident/Spot" is not assigned to Function Button -1 or -2. (⇒ P33)		
11	Analog Scale	Displays various information such as measured values, exposure profiles, and flash or ambient light components for flash analyzing, depending on the Measuring Mode. (▶ P22)	
12	Function Button -1	Set the desired function to this Function Button. (➡P166)	
13	Function Button -2		
14	[Tool Box] Icon To make various settings for the current measurement, touch the [Tool Box] Icon on the Measuring Screen. (▶ P26)		

Function Button [Selectable in Custom Setting Menu]

Name	Icon/Button	Description
[Set Average/Contrast Function] Button	AVE / △EV	Set the Average/Contrast Function. Used with the Memory Function, displays the average of up to nine measured values. (♣ P122) The Contrast Function displays a difference between current value and memorized/averaged value when Measuring Button ③ is pressed. (Excluding the Multiple (Cumu.) Flash Mode)
[Select Incident/Spot] Icon		Set the light receiving method. (⇒ P32) Touch to switch between the Incident light (extended lumisphere or retracted lumisphere) and the reflected light (spot) measuring system.
[Set Exposure Compensation] Button	Comp.	Toggling In/Out set exposure compensation for measured value. (⇒ P129)
[Filter Compensation] Button	Filter	Toggling In/Out set filter compensation for measured value. (➡ P132)
[Mid. Tone] Button	Mid. Tone	Activate to set current value as Mid-Tone for comparison on Analog Scale. (➡ P144)
[All Memory/Multi Clear] Button	M. Clear	Clear all memorized data and multiple cumulative value. (➡ P194)

Status bar



* This example shows all the items for explanation purposes. The displayed information vary depending on settings.

Displayed item list


No.	Name		Description
	Battery Capacity Indicator Display	-	Full battery power remaining.
			Sufficient battery power remaining.
1			Low battery power remaining. Have spare batteries ready.
			Replace the batteries immediately.
2	Memory Count	M9	Displays the number of measurement data items saved in the memory. The total number of data items in the memory is displayed up to "9" on the right of the M symbol.
			Displays when Memory Button is set to "OFF"
3	Exposure Profile	Р	Appears when the exposure profile is set.
4	Exposure Compensation	ADJ +1.0	Appears when Exposure compensation (adjustment) is set for the measured value. The numeric value indicates the compensation value (+/-9.9 EV).
5	Filter Compensation	1 +20. 0	Appears when filter compensation is set for the measured value. The numeric value indicates the compensation value (+/-20.0 EV).
6	Key Locked Status Display	6	Appears when the Screen Lock Function is active. No touch panel operations are available when the screen is locked.
7	Multiple (Cumu.) Flash Mode/ Cumulative Count	<u>MLT</u> 99	Indicates that the Multiple (Cumulative) Flash Mode is selected. Cordless Multiple (Cumulative) Flash Mode Cord Multiple (Cumulative) Flash Mode Radio Triggering Multiple (Cumulative) Flash Mode This item is displayed on each Measuring Screen of the modes above. Cumulative count (up to 99) is displayed on the right of the MLT symbol. When the cumulative count exceeds the maximum, the value begins from "00" again.
8	Menu Title	-	Displays the screen title. (The title is displayed, excluding the Measuring Screen.)
9	Page Number	P1	Displays the page number when there are multiple screens.

3-4-2 Measuring Operation/Display Area


The measuring operation/display area consists of the following components:

- Measuring Mode Icon
- · Setting Value Icon
- · Measured value/measuring unit display area
- · Analog scale

Measuring Screen (Ambient T Priority Mode)



Measuring Screen (Ambient CINE Mode)



Measuring Mode Icon

Setting Value Icon

You can set the shutter speed, aperture, etc.

The setting value is displayed in the icon.

The displayed icon varies depending on the Measuring Mode.



Settings

Character	Description				
Т	Shutter speed Shutter speed is displayed in the following way. 30m (30 minutes), 8s (8 seconds), 125 (1/125 of a second)				
ISO	ISO sensitivity				
F	Aperture				
Ang	Shutter angle				
f/s	Frames per second (Frame rate)				

Operating the Setting Value Icon

If you touch the arrow icon (), the setting value increases.

If you touch the arrow icon (), the setting value decreases.

Slide the icon number up or down with your fingertip to increase or decrease the setting value.




* If you touch the Setting Value Icon while the HD CINE Mode or CINE Mode is enabled, the display is enlarged.




Measured value/measuring unit display area

Displays information such as measured values and measuring units.




Measuring Mode information display

- Ix : Ambient light illuminance Ix independent display
- cd/m²: Ambient light luminance (cd/m²) independent display



* If the light receiving method is changed from the incident light system to the reflected light system, the display is automatically changed from the Ambient Light Illuminance (Ix or fc) Mode to the Ambient Light Luminance (cd/m² or fl) Mode.





Fractions of a measured value can be displayed or hidden using the "Increments of T+F" in Custom Setting. (▶ P171)

Display in Measuring Screen

Fraction hidden

Fraction displayed


O. 4s

T. 1. 3m

T.

Analog scale

The analog scale displays the exposure setting for a current measurement and value relationships between two or more memorized measurements.



Measured value scale

Depending on the Measuring Mode, the following values will be displayed on the scale.


F value, T value, illuminance lx, luminance cd/m²



EV scale

This scale has two modes that can be selected: measured value scale and EV scale. You can switch between these two modes using the Menu Function.





Flash analyzing scale


The ambient light and flash light components are displayed on the analog scale when a flash light measurement is made. You can touch the scale to switch whether to display components or not. (▶ P74)





Mid tone scale

The scale color is changed when the Mid-Tone Mode is selected, and the clipping point and dynamic range are displayed. (▶ P144)



3-4-3 USB Connection Screen


The USB symbol is displayed on the screen whenever meter is connected to a computer via USB cable. Button and touch panel operations are disabled, excluding the Power Button 5.

Screen displayed when a USB storage drive is connected



3-4-4 Viewfinder Display

Viewfinder Display



Viewfinder item list

No.	Name	Description		
1)	Measured value display	Displays the measured value.		
2	Additional display	Displays the flash component ratio and the luminance symbol.		
3	Exposure compensation	Displays only the plus or minus sign when exposure compensation is set for the actually measured exposure value.		
4	Unit display	 The ratio of flash light to the total exposure is displayed as a percentage (in steps of 10%) Appears when the shutter speed is set in minutes. Appears when the shutter speed is set in seconds. Appears when the shutter speed is set with the cine frame rate. 		
(5)	Monitor value/ average value display area	 ▲ Appears when the monitor measurement is active. ▲ Appears when the average measurement is active or the standard value is specified for monitor measurement. 		



The viewfinder displays only measured values. The set value or additional data cannot be displayed.

Special Viewfinder display examples

 Shutter speeds higher that 1/1600s are abbreviated to the first digit and "k" multiplier symbol.

Example: 1/2,000s = 2k

Viewfinder Display

Units: k (x 1,000)

• In T+F priority, ISO numbers higher than ISO 160,000 as the first 3 digits and k multiplier symbol.


Example: ISO 204,800 = 204k Viewfinder Display




Units: k (x 1,000)

3-4-5 Tool Box Screen

Touch the [Tool Box] Icon () on the Measuring Screen to make the following settings.





- * When the Multiple (Cumu.) Flash Mode is selected, page 2 of the Tool Box Screen displays contents that are different from those shown above.
- * The setting of radio system is displayed on page 2 of the Tool Box Screen if a transmitter (sold separately) is installed.

Tool Box item list

No.	Name	Description	
1	Set Average/Contrast Function	Select ON or OFF. (⇒P122)	
2	Select Incident/Spot	Select the light receiving method (Incident/Spot). (→ P32)	
3	Set Exposure Compensation	Input an Exposure compensation value. The allowable exposure compensation range is -9.9 EV to +9.9 EV. (➡ P129)	
4	Filter Compensation	Set filter compensation (you can input the filter compensation value or select the filter name). The allowable filter compensation range is -20.0 to +20.0. (→ P132)	
5	Set Mid. Tone	Set the mid-tone (from the current measured value or memorized value) or edit the mid tone value. (▶ P144)	
6	Mid. Tone Clear	Delete the mid-tone value. (⇒ P150)	
7	Mid. Tone Recall	Recall the set mid-tone value. (⇒ P149)	
8	Set Exposure Profile	Select an exposure profile. (⇒ P152)	
9	Memory Clear ^{*1}	Delete the measured value that is saved in the memory. (Not displayed in the Multiple (Cumu.) Flash Mode.) (→ P117)	
10	Memory Recall ^{*1}	Recall the measured value that is saved in the memory. (Not displayed in the Multiple (Cumu.) Flash Mode.) (→ P120)	
11	Multi Clear ^{*1}	Clear the multiple flash reading. (Displayed in the Multiple (Cumu.) Flash Mode only.) (➡ P84, P91)	
12	Number of Pre-flash	Select the number of pre-flash cancellation times. (⇒ P78, P85, P96, P102)	
13	Flash Duration Analysis t Value	Select the analysis t value of the flash duration time. (⇒ P104, P109)	
14	Radio CH/Zone (Group)* ²	Select Radio channel and Zone (or Group). (➡ P92)	

^{*1} When the Multiple (Cumu.) Flash Mode is selected, the displayed information are different from those shown above.

^{*2} Displayed if a transmitter (sold separately) is installed. The contents may differ depending on the transmitter.


3-4-6 Menu Screen

Touch the Menu Button 9 to make the following settings. **Custom Setting Menu Analog Scale Screen** Screen Menu Button Custom Setting Menu P1 Analog Scale <<MFNU>> 9 Function Button -1 Heasurement Scale Function Button -2 1 1.4 2 2.8 4 5.6 8 11 16 22 32 45 64 90 Increments of T+F 10101010101010101 MENU Display of 1/10 Step Increments O EV Scale SPEEDMASTER L-858D 1 - - 1 - - 1 - - 1 - - 1 - - 1 Switching Measure , Memory Buttons Close Close Menu Screen **Edit Exposure Profile Edit Frame Rate** Page 1 Screen Screen Henu Edit Exposure Profile P1 Edit Frame Rate Set Analog Scale Default Profile Custom Setting 24(f/s) Edit Exposure Profile 2 🔲 Profile 1 2 🔲 24(f/s) Edit Frame Rate Profile 2 24(f/s) 3 🔲 3 🔲 5 Edit Shutter Angle Profile 3 24(f/s) Edit Filter Profile 4 5 🗍 24(f/s) Close **Edit Shutter Angle** [Close] Button Screen **Edit Filter Screen** Edit Shutter Angle P1 Edit Filter P1 Menu Screen 1 ☑ NDO. 3 Page 2 2 🗸 NDO. 6 2 🔲 180 Menu 3 ☑ NDO. 9 Product Information 180 4 ☑ CTO Double Regulation 180 **Product Information** 5 🔽 CTO Full Screen 180 6 ☑ CTO Three-Quarter Product Information Close Model Name L-858D Serial Numbe 8 JYXX-XXXXXX 01_01.000 User Information * The contents on the Regulation Unnamed Screen vary depending on the Radio Transmitter PocketWizard (433MHz) destination or whether a transmitter Close (sold separately) is installed.

Menu item list

No.	Name	Description
1	Analog Scale	Set the display of the analog scale. (➡ P22)
2	Custom Setting Menu	Select a function or set and edit the displayed information. (⇒ P161)
3	Edit Exposure Profile	Edit exposure files created by Data Transfer Software on the meter side (about setting values and names). (→ P153)
4	Edit Frame Rate	Create up to 20 frame rates in addition to the standard frame rates. (➡ P58, P64)
5	Edit Shutter Angle	Create up to 20 shutter angles in addition to the standard shutter angles. (➡ P67)
6	Edit Filter	Set filter compensation up to 30 sheets (No. 1 to No. 30). The specified filter compensation values can be freely edited. (→ P132)
7	Product Information	Displays information such as the meter version.
8	Regulation	Displays the compatibility symbol (institutions) for the legal restrictions according to which the meter is licensed.


4. Basic Operations



4-2 Switch the Light Receiving Method

4-2-1 Incident Light System

The incident light system measures the light that is falling on the subject using the Extended lumisphere or Retracted Lumisphere Function. Point the lumisphere at the camera lens (lens optical axis) from a location close to the subject, then make a measurement.



1) Using the Function Button for Setting

- * This section describes how to switch the light receiving method from the reflected light system to the incident light system.
 - 1. Touch the [Function Button] Icon () on the Measuring Screen.

This changes the screen to the Select Incident/Spot Screen.

2. Touch the [Incident Light] Radio Button.

This changes the system to the incident light system, and the display returns to the Measuring Screen.





If you used Custom Functions to change the Function Button assignment, sellect Incident/Spot using the Tool Box Screen. (▶ P34)

Measuring Screen





Icon	Description
	Displayed when the extended lumisphere is selected for incident light.
	Displayed when the retracted lumisphere is selected for incident light.
4	Displayed when reflected light is selected.


2) Setting on the Tool Box Screen

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Select Incident/Spot] Button on the Tool Box Screen.

 The Select Incident/Spot Screen is displayed.
- 3. Touch the [Incident Light] Radio Button.

This changes the system to the incident light system, and the display returns to the Measuring Screen.

If you do not want to make any changes, touch the [Close] Button to return to the Measuring Screen.





Measurement values for the current Measuring Mode will be cleared when going to the Select Incident/Spot Screen.

3) Interchanging the Extended Lumisphere and Retracted Lumisphere

1. Extending Lumisphere


Extend the Lumisphere to measure the illumination of people, buildings, and other three dimensional subjects.

Rotate the top of the Lumisphere Retracting Ring ① to securely align the mark on the ring with the lumisphere mark ()).

2. Retracting Lumisphere

Retract the Lumisphere to measure the illumination of flat subjects such as manuscripts, books, or paintings, measure the illumination ratio (Contrast Function), and simply measure the illuminance.

Rotate the Lumisphere Retracting Ring 1 to securely align the mark on the ring with the retracted lumisphere mark ().





- Try to minimize your influence on the light measurement. Do not block the light falling on the subject with your hand or body. Do not allow light toned clothing to reflect light into the meter.
- Do not set the Lumisphere Retracting Ring 1 to an intermediate position. This will
 change the quality of the light and produce an incorrect measurement.
- Do not push down the Lumisphere 2 with your hand.
- Because it may affect the precision of the measurements, be careful not to damage or contaminate the Lumisphere ② . If the Lumisphere ② becomes dirty, wipe it with a dry soft cloth. Never use organic solvent such as thinner or benzene.



If the Lumisphere ② is damaged or stains cannot be removed, purchase a replacement of lumisphere for L-858 separately, and replace the defective lumisphere with the new one.


How to replace the Lumisphere Push down the Lumisphere Lock Lever (a). While holding both the upper and lower parts of Lumisphere Retracting Ring (1), turn the ring counterclockwise to remove the lumisphere unit.

2) How to attach the Lumisphere 2


Align the mark on the Lumisphere Retracting Ring 1 with the mark on the meter head, and press the lumisphere unit in the meter head. Then, turn the ring clockwise until it clicks into place.

- * Check to see that the Lumisphere Lock Lever 1 is engaged.
- * When attaching/detaching the Lumisphere 2, be sure not to touch the light receiving element inside the meter head.

Lumisphere Retracting Ring 1



Lumisphere Lock Lever 21



Light Receiving Element

4-2-2 Reflected Light System

Switch the light receiving method to the reflected light system to make a measurement. The reflected light system measures the brightness (luminance) of the light reflected from the subject. It is useful to meter distant objects such as landscapes, if you cannot go to the location of the subject, or to meter subjects that generate light (neon signs, etc.), highly reflective surfaces, or translucent subjects (stained glass, etc.). Although the reflected measurement is useful to see from the highlight to shadow, the measured value should be compensated to use as the proper exposure depending on the reflectance ratio. Reflected light measurements are made by aligning the circle in the viewfinder with the subject area to be measured at the camera position or in the camera direction.




1) Using the Function Button for Setting

- * This section describes how to switch the light receiving method from the incident light system to the reflected light system.
 - 1. Touch the [Function Button] Icon () on the Measuring Screen.

This changes the screen to the Select Incident/Spot Screen.

2. Touch the [Reflected Light (Spot)] Radio Button.

This changes the reflected light system, and the display returns to the Measuring Screen.





If you used Custom Functions to change the Function Button assignment, sellect Incident/Spot using the Tool Box Screen. (▶ P39)

Measuring Screen





Icon	Description
	Displayed when the extended lumisphere is selected for incident light.
	Displayed when the retracted lumisphere is selected for incident light.
4	Displayed when reflected light is selected.


2) Setting on the Tool Box Screen

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Select Incident/Spot] Button on the Tool Box Screen.

 The Select Incident/Spot Screen is displayed.
- 3. Touch the [Reflected Light (Spot)] Radio Button.

This changes the reflected light system, and the display returns to the Measuring Screen.

If you do not want to make any changes, touch the [Close] Button to return to the Measuring Screen.






Measurement values for the current Measuring Mode will be cleared when going to the Select Incident/Spot Screen.

3) Measuring Area

The measuring area is the inside of circle in the viewfinder.

The light receiving angle is 1 degree.



4) Diopter Scale Compensation

While looking through the viewfinder, adjust the diopter by rotating the Viewfinder Eyepiece ② so that the circle and digital display can be seen clearly. (The setting range is -2.5 to 1.0 D.)





WARNING

Be careful not to directly look at the sun or bright light sources during measurement.

This may cause a serious eye injury or lead to blindness.



<<Step-up ring>> (Accessory sold separately)

You can attach a filter to the objective lens side using the step-up ring (30.5 mm \rightarrow 40.5 mm). This allows you to determine the exposure without specifying the filter compensation value of the PL filter, etc., which is a burdensome task.




The step-up ring can also be used as a hood to protect the lens part from damage or dirt and prevent an incorrect measurement due to lens flare or glare. (▶ P206)

4-2-3 Setting the Measuring Button (a) and Memory Button (2)

You can change the Measuring Button **⑤** and Memory Button **⑦** using Custom Setting. (**⇒** P174)


When mainly using the incident light system
 "Switching Measure/Memory Buttons" is set to "Standard"
 in the Custom Setting menu. (→ P162)





Right after the setting is changed and returning to Measuring screen, or each time the meter is powered on, the assignment of the Memory and Measuring Buttons will be displayed for two seconds.








Right after the setting is changed and returning to Measuring screen, or each time the meter is powered on, the assignment of the Memory and Measuring Buttons will be displayed for two seconds.



3. When frequently using both the incident light and reflected light systems

In the incident light system, the button position can be changed automatically to the standard configuration. In the reflected light system, it can be changed automatically to the reverse configuration.

Select "Auto (Incident:Standard, Spot:Reverse)" in "Switching Measure/Memory Buttons" on the Custom Setting menu. (→ P174)



In Incident Light System

In Reflected Light System

4. When inactivating the Memory Button

"Memory Button" on the Custom Setting menu is set to "ON" (default setting). In case of inactivating Memory Button, select "OFF". (▶ P194)





Right after the setting is changed and returning to Measuring screen, or each time the meter is powered on, the assignment of the Memory and Measuring Buttons (5) will be displayed for two seconds.

In case that Memory Button is set to OFF, The icon of (appears on the status bar to show that Memory Button does not function.

Measuring Screen



4-3 Selecting the Measuring Mode

Select the desired Measuring Mode.



If you change the Measuring Mode, the measured value is cleared.

Touch the [Measuring Mode] Icon () on the Measuring Screen to display the Measuring Mode Screen. Here you can select any Measuring Mode to suit your light measuring needs.

* The screens may differ depending on the setting of meter or optional accessory installed. (▶ P162)





Measuring Mode Screen



Icons on the Measuring Mode Screen

Measuring Mode: Ambient Mode (⇒ P176)		
No.	Icon	Description
1	☆ τ	Ambient Light T (shutter speed) Priority Mode Displays F-stop value (aperture) for input shutter speed and ISO sensitivity. (→ P49)
2	☆ F	Ambient Light F (Aperture) Priority Mode Displays shutter speed value for input F-stop and ISO sensitivity. (→ P51)
3	☼ TF	Ambient Light T+F (Shutter Speed and Aperture) Priority Mode Displays ISO sensitivity for input shutter speed and F-stop value. (⇒ P53)
4	☆ 1 1 1 1 1 1 1 1 1 1	Ambient Light HD CINE Mode Displays F-stop value for input shutter speed, frame rate and ISO sensitivity. (→ P55)

(5)	₩ IENE	Ambient Light CINE Mode Displays F-stop value for input frame rate, ISO sensitivity, and shutter angle values. (➡ P61)
6	₩ lux	Ambient Light Illuminance lux Mode (Incident light measurement) Displays brightness value in lux (lx) unit. (⇒ P70)
	☆ fc	Ambient Light Illuminance fc Mode (Incident light measurement) Displays brightness value in foot-candle (fc) unit. (→ P70)
	☆ cd/m²	Ambient Light Luminance cd/m² Mode (Reflected light measurement) Displays brightness values in cd/m² unit. (⇒ P72)
	☆ fl	Ambient Light Luminance fl Mode (Reflected light measurement) Displays brightness value in foot-lambert (fl) unit. (♣ P72)



Ambient Light refers to natural light (sunlight) as well as continuous light like tungsten lamps and fluorescent lamps.

Mea	Measuring Mode: Flash Mode (⇒ P178)		
No.	lcon	Description	
7	3	Cordless Flash Mode Detects flash brightness without meter-flash connection after Measuring Button pressed to arm meter for 90 seconds and flash fired separately, and displays F-stop value for input shutter speed and ISO sensitivity. (▶ P75)	
8	∌ MLT	Cordless Multiple (Cumulative) Flash Mode Detects and accumulates flash brightness without meter-flash connection after Measuring Button pressed to arm meter for 90 seconds and flash fired separately, and displays F-stop value for input shutter speed and ISO sensitivity. (> P80)	
9	₹ c	Cord Flash Mode Detects flash brightness with synchro cord meter- flash connection, and displays F-stop value for input shutter speed and ISO sensitivity. (▶ P87)	
10	∮ c MLT	Cord Multiple (Cumulative) Flash Mode Detects and accumulate flash brightness with synchro cord meter- flash connection, and displays F-stop value for input shutter speed and ISO sensitivity. (>> P89)	
11)	3 _∀	Radio Triggering Flash Mode Detects flash brightness after Measuring Button is pressed to send radio transmitted signal to radio receiver connected to flash. Displays F-stop value for input shutter speed and ISO sensitivity (When a transmitter sold separately is installed). (→ P92)	



Radio Triggering Multiple (Cumulative) Flash Mode

Detects and accumulate flash brightness after Measuring Button is pressed to send radio transmitted signal to radio receiver connected to flash. Displays F-stop value for input shutter speed and ISO sensitivity (When a transmitter sold separately is installed). (\Rightarrow P93)

Measuring Mode: HSS Mode (⇒ P180)			
No.	lcon	Description	
(13)	≯ HSS	HSS (High Speed Synchro) Flash Cordless Mode Select this mode to measure the brightness of a flash activated in HSS (High Speed Synchro) Flash Mode. Detects flash brightness without meter-flash connection after Measuring Button pressed to arm meter for 90 seconds and flash fired separately, and displays F-stop value for input shutter speed and ISO sensitivity. (▶ P94)	
14)	≸ _∀ HSS	HSS (High Speed Synchro) Flash Radio Triggering Mode Select this mode to measure the brightness of a flash activated in HSS (High Speed Synchro) Flash Mode. Detects flash brightness after Measuring button is pressed to send radio transmitted signal to radio receiver connected to flash. Displays F-Stop value for input shutter speed and ISO sensitivity (When a transmitter sold separately is installed). (♣ P98)	

Measuring Mode: Flash Duration Analysis Mode (⇒ P182)		
No.	Icon	Description
15)	🗲 FDA	Flash Duration Analysis Cordless Mode Detects flash brightness without meter-flash connection after Measuring Button pressed to arm meter for 90 seconds and flash fired separately, and displays flash duration time, graph of flash waveform and F-stop value for input shutter speed and ISO sensitivity. (▶ P99)
16	∮ _c FDA	Flash Duration Analysis Cord Mode Detects flash brightness with synchro cord meter- flash connection, and displays flash duration time, graph of flash waveform and F-stop value for input shutter speed and ISO sensitivity. (▶ P106)
17	∮ γ FDA	Flash Duration Analysis Radio Triggering Mode Detects flash brightness after Measuring Button is pressed to send radio transmitted signal to radio receiver connected to flash. Displays flash duration time, graph of flash waveform and F-stop value for input shutter speed and ISO sensitivity (When a transmitter sold separately is installed). (▶ P111)




Flash refers to momentary light such as that produced by a flashlight or flash bulb.

Operation


- * This section describes how to switch from the Ambient T Priority Mode to the Ambient CINE Mode.
- 1. Touch the [Measuring Mode] Icon on the upper left of the screen.

 The Measuring Mode Screen is displayed.



2. Touch the desired icon on the Measuring Mode Screen.

Select the desired Measuring Mode. Then, the screen changes.



5. Measuring

5-1 Measuring in Ambient Light Mode

Continuous light like natural light (sunlight) as well as tungsten lamps and fluorescent lamps are measured in Ambient Light Mode.

The following measuring methods are available in Ambient Light Mode.

- T (shutter speed) priority
- · F (f-stop) priority
- T+F (EV) priority
- Illuminance Mode (Lux or Foot-candle) (in incident light measurement)
- Luminance Mode (cd/m² or Foot-lambert) (in reflected light measurement)



- Shutter speed and f-stop (aperture) values can be displayed in 1, 1/2 and 1/3 stop increments in Custom Setting. (⇒ P169)
- After taking a measurement, changing a setting value (ISO sensitivity, shutter speed, aperture, frame rate, or shutter angle) will display the corresponding measured value.
- Touching the [Average/Contrast Function] Button (at the bottom of the screen activates the Average Function. (P122)
- The Analog Scale display will change according to Measuring Mode, Incident/Reflected and Mid-Tone Mode selected as well as "Set Analog Scale" (Measurement Scale or EV Scale) in Menu list. (*) P22)
- If the reading is outside the display range or beyond the measuring range, change the aperture or adjust the brightness. (₱ P112)


5-1-1 T (shutter speed) Priority Mode

Displays the measured value (F-stop) for input ISO sensitivity and shutter speed values.

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 5. Set the shutter speed on the [T] Icon. (→ P208)

Measuring Screen



6. Press the Measuring Button **6** on the side of the meter to measure the light.

The measured value (F-stop) will be displayed.

While the Measuring Button of is being pressed, the meter measures continuously until the button is released.

When the Measuring Button **(3)** is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (**P** P22, P24)

Measuring Screen



Viewfinder Display (in reflected light measurement)



Measured Value (F-stop)


5-1-2 F (Aperture) Priority Mode

Displays the measured value (shutter speed) for input ISO sensitivity and F-stop values.

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.




3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♣ P32, P37)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 5. Set the aperture on the [F (f-stop)] Icon. (→ P208)

Measuring Screen



6. Press the Measuring Button **6** on the side of the meter to measure the light.

The measured value (shutter speed) will be displayed.

While the Measuring Button of is being pressed, the meter measures continuously until the button is released.

When the Measuring Button **(3)** is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (**P** P22, P24)

Measuring Screen



Viewfinder Display (in reflected light measurement)



Measured Value (Shutter Speed)

5-1-3 T+F (Shutter Speed/F-stop) Priority Mode


Displays the measured value (ISO sensitivity) for input shutter speed and F-stop values.

The T+F (Shutter Speed/F-stop) Priority Mode is useful for today's digital cameras when a fixed speed and aperture are desired and the ISO can be adjusted for appropriate exposure.

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon (property) on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♣ P32, P37)

- 4. Set the shutter speed on the [T] Icon. (→ P208)
- 5. Set the aperture on the [F (f-stop)] Icon. (→ P208)

Measuring Screen



6. Press the Measuring Button **6** to measure the light on the side of the meter.

The measured ISO sensitivity value will be displayed.

While the Measuring Button **(3)** is being pressed, the meter measures continuously until the button is released.

When the Measuring Button **(3)** is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (**P** P22, P24)

Measuring Screen



Viewfinder Display (in reflected light measurement)



Measured Value (ISO Sensitivity)



In the T+F (Shutter Speed/F-stop) Priority Mode, the ISO sensitivity (measured value) can be stored in the memory, but cannot be displayed on the scale.

5-1-4 HD CINE Mode


Displays the measured value (F-stop) for input shutter speed, ISO sensitivity and frame rate (f/s).

1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)

Touch the [ISO] Icon to expand it.

Slide the icon number up or down using your fingertip to set the measured value. The icon will return to its reduced size after the icon is not touched for a short time.



5. Set the frame rate on [f/s] Icon.

Touch the [f/s] Icon to expand it.

Slide the icon number up or down using your fingertip to set the frame rate.

The icon will return to its reduced size after the icon is not touched for a short time.



6. Set the shutter speed on the [T] Icon. (⇒ P208)

Measuring Screen



7. Press the Measuring Button 3 on the side of the meter to measure the light.

The measured value (F-stop) will be displayed.

While the Measuring Button 3 is being pressed, the meter measures continuously until the button is released.

When the Measuring Button o is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (▶ P22, P24)

Measuring Screen



Viewfinder Display (in reflected light measurement)




Measured Value (F-stop)




- There are 20 preset of frame rates that can be customized. (⇒ P58)
- The T value cannot be set lower than the selected frame rate.

2) Frame Rate Editing


In addition to the standard frame rates available in the meter, up to 20 frame rates can be customized and displayed in the Meter Screen. The stored frame rates can be edited as desired. (*P209)








- 2. Touch [Edit Frame Rate] Button to display the Edit Frame Rate Screen.
- 3. Touch [Frame Rate] Button to display the Frame Rate Screen.



- 4. Input a numeric value in the Input Frame Rate Screen. (⇒ P11)
- 5. Touch [OK] Button.

The display will return to the Edit Frame Rate Screen.

Touch the [Cancel] Button to return to the Edit Frame Rate Screen without changing the value.





- The frame rate is set in steps of 0.001 (f/s) within a range from 0.001 to 99,999.999 (f/s). (→ P209)
- The frame rate is not displayed if its box is unchecked.

6. Check the box of the desired frame rate.

Touch the box (\square) to check it \checkmark (check mark \boxtimes). The checked frame rate is displayed after 1,000f/s on the Measured Screen. When the box is unchecked, it is deselected.

Edit Frame Rate Screen P1 Edit Frame Rate 24(f/s) The input numeric 2 🗸 119.88(f/s) value is displayed. Check Box -24(f/s) 24(f/s) 24(f/s) Close [Close] Button To next page **Measuring Screen Measuring Screen** 250 250

- 7. Touch [Close] Button on the Edit Frame Rate Screen.
 The display returns to the Menu Screen.
- 8. Touch [Close] Button on the Menu Screen.
 The display returns to the Measuring Screen.



5-1-5 CINE Mode


Displays the measured value (F-stop) for input frame rate (f/s), ISO sensitivity and shutter angle (Ang).

1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)

Touch the [ISO] Icon to expand it.

Slide the icon number up or down using your fingertip to set the measured value. The icon will return to its reduced size after the icon is not touched for 3 seconds.



5. Set the shutter angle on the [Ang] Icon.

Touch the [Ang] Icon to expand it.

Set the shutter angle under this condition.

The icon will return to its reduced size after the icon is not touched for 3 seconds.



6. Set the frame rate on the [f/s] Icon. (→ P209)

Slide the icon number up or down using your fingertip to set the frame rate.



7. Press the Measuring Button 6 on the side of the meter to measure the light.

The measured value (F-stop) will be displayed.

While the Measuring Button 3 is being pressed, the meter measures continuously until the button is released.

When the Measuring Button o is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (▶ P22, P24)

Measuring Screen



Viewfinder Display (in reflected light measurement)



Measured Value (F-stop)



- There are 20 preset of frame rates that can be set at "Edit Frame Rate" in the MENU list. (⇒ P64)
- There are 20 preset of shutter angles that can be set at "Edit Shutter Angle" in the MENU list. (⇒ P67)
- The T value cannot be set lower than the selected frame rate.

2) Frame Rate Editing

In addition to the standard frame rates available in the meter, up to 20 frame rates can be customized and displayed in the Meter Screen. The stored frame rates can be edited as desired.



Page 1 Page 2 Page 3 Edit Frame Rate Edit Frame Rate Edit Frame Rate 24(f/s) 24(f/s) 24(f/s) 6 🗌 11 🔲 24(f/s) 7 🔲 24(f/s) 24(f/s) 24(f/s) 24(f/s)

24(f/s)

24(f/s)



Page 4

To next page To next page [Close] Button To previous page

Operation

24(f/s)

24(f/s)


Close

5 🔲

1. Press the Menu Button
on the meter to open the Menu Screen.




- 2. Touch [Edit Frame Rate] Button to display the Edit Frame Rate Screen.
- 3. Touch [Frame Rate] Button to display the Frame Rate Screen.



- 4. Input a numeric value in the Input Frame Rate Screen. (⇒ P11)
- 5. Touch [OK] Button.

The display will return to the Edit Frame Rate Screen.

Touch the [Cancel] Button to return to the Edit Frame Rate Screen without changing the value.





- The frame rate is set in steps of 0.001 (f/s) within a range from 0.001 to 99,999.999 (f/s). (→ P209)
- The frame rate is not displayed if its box is unchecked.

6. Check the box of the desired frame rate.

Touch the box (\square) to check it \checkmark (check mark \boxtimes). The checked frame rate is displayed after 1000f/s on the Measured Screen. When the box is unchecked, it is deselected.

Edit Frame Rate Screen P1 Edit Frame Rate 24(f/s) The input numeric 2 🗸 119.88(f/s) value is displayed. Check Box-24(f/s) 24(f/s) 24(f/s) Close [Close] Button To next page **Measuring Screen Measuring Screen**



- 7. Touch [Close] Button on the Edit Frame Rate Screen.

 The display returns to the Menu Screen.
- 8. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.




3) Shutter Angle Editing

In addition to the standard shutter angles available in the meter, up to 20 shutter angles can be customized and displayed in the Meter Screen. The input shutter angle can be edited as desired.



Edit Shutter Angle Screen



Operation

1. Press the Menu Button 9 on the meter to open the Menu Screen.



2. Touch the [Edit Shutter Angle] Button.

The Edit Shutter Angle Screen is displayed.

3. Touch the [Shutter Angle] Button.

The Input Shutter Angle Screen is displayed.




[Shutter Angle] Button

4. Input a numeric value on the Input Shutter Angle Screen. (⇒ P11)

5. Touch [OK] Button.

The display will return to the Edit Shutter Angle Screen.

Touch the [Cancel] Button to return to the Edit Shutter Angle Screen without changing the value






- Shutter angle is set in steps of 0.001° within a range from 0.001 to 360°.
- The frame rate is not displayed if its box is unchecked.

6. Check the box corresponding to the desired shutter angle.

Touch the box (\square) to check it \checkmark (check mark \boxtimes). The checked shutter angle is displayed after Ang 358 on the Measuring Screen. When the box is unchecked, it is deselected. When checked (check mark \boxtimes), an arrow is displayed above Ang 358.

Edit Shutter Angle Screen





7. Touch the [Close] Button on the Edit Shutter Angle Screen.

The display returns to the Menu Screen.

The added shutter angle is displayed at the end of the sequence on the Measuring Screen.

8. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.



5-1-6 Illuminance/Luminance Mode

Illuminance is measured using the Incident Light Mode, and luminance is measured using the Reflected Light (Spot) Mode.

The following are the units that can be set. Select the Illuminance/Luminance Unit in the Custom Setting. (→P161)

Incident light measurement (Illuminance)	Lux (Unit: lx)	(⇒ P70)
	Foot-candle (Unit: fc)	
Reflected light measurement (Luminance) cd/m²	Candela per square meter (Unit: cd/m²)	(⇒ P72)
	Foot-lambert (Unit: fl)	



Any calibration or exposure compensation will not be in effect when measuring illuminance or luminance.

1) Illumination Measuring

Operation


- 1. Switch the light receiving method to incident light. (⇒ P32)
- 2. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 3. Touch the icon (or or or on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



4. Switch to the retracted lumisphere.

If extended lumisphere is selected, rotate the Lumisphere Retracting Ring 1 to switch to the retracted lumisphere () position.





- 5. Point the light receptor directly toward the light source.
- **6.** Press the Measuring Button **6** on the side of the meter to measure the light.

The measured illuminance will be displayed in lux (measured value).

While the Measuring Button 3 is being pressed, the meter measures continuously until the button is released.


When the Measuring Button of is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (▶ P22)

Measuring Screen

800 lx

100 200 300 400 500 600 700 800 300 1000

AVE /



Measuring Screen


71

2) Luminance Measuring

Operation

- 1. Switch the light receiving method to reflected light. (⇒ P37)
- 2. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 3. Touch the icon (or or on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



4. While looking through the viewfinder, press the Measuring Button on the side of the meter to measure the light.


While looking through the viewfinder, locate the subject area to be measured within the finder circle.

Press the Measuring Button **(3)**, and the luminance will be displayed in Candelas square meter (measured value).


While the Measuring Button 3 is being pressed, the meter measures continuously until the button is released.

When the Measuring Button **(3)** is released, the measurement is completed. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (**P** P22, P24)

Measuring Screen







Measured Value (cd/m²)

Measured Value (fl)



WARNING

Do not look directly at the sun or an intense light source via the viewfinder. Doing so may damage your eyesight.



While looking through the viewfinder, adjust the diopter by rotating the Viewfinder Eyepiece (with diopter adjustment) 4 so that the circle can be seen clearly.



5-2 Measuring in Flash Light Mode

Flash illumination is light that is produced by the very brief light pulse of an electronic flash unit or flash bulb. Flash measurement is available in the following modes:

- · Cordless Flash Mode
- Cordless Multiple (Cumulative) Flash Mode
- Cord (PC) Flash Mode
- Cord Multiple (Cumulative) Flash Mode
- Radio Triggering Flash Mode *Available when a transmitter (sold separately) is installed
- Radio Triggering Multiple (Cumulative) Flash Mode *Available when a transmitter (sold separately) is installed

Screen Display Details


When flash light is measured, f-stop (Ambient brightness + Flash brightness = total exposure) is displayed on the screen.

The ratio of flash light to the total exposure is displayed in steps of 10%.

The analog scale displays the ambient component (orange line) and flash component (blue line).

Example: As shown in the screen below, if the shutter speed is 1/125s and ISO sensitivity is 100, the flash component and ambient light component will be 50%, respectively. The analog scale displays the measured value of both the flash component (blue) and the ambient component (orange), and the photo becomes a little yellowish if the tungsten light is used as the ambient light.

Measuring Screen example in Cordless Flash Mode





- Shutter speed and f-stop (aperture) values can be displayed in 1, 1/2 and 1/3 stop increments in Custom Setting. (→ P169)
- After taking a measurement, changing a setting value (ISO value or shutter speed) will
 display the corresponding aperture.
- The Analog Scale display will change according to Measuring Mode, Incident/Reflected and Mid-Tone Mode selected as well as "Set Analog Scale" (Measurement Scale or EV Scale) in Menu list. (→ P22)
- If the reading is out of the display range or beyond the measuring range, change the aperture or adjust the brightness. (➡ P112)

5-2-1 Cordless Flash Mode


The meter detects flash brightness without meter-flash connection after Measuring Button of pressed to arm meter for 90 seconds and flash fired separately. The measured value (F-stop) for input shutter speed and ISO sensitivity is displayed. It is used when the synchro cord will not reach because of the distance between the flash and meter, or when use of synchro cord is inconvenient.

1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 5. Set the shutter speed on the [T] Icon. (⇒ P208)

Measuring Screen





Make sure that the settings are within the specifications of the camera and flash system.

6. Press the Measuring Button **6** .

The meter will enter the Measuring Standby Mode, and the [Measuring Mode] Icon () will blink for 90 seconds.

The LCD screen dims and stands by.


Measuring Screen



7. Trigger the flash unit manually while the [Measuring Mode] Icon (3) is blinking.

When the flash light is detected, the measurement is made automatically and the measured value (F-stop) is displayed.

Measuring Screen





- In case of the following, please follow "5-2-3 Cord Flash Mode". (→ P87)
 - When firing the flash, if the flash brightness is lower than the ambient light, the meter may fail to detect the light.
 - Rapid start fluorescent lamps and special lighting are sometimes mistaken for flash and accidentally measured.
 - Even if the flash is not fired, when a sudden light change occurs in the light receptor, measurement may be made.
 - The waveform of a flash bulb has a slight slope and there is a possibility that the light meter cannot recognize the flash bulb in Cordless Flash Mode.
 - When shooting with faster shutter speed than the camera's synch speed in the dark environment.



- In the Cordless Flash Mode, the backlight of the LCD screen dims and is only illuminated for three seconds after measurement.
- After the measurement, the meter enters the 90-second Measuring Standby Mode again.
 If you need to measure again, fire the flash during this time.
- If the measured values are stored in the memory, the Measuring Standby Mode is canceled.
- If the icon stops blinking before the flash fires, repeat Steps 6 and 7.
- To stop the Measuring Standby Mode, just touch the screen.
- It is convenient to set the light meter in a fixed position during the measuring time. This
 can be accomplished by mounting the meter on a tripod or stand using the tripod socket
 on the bottom of the meter.

2) Number of Pre-flash

For red-eye prevention and auto-flash light adjustment, some devices can pre-flash before main flash burst.

With the normal setting, the light meter will measure the pre-flash bursts and not the main flash burst. To take a successful reading, activate the pre-flash feature in the Tool Box.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Number of Pre-flash].

This button is enabled if Flash Mode is selected. If it is grayed out, check the Measuring Mode.

3. Touch the [Number of Pre-flash] Button of the Tool Box.

The Number of Pre-flash Screen is displayed.

If you do not change this number, touch the [Close] Button.




4. Touch the radio button of the [Number of Pre-flash] Button.

Set the number of pre-flash on the Number of Pre-flash Screen.

The display returns to the Measuring Screen.

If you do not change this number, touch the [Close] Button to return to the Measuring Screen.

Number of Pre-flash Screen





Normally the burst of pre-flash is once, but it can be different for each device in use. Please check the operation manual of your device to know the number of the pre-flash.

5-2-2 Cordless Multiple (Cumulative) Flash Mode

This Measuring Mode is used when the light generated by the flash at one time is inadequate for the desired F-stop setting. Repeated flash pops can be accumulated until the desired F-stop value is displayed.

When the Measuring Button **6** is pressed, the light meter is set to the Standby Mode (90 seconds) and makes a measurement by activating the flash. Each time the flash fires, the measured value (F-stop) for input shutter speed and ISO sensitivity is displayed.


The cumulative count is infinite. Up to 99 times is displayed in the Status/Title field, however, the cumulative count returns to 0(zero) for more than 100 times (0=100, 1=101, 2=102, etc.).

1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 5. Set the shutter speed on the [T] Icon. (→ P208)

Measuring Screen





Make sure that the settings are within the specifications of the camera and flash system.

6. Press the Measuring Button **6** .

The meter will enter the Measuring Standby Mode, and the [Measuring Mode] Icon () will blink for 90 seconds.

The LCD screen dims and stands by.


Measuring Screen



7. Trigger the flash unit manually while the [Measuring Mode] Icon () is blinking.

When the flash light is detected, the measurement is made automatically and the measured value (F-stop) and cumulative count are displayed. Repeat triggering the flash unit until the desired F-stop is displayed during the Standby Mode.

Measuring Screen





- In case of the following, please follow "5-2-4 Cord Multiple (Cumulative) Flash Mode". (⇒ P89)
 - When firing the flash, if the flash brightness is significantly lower than the ambient light, the meter may fail to detect the light.
 - Rapid start fluorescent lamps and special lighting are sometimes mistaken for flash and accidentally measured.
 - Even if the flash is not fired, when a sudden light change occurs in the light receptor, measurement may be made.
 - The waveform of a flash bulb has a slight slope and there is a possibility that the light meter cannot recognize the flash bulb in Cordless Flash Mode.
 - When shooting with faster shutter speed than the camera's synch speed in the dark environment.
- The EV scale cannot be displayed in this Measuring Mode.



- In the Cordless Multiple (Cumulative) Flash Mode, the backlight of the LCD screen dims and is only illuminated for three seconds after measurement.
- After the measurement, the meter enters the 90-second Measuring Standby Mode again.
 If you need to measure again, fire the flash during this time.
- If the Memory Button is pressed in Measuring Standby Mode, Measuring Standby Mode is canceled.
- If Memory Button is pressed when it is not in Measuring Standby Mode, the multiple cumulative value and count are cleared.
- If the icon stops blinking before the flash fires, repeat Steps 6 and 7.
- To stop the Measuring Standby Mode, just touch the screen.
- It is convenient to set the light meter in a fixed position during the measuring time. This
 can be accomplished by mounting the meter on a tripod or stand using the tripod socket
 on the bottom of the meter.

2) Multi Clear

Clears the multiple cumulative count.



- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Multi Clear].

This button is only enabled during measurement.

If the button is grayed out, the multiple cumulative measurement is not made and the count cannot be cleared.

3. Touch the [Multi Clear] Button of the Tool Box.

The multiple cumulate value is cleared, and the display returns to the Measuring Screen.

If you do not change the value, touch the [Close] Button. The display returns to the Measuring Screen.





When the Measuring Standby Mode is canceled and when the Measuring Button (3) is pressed again, the measuring will start with a cumulative count of "0".

3) Number of Pre-flash

For red-eye prevention and auto-flash light adjustment, some devices can pre-flash before main flash burst.

With the normal setting, the light meter will measure the pre-flash bursts and not the main flash burst. To take a successful reading, activate the pre-flash feature in the Tool Box.

Operation


- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Number of Pre-flash].

This button is enabled if Flash Mode is selected. If it is grayed out, check the Measuring Mode.

3. Touch the [Number of Pre-flash] Button of the Tool Box.

The Number of Pre-flash Screen is displayed.

If you do not change this number, touch the [Close] Button.




4. Touch the radio button of the [Number of Pre-flash] Button.

Set the number of pre-flash on the Number of Pre-flash Screen.

The display returns to the Measuring Screen.

If you do not change this number, touch the [Close] Button to return to the Measuring Screen.

Number of Pre-flash Screen





Normally the burst of pre-flash is once, but it can be different for each device in use. Please check the operation manual of your device to know the number of the pre-flash.


5-2-3 Cord Flash Mode

A synchro cord (sold separately) is used to connect the flash to the meter. Use this Cord Flash Mode when you need to ensure synchronization with the flash or use a flash bulb. After pressing the Measuring Button 6, the meter trigger the flash unit and displays F-stop value for input shutter speed and ISO sensitivity.

Operation

- 1. Connect the synchro cord (sold separately), which is connected to the flash, to the meter. (→ P205)
- 2. Touch the [Measuring Mode] Icon on the Measuring Screen.

The Measuring Mode Screen is displayed.



Synchro Terminal (1)

3. Touch the icon () on the Measuring Mode Screen.

When it is selected, the display changes to the Measuring Screen.



4. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

- 5. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 6. Set the shutter speed on the [T] Icon. (⇒ P208)

Measuring Screen






Make sure that the settings are within the specifications of the camera and flash system.

7. Press the Measuring Button 6.

The flash will fire and the measured value (F-stop) will be displayed.

Measuring Screen





- When the synchro cord is connected to the Synchro Terminal ② or when the meter's Power Button ③ is operated, the flash may fire.
- Also, the flash may not fire when the trigger voltage is very low. In such a case, follow "5-2-1 Cordless Flash Mode". (⇒ P75)

5-2-4 Cord Multiple (Cumulative) Flash Mode

This Measuring Mode is used when the light generated by the flash at one time is inadequate for the desired F-stop setting. Repeated flash pops can be accumulated until the desired F-stop value is displayed. Each time the flash fires, the measured value (F-stop) for input shutter speed and ISO sensitivity is displayed. The cumulative count is displayed in the Status/Title field. The cumulative count is infinite. Up to 99 times is displayed in the Status/Title field, however, the cumulative count returns to 0(zero) for more than 100 times (0=100, 1=101, 2=102, etc.).


1) Measuring

Operation

- 1. Connect the synchro cord (sold separately), which is connected to the flash, to the meter. (→ P205)
 - Connect the synchro cord (sold separately) to the meter's Synchro Terminal p.
- 2. Touch the [Measuring Mode] Icon on the Measuring Screen.

The Measuring Mode Screen is displayed.


Synchro Cord (sold separately)



Synchro Terminal (1)

3. Touch the icon () on the Measuring Mode Screen.

When it is selected, the display changes to the Measuring Screen.



4. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

5. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)

6. Set the shutter speed on the [T] Icon. (→ P208)

Measuring Screen






Make sure that the settings are within the specifications of the camera and flash system.

7. Press the Measuring Button 6.

The accumulated measured value (F-stop) and the number of cumulative flashes will be displayed. Press the Measuring Button ③ until the desired F-stop is displayed.





- Also, the flash may not fire when the trigger voltage is very low. In such a case, follow "5-2-2 Cordless Multiple (Cumulative) Flash Mode". (→ P80)
- The EV scale cannot be displayed in this Measuring Mode.



If Memory Button 7 is pressed, the multiple cumulative value and count are cleared.

2) Multi Clear

Clears the multiple cumulative count.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Multi Clear].


This button is only enabled during measurement.


If the button is grayed out, the multiple cumulative measurement is not made and the count cannot be cleared.

3. Touch the [Multi Clear] Button of the Tool Box.

The multiple cumulate value is cleared, and the display returns to the Measuring Screen.

If you do not change the value, touch the [Close] Button. The display returns to the Measuring Screen.






5-2-5 Radio Triggering Flash Mode

(Available when a transmitter sold separately is installed)

The meter detects flash brightness after Measuring Button ③ is pressed to send radio transmitted signal to radio receiver connected to flash. Displays F-stop value for input ISO sensitivity and shutter speed. Depending on the radio system in use, the meter controls the output power of flash units and the modeling lamps with turning ON/OFF. For details, see the operating manual of the transmitter (sold separately). (▶ P206)




5-2-6 Radio Triggering Multiple (Cumulative) Flash Mode

(Available when a transmitter sold separately is installed)

This Measuring Mode is used when the light generated by the flash at one time is inadequate for the desired F-stop setting. Repeated flash pops can be accumulated until the desired F-stop value is displayed.

The meter detects flash brightness after Measuring Button ③ is pressed to send radio transmitted signal to radio receiver connected to flash. Each time flash fires, the measured value (F-stop) for input ISO sensitivity and shutter speed is displayed. In Multiple (Cumulative) Flash Mode, Multiple (Cumulative) measurement is not available in Flash Power Control Screen and Modeling Lamp Power Control Screen (Only the single measurement is available).

For details, see the operating manual of the transmitter (sold separately).(⇒ P206)





If Memory Button 7 is pressed, the multiple cumulative value and count are cleared.

5-3 HSS (High Speed Synchro) Flash Cordless Mode

Measures the HSS (High Speed Synchro) or FP flash.

HSS (High Speed Synchro) Flash measurement is available in the following modes:

- · HSS (High Speed Synchro) Flash Cordless Mode
- HSS (High Speed Synchro) Flash Radio Triggering Mode (with RT-GX installed)

5-3-1 HSS (High Speed Synchro) Flash Cordless Mode


Select this mode to measure the brightness of a flash activated in HSS (High Speed Synchro) Mode. Press the Measuring Button **6** without a meter-flash connection. When the flash brightness is detected, the measured value (F-stop) for input shutter speed and ISO sensitivity is displayed.

1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

 When it is selected, the display changes to the Measuring Screen.



3. Set the light receiving method.

Switch to the incident light, extended lumisphere (♠)/retracted lumisphere (♠), or reflected light. (♦ P32, P37)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (→ P208)
- 5. Set the shutter speed on the [T] Icon. (→ P208)

Measuring Screen





Make sure that the settings are within the specifications of the camera and flash system.

6. Press the Measuring Button 6.

The meter will enter the Measuring Standby Mode, and the [Measuring Mode] Icon () will blink for 90 seconds.


The LCD screen dims and stands by.

Measuring Screen



7. When the [Measuring Mode] Icon () is blinking, release the shutter button of the camera that is set to HSS Flash Mode to fire the flash unit. When the flash light is detected, the measurement is made automatically and the measured value (F-stop) is displayed.

Measuring Screen





- In the HSS Cordless Flash Mode, the backlight of the LCD screen dims and is only illuminated for three seconds after measurement.
- After the measurement, the meter enters the 90-second Measuring Standby Mode again. If you need to measure again, fire the flash during this time.
- If the measured values are stored in the memory, the Measuring Standby Mode is canceled.
- If the icon stops blinking before the flash fires, repeat Steps 6 and 7.
- To stop the Measuring Standby Mode, just touch the screen.
- It is convenient to set the light meter in a fixed position during the measuring time. This
 can be accomplished by mounting the meter on a tripod or stand using the tripod socket
 on the bottom of the meter.

2) Number of Pre-flash

For red-eye prevention and auto-flash light adjustment, some devices can pre-flash before main flash burst.

With the normal setting, the light meter will measure the pre-flash bursts and not the main flash burst. To take a successful reading, activate the pre-flash feature in the Tool Box.

Operation

1. Touch the [Tool Box] Icon () on the Measuring Screen.
The Tool Box Screen is displayed.

2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Number of Pre-flash].

This button is enabled if Flash Mode is selected. If it is grayed out, check the Measuring Mode. (→ P45)

3. Touch the [Number of Pre-flash] Button of the Tool Box.

The Number of Pre-flash Screen is displayed.

If you do not change this number, touch the [Close] Button.




4. Touch the radio button of the [Number of Pre-flash] Button.

Set the number of pre-flash on the Number of Pre-flash Screen.

The display returns to the Measuring Screen.

If you do not change this number, touch the [Close] Button to return to the Measuring Screen.

Number of Pre-flash Screen





Normally the burst of pre-flash is once, but it can be different for each device in use. Please check the operation manual of your device to know the number of the pre-flash.


5-3-2

HSS (High Speed Synchro) Flash Radio Triggering Mode (for RT-GX only)

(Available when a RT-GX transmitter (sold separately) is installed)

Select this mode to measure the brightness of a flash activated in HSS (High Speed Synchro) The meter detects flash brightness after Measuring Button ③ is pressed to send radio transmitted signal to radio receiver connected to flash. Displays F-stop value for input ISO sensitivity and shutter speed. Depending on the radio system in use, the meter controls the output power of flash units and the modeling lamps with turning ON/OFF. This measuring mode is available only when the RT-GX (sold separately) is installed on the meter.

For details, see the operating manual of RT-GX.(→ P207)



5-4 Measuring in Flash Duration Analysis Mode

In the Flash Duration Analysis Mode, F-stop, flash duration time and graph of flash waveform can be measured for input shutter speed and ISO sensitivity. Flash Duration Analysis is performed with incident light Measuring Mode only. Flash duration measurement is available in the following modes:

- Flash Duration Analysis Cordless Mode
- Flash Duration Analysis Cord Mode
- Flash Duration Analysis Radio Triggering Mode *Available when a transmitter (sold separately) is installed

5-4-1 Flash Duration Analysis Cordless Mode

The meter detects flash brightness without meter-flash connection after Measuring Button of pressed to arm meter for 90 seconds and flash fired separately. The measured value (F-stop), flash duration time and graph of flash waveform are displayed.


1) Measuring

Operation

- 1. Touch the [Measuring Mode] Icon on the Measuring Screen.
 The Measuring Mode Screen is displayed.
- 2. Touch the icon () on the Measuring Mode Screen.

When it is selected, the display changes to the Measuring Screen.

If the Reflected Light Mode is set, the Flash Duration Analysis Mode cannot be selected. Before switching to the Measuring Mode Selection Screen, set the light receiving method to the incident light and select the Flash Duration Analysis Mode.



3. Set the light receiving method.

Incident light system Switch to the extended lumisphere (♠)/retracted lumisphere (♠). (♦ P32)

- 4. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 5. Set the shutter speed on the [T] Icon. (⇒ P208)

Measuring Screen





- Make sure that the settings are within the specifications of the camera and flash system.
- If the measured flash duration time is longer than the input shutter speed, an appropriate F-stop cannot be measured. The yellow "Under" indication appears.
 In this case, slower the shutter speed than the flash duration time and measure again.

Measuring Screen




- 6. Set the Flash Duration Analysis t value. (⇒ P104)
- 7. Press the Measuring Button 6.

The meter will enter the Measuring Standby Mode, and the [Measuring Mode] Icon () will blink for 90 seconds. The LCD screen dims and stands by.

8. Trigger the flash unit manually while the [Measuring Mode] Icon () is blinking.

When the flash light is detected, the measurement is made automatically and the measured value (F-stop) will be displayed.

Measuring Screen



NOTICE

- In case of the following, please follow "5-4-2 Flash Duration Analysis Code Mode".
 (⇒ P106)
 - When firing the flash, if the flash brightness is lower than the ambient light, the meter may fail to detect the light.
 - Rapid start fluorescent lamps and special lighting are sometimes mistaken for flash and accidentally measured.
 - Even if the flash is not fired, when a sudden light change occurs in the light receptor, measurement may be made.
 - The waveform of a flash bulb has a slight slope and there is a possibility that the light meter cannot recognize the flash bulb in Cordless Flash Mode.
 - When shooting with faster shutter speed than the camera's synch speed in the dark environment.
- The flash duration time and graph are displayed in the Flash Duration Analysis Mode, however, they cannot be stored in the memory.
 - They are cleared if the Measuring Mode is changed or the POWER switch is turned OFF.
- The incident light measurement can only be used in Flash Duration Analysis Mode.
- During 90 Seconds Standby Mode, the meter receives and measure the flash light only once, and does not enter the Standby Mode. Repeat the procedure 7. and 8. above to measure again and manually trigger the flash units.



 When the measured value display area is touched, both flash waveform graph and measured value are displayed. When it is touched again, the display returns to the previous screen.

Measuring Screen Mode Flash Waveform Graph Screen 10.5 1/474 2, 11ms F 168 Measured value area changes the display.

* The Graph Screen cannot be used to make measurements.

Flash Duration Analysis Cordless

- Measure the flash light characteristics in a darkroom without ambient light.
- When using a pre-flashing light, set the [Number of Pre-flash] of the Tool Box. (⇒ P102)
- It is convenient to set the light meter in a fixed position during the measuring time. This
 can be accomplished by mounting the meter on a tripod or stand using the tripod socket
 on the bottom of the meter.

2) Number of Pre-flash

For red-eye prevention and auto-flash light adjustment, some devices can pre-flash before main flash burst.

With the normal setting, the light meter will measure the pre-flash bursts and not the main flash burst. To take a successful reading, activate the pre-flash feature in the Tool Box.

Operation


- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Number of Pre-flash].

This button is enabled if Flash Mode is selected. If it is grayed out, check the Measuring Mode.

3. Touch the [Number of Pre-flash] Button of the Tool Box.

The Number of Pre-flash Screen is displayed.

If you do not change this number, touch the [Close] Button.




4. Touch the radio button of the [Number of Pre-flash] Button.

Set the number of pre-flash on the Number of Pre-flash Screen.

The display returns to the Measuring Screen.

If you do not change this number, touch the [Close] Button to return to the Measuring Screen

Number of Pre-flash Screen





Normally the burst of pre-flash is once, but it can be different for each device in use. Please check the operation manual of your device to know the number of the pre-flash.

3) Flash Duration Analysis t Value

The t value can be set in steps of 0.1 at a range of 0.1 to 0.9.

The measuring range of the flash duration time varies depending on the set t value.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Flash Duration Analysis t Value].

This button is enabled if Flash Duration Analysis Mode is selected. If it is not grayed out, check the Measuring Mode.

3. Touch the [Flash Duration Analysis t Value] Button of the Tool Box.

The Flash Duration Analysis t Value Screen is displayed.


If you do not change this number, touch the [Close] Button.



4. Input the "Reference" of 0.1 to 0.9 by touching the numeric value.

The t value can be set in steps of 0.1 at a range of 0.1 to 0.9.

The first "0." is fixed. Input the first digit decimal only. (To set "0.1", input "1".)



5. Touch [OK] Button.

The setting is input, and the display returns to the Measuring Screen.

Touch the [Cancel] Button to return to the Measuring Screen without making the modification.

Measuring Screen





Two rules apply to the reference flash duration time.

t0.5 = Effective flash duration time

t0.1 = Total flash duration time

After flash firing, the time at which the maximum intensity drops by half is called "t0.5". The time at which the maximum intensity drops to 1/10 is called "t0.1".

Generally, "t0.5" is called the flash duration time.



5-4-2 Flash Duration Analysis Code Mode


Press the Measuring Button **(i)** with a meter-flash connection. When the flash brightness is detected, F-stop, flash duration time and graph of flash waveform are measured for input shutter speed and ISO sensitivity.

1) Measuring

Operation

- 1. Connect the synchro cord (sold separately), which is connected to the flash, to the meter. (⇒ P205)
 - Connect the synchro cord (sold separately) to the meter's synchro terminal ${\bf @}$.
- 2. Touch the [Measuring Mode] Icon on the Measuring Screen.

The Measuring Mode Screen is displayed.






Synchro Terminal (12)

- 3. Touch the icon () on the Measuring Mode Screen.
 - When it is selected, the display changes to the Measuring Screen.

If the Reflected Light Mode is set, the Flash Duration Analysis Mode cannot be selected. Before switching to the Measuring Mode Selection Screen, set the light receiving method to the incident light and select the Flash Duration Analysis Mode.



4. Set the light receiving method.

Incident light system Switch to the extended lumisphere (♠)/retracted lumisphere (♠). (♦ P32)

- 5. Set the ISO sensitivity value on the [ISO] Icon. (⇒ P208)
- 6. Set the shutter speed on the [T] Icon. (⇒ P208)

Measuring Screen





- Make sure that the settings are within the specifications of the camera and flash system.
- If the measured flash duration time is longer than the input shutter speed, an appropriate F-stop cannot be measured. The yellow "Under" indication appears.
 In this case, slower the shutter speed than the flash duration time and measure again.

Measuring Screen



- 7. Set the Flash Duration Analysis t value. (⇒ P109)
- 8. Press the Measuring Button 6.

The flash will fire and the measured value (F-stop) will be displayed.

Measuring Screen







- The flash duration time and graph are displayed in the Flash Duration Analysis Mode, however, they cannot be stored in the memory.
 They are cleared if the Measuring Mode is changed or the POWER switch is turned OFF.
- The incident light measurement can only be used in Flash Duration Analysis Mode.
- Also, the flash may not fire when the trigger voltage is very low. In such a case, follow "5-4-1 Flash Duration Analysis Cordless Mode". (→ P99)



 When the measured value display area is touched, both flash waveform graph and measured value are displayed. When it is touched again, the display returns to the previous screen.



- * The Graph Screen cannot be used to make measurements.
- Measure the flash light characteristics in a darkroom without ambient light.
- The measurement can be started immediately after pressing the measurement button, and the total flash firing time can be accurately measured.
 In this Flash Duration Analysis Cord Mode, the measured value may differ depending on the flash waveform and analysis t value because measurement is started after sensing the flash light.



Cord Flash Mode

Cordless Flash Mode

Time lag until the start of measurement

2) Flash Duration Analysis t Value

The t value can be set in steps of 0.1 at a range of 0.1 to 0.9.

The measuring range of the flash duration time varies depending on the set t value.

Operation


- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Next Page] Icon () of the Tool Box to display the Tool Box showing [Flash Duration Analysis t Value].

This button is enabled if Flash Duration Analysis Mode is selected. If it is not grayed out, check the Measuring Mode.

3. Touch the [Flash Duration Analysis t Value] Button of the Tool Box.

The Flash Duration Analysis t Value Screen is displayed.


If you do not change this number, touch the [Close] Button.



4. Input the "Reference" of 0.1 to 0.9 by touching the numeric value.

The t value can be set in steps of 0.1 at a range of 0.1 to 0.9.

The first "0." is fixed. Input the first digit decimal only. (To set "0.1", input "1".)



5. Touch [OK] Button.

The setting is input, and the display returns to the Measuring Screen.

Touch the [Cancel] Button to return to the Measuring Screen without making the modification.

Measuring Screen






Two rules apply to the reference flash duration time.

t0.5 = Effective flash duration time

t0.1 = Total flash duration time

After flash firing, the time at which the maximum intensity drops by half is called "t0.5". The time at which the maximum intensity drops to 1/10 is called "t0.1".

Generally, "t0.5" is called the flash duration time.




5-4-3 Flash Duration Analysis Radio Triggering Mode

(Available when a transmitter sold separately is installed)

The meter detects flash brightness after Measuring Button **6** is pressed to send radio transmitted signal to radio receiver connected to flash. Displays the measured value (F-stop) for input ISO sensitivity and shutter speed, flash duration time and graph of flash waveform. Depending on the radio system in use, the meter controls the output power of flash units and the modeling lamps with turning ON/OFF.

For details, see the operating manual of the transmitter (sold separately). (→ P206)



5-5 Out of Displayed Range or Measuring Range

5-5-1 When Displayed Range Is Exceeded

Depending on the setting value, "Under" or "Over" is displayed if the measured value exceeds the display range even if it is within measuring range. In these cases, take the following actions.

Under Exposure display



Viewfinder Display



Over Exposure display



Viewfinder Display



1) When Under Exposure "Under" Is Displayed:

If "Under" is displayed when the measured value is lower than the minimum value, slower the shutter speed, set higher ISO sensitivity or increase the flash brightness to measure it again.

The correct F-stop will be displayed for input values.

2) When Over Exposure "Over" Is Displayed:

If "Over" is displayed when the measured value is higher than the maximum value, faster the shutter speed, set lower ISO sensitivity or reduce the flash brightness to measure it again.

The correct F-stop will be displayed for input values.




The setting value for each measurement mode is different. For the setting values, refer to each measurement mode in "5. Measurement" (➡ P48).

5-5-2 When Measuring Range Is Exceeded

When the amount of light is out of the measuring range of the meter, "Over" and "Under" will appear and blink.

If using the flash unit which the light output can be changed, adjust the brightness level and measure again.





Display Range

ISO sensitivity ISO 3 to ISO 13,107,200 (in 1/3 steps)

Shutter speed Ambient light 30 min to 1/64,000 sec, 1/200, 1/400

(in 1, 1/2, 1/3 steps)

Flash light 30 min to 1/16,000 sec, 1/75, 1/80, 1/90, 1/100,

1/200, 1/400 (in 1, 1/2, 1/3 steps)

Aperture F0.5 to F128.9 (in 1 steps)

F0.5 to F152.4 (in 1/2 steps) F0.5 to F161.2 (in 1/3 steps)

Flash duration time 1/40 to 1/55,500 sec (25 ms to 18 us)

Measuring Range (ISO100)

Ambient light Incident light system -5EV to EV22.9

Reflected light system -1EV to EV24.4

Flash light Incident light system F0.5 to F128.9

Reflected light system F1.0 to F128.9

Illuminance 0.1 to 2,000,000 lx Luminance 0.1 to 980,000 cd/m²

6. Functions

6-1 Memory Function

This meter can save measured values in the memory. This function is available in the following Measuring Modes.

Ambient Mode

- T Priority Mode
- · F Priority Mode
- TF Priority Mode
- HD CINE Mode
- CINE Mode

Flash Mode

- Cord in (PC) Mode
- · Cordless Mode
- Radio Triggering Mode

HSS Flash Mode

- HSS Flash Cordless Mode
- HSS Flash Radio Triggering Mode

You can save (in the memory) and recall up to nine measured values regardless of whether the incident light system or reflected light system is selected.



- When you have used the incident light system to save measured values in the memory
 and then changed the system to the reflected light system, the measured values that
 are saved in the memory using the incident light system are maintained. Then, you can
 newly display measured values saved in the memory using the reflected light system.
- In Ambient Mode, the measured values saved in the memory are maintained even if the mode is switched.
 - In Flash Mode, the measured values saved in the memory are not maintained if the mode is switched.
- If the memory button is disabled in the custom setting, the memory value does not remain.

6-1-1 How to Save Values in the Memory

Operation

1. Press the Measuring Button 6.

The measured value at that time will be displayed.

In Ambient Mode, while the Measuring Button (3) is held down, the meter continues to make measurements.


When the Measuring Button of is released, the measurement ends. The measured value at that time will be displayed in the measured value/measuring unit display area and on the analog scale. (> P22, P24)

2. Press the Memory Button 2.

The measured value is saved in the memory. The measured value saved in the memory is displayed as a dot on the analog scale.

3. Repeat Steps 1 and 2.

This meter can store up to nine measured values in the memory.





The Memory Function cannot be used in the following Measuring Modes.

- Cordless Multiple (Cumulative) Flash Mode
- Cord Multiple (Cumulative) Flash Mode
- Radio Triggering Multiple (Cumulative) Flash Mode
- Illuminance/Luminance Measuring Mode
- Flash Duration Analysis Cordless Mode
- Flash Duration Analysis Cord Mode
- Flash Duration Analysis Radio Triggering Mode



Memory count warning

Up to nine measured values can be saved in the memory. If you attempt to save a 10th or subsequent measured value, the "Memory Full" warning message will be displayed, and the measured value cannot be saved in the memory.

Measuring Screen



• Memory button ON/OFF

The memory button can be disabled in a custom setting. When the memory button is set to "OFF", (▶■■) is displayed on the status bar. (▶ P194)


Measuring Screen



6-1-2 Memory Clear

This function individually or collectively clears measured values that are saved in the memory. The Memory Clear Screen displays memory information (memory count, incident light () or reflected light (), and measured value) in the order in which they are saved in the memory.

Measured values that are saved in the memory are displayed as dots () on the analog scale.



1) Individual Clear

Operation

1. Select the memory value to be deleted on the Memory Clear Screen.

Multiple memory values are selectable.

2. Touch [Clear] Button.

This changes the display to the Selected Memory Clear Confirmation Screen, and the "Selected memory is cleared. Are you sure?" message is displayed.

When you touch [Close] Button, the display returns to the Measuring Screen without clearing the memory value.


3. Touch [OK] Button.

The selected item is cleared, and the display returns to the Memory Clear Screen. The contents are displayed without a space.

When you touch [Cancel] Button, the display returns to the Memory Clear Screen without clearing the memory value.

4. Touch [Close] Button on the Memory Clear Screen.

The display returns to the Measuring Screen.



2) Collective Clear

The measured values that are saved in the memory can be cleared collectively.

Operation

1. Touch [ALL] Button on the Memory Clear Screen.

This changes the display to the All Clear Confirmation Screen, and the "All memory is cleared. Are you sure?" message is displayed.

2. Touch [OK] Button.


All the memory values are cleared, and the display returns to the Measuring Screen.

When you touch [Cancel] Button, the display returns to the Memory Clear Screen without clearing the memory value.




6-1-3 Memory Recall

This function recalls the measured values that are saved in the memory to enable the user to view details. This screen displays memory information (memory count, incident light (\bigcirc) or reflected light (\bigcirc), and measured value) in the order in which they are saved in the memory. Measured values that are saved in the memory are displayed as dots (\bigcap) on the analog scale.



4. Touch the item to be recalled.

Contents saved in the memory are displayed on the Measuring Screen. (Green background)





- In Ambient Mode, the measured values saved in the memory are maintained even if the mode is switched. Values saved in the memory in each Measuring Mode are displayed in the value type corresponding to the measurement mode in which memory recall was carried out.
 - Example: When an ISO value is saved in the memory in TF Priority Mode, if it is recalled in T Priority Mode, the f-stop value is displayed.
- As the setting value is changed on the Memory Recall Screen, the measured value (memory recall value) is also changed.

 Setting Value

 Recall Screen

 Beauty 2 Recall

 F 4 0 3

5. Touch [Memory Recall] Button.

If you touch [Memory Recall] Button on the Recall Screen to display another memory value, the display returns to the Memory Recall Screen.


If you touch [Close] Button, the display returns to the Measuring Screen instead of returning to the Memory Recall Screen.

6. Touch [Close] Button.

If you touch [Close] Button, the display returns to the Measuring Screen instead of returning to the Memory Recall Screen.

7. Touch [Close] Button on the Memory Recall Screen.

The display returns to the Measuring Screen.



6-2 Average/Contrast Function

1) Average Function

This function averages up to nine measured values that are saved in the memory, and displays the result. This function is available in Ambient Mode (T Priority, F Priority, TF Priority, HD CINE, and CINE Mode), Flash Mode (Cord, Cordless, and Radio Triggering), and HSS Flash Mode.


Operation

1. Press the Measuring Button 6.

Press this button to make a measurement.

2. Press the Memory Button 2.

The measured value is saved in the memory. Each measured value that is saved in the memory is displayed as a dot (\prod) on the analog scale.




3. Repeat Steps 1 and 2.

Up to nine measurements can be stored in the memory. The memory count is displayed on the status bar.

4. Touch the [Set Average/Contrast Function] Button ().

The "Ave" symbol appears on the screen. The average of all memory values is displayed.

When the Average Function is active, the measured value is in yellow and the [Set Average/Contrast Function] Button () is highlighted ().





- The Average Function can be used only in the modes that the memory function is valid
- The [Set Average/Contrast Function] Button is set to Function Button -1 Button in Factory Setting. When the [Set Average/Contrast Function] Button is not displayed, set the Function Button in Custom Setting (⇒ P166), or set the Average/Contrast Function on the Tool Box Screen (⇒ P128).
- 5. Touch the [Set Average/Contrast Function] Button () again.

 The Average Function is released, and the highlighted Button () returns to the normal state (). Then, the "Ave" symbol disappears from the screen.

 The last measured value is displayed.





In case that the Average/Contrast Function is assigned to Function Button -1 or -2. (→ P166)

Button	Description
AVE / ⊿EV	Displayed when no measured or memorized values are registered.
AVE / ⊿EV	Displayed when the Set Average/Contrast Function is disabled.
AVE / ⊿EV	Displayed when the Set Average/Contrast Function is enabled.

2) Contrast Function

This function can be used in ambient light (T priority, F-stop priority, TF priority, HD CINE, CINE, Illuminance/Luminance mode), flash light (Cord Flash, Cordless Flash, Radio Triggering Flash mode), and HSS flash mode.

This function is useful for checking studio lighting or illumination unevenness. This function is also convenient when you check the difference in luminance between the intermediate value and the highlight and/or shadow value for landscape shooting. While you are holding down the Measuring Button ③ at the comparison position after defining the measured value at a specific point as the standard value, a difference between the standard value and the value at the comparison position is displayed with an EV value (difference in stops), and the current measured value is displayed on the analog scale.

* If there are no values in the memory, the standard value will be the last measured value. If there are values in the memory, the standard value will be the average of all values (up to nine readings) saved in the memory.

The example of lighting ratio using the Contrast Function

(In T Priority Mode in the incident light system)

When you want to measure the lighting ratio between the main and second light sources, lower the lumisphere to use the Retracted Lumisphere Function.

Operation

1. Rotate the Lumisphere Retracting Ring 1 .

Turn the Lumisphere Retracting Ring 1 to aligh the dot to the retracted mark () position.

Only the light source can be measured by setting the light receptor to the retracted lumisphere.

2. Turn ON the main light source only.

Turn OFF the second light source.


3. Press the Measuring Button 6.

Point the light receptor at the main light source from the subject position to make a measurement



4. Touch the [Set Average/Contrast Function] Button ().

When the Contrast Function is active, the measured value is in yellow and the [Set Average/Contrast Function] Button () is highlighted ().



[Set Average/Contrast Function] Button

The Contrast Function is active.

5. Turn ON the second light source only.

Turn OFF the main light source.

6. Hold down the Measuring Button 6.


Point the light receptor at the second light source from the subject position to make a measurement. While holding down the Measuring Button \odot , the difference between the standard value of the main light source and the second light source being measured is displayed in white and in terms of an EV value.

7. Release the Measuring Button 6.

The Contrast Function is released. And the standard value is displayed at the position of the measured value area.

8. Touch the [Set Average/Contrast Function] Button () again.

The Contrast Function is cleared and the standard value in yellow returns to the measured value in white. The last measured value when the Measuring Button is released is displayed.



EV Difference of Measured Value	Illumination Ratio
1	2:1
1.5	3:1
2	4:1
3	8:1
4	16:1



- To determine the final exposure in the incident light system, turn on the main and sub light sources, and set the right receptor to the extended lumisphere. Then, point it at the optical axis of the camera to make a measurement.
- The [Set Average/Contrast Function] Button is set to Function Button -1 in Factory Setting. When the [Set Average/Contrast Function] Button is not displayed, set the Function Button in Custom Setting (→ P166), or set the Average/Contrast Function on the Tool Box Screen (→ P128).
- The Set Average/Contrast Function is only available in a mode in which the Memory Function is valid. (⇒ P114)
- When measuring the contrast ratio, use the EV scale to make it more visible.
- "Measurement" or "EV Scale" on the analog scale can be changed in Custom Setting.
 (⇒ P22)

3) Average/Contrast Function Setting on the Tool Box Screen

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Average/Contrast Function] Button on the Tool Box Screen.


The Set Average/Contrast Function Screen is displayed.

3. Touch the [ON] or [OFF] radio button or an area around an item name.

You can set the Average/Contrast Function to [ON] or [OFF].

If there are values in the memory, the standard value will be the average of all values saved in the memory. If there are no values in the memory, the standard value will be the last measured value. Standard value is in yellow.

When you touch either one, the display returns to the Measuring Screen.





Function is "ON" (When values in memory)

Case in which Average/Contrast Case in which Average/Contrast Function is "OFF" (When values in memory)

6-3 **Exposure Compensation Function**

This function is useful when compensation is necessary for highlight and/or shadow in reflected-light measurements.

The input value range is -9.9 EV to +9.9 EV in 0.1 step increments.

To use the Set Exposure Compensation Function, first specify the Measuring Mode (incident light system or reflected light system). Exposure Compensation can be set individually in the incident light system and the reflected light system.

Minus Compensation

If a lighter image is obtained when shooting was carried out based on the measured values of this meter, you can use the minus compensation to adjust the exposure to a darker value.

Plus Compensation

If a darker image is obtained when shooting was carried out based on the measured values of this meter, you can use the plus compensation to adjust the exposure to a more positive value.



- Compensation of the measured value must be performed based on a sufficient number of test shooting results.
- Note that the individual compensation is possible in the incident light system and reflected light system while uniform compensation is applied in Ambient Mode and Flash Mode.



In Factory Setting, the light intensity can be adjusted using the minus or plus compensation. However, to adjust the exposure value (exposure decrease by plus compensation and exposure increase by minus compensation), select "Measured Value (+ is dark, - is bright)" in "Compensation +/- Preference" of Custom Setting. (*) P172)



In case that the Exposure Compensation is assigned to Function Button -1 or -2. (▶ P166)

Button	Description						
Comp. Disabled when Exposure compensation is not set.							
Comp. Displayed when Exposure compensation is OFF.							
Comp.	Displayed when Exposure compensation is ON.						

Operation


- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Exposure Compensation] Button on the Tool Box Screen. The Exposure Comp. Value Screen is displayed.
- 3. Set the compensation value.

Set the compensation value on the Exposure Comp. Value Screen that is displayed. The input value range is +/-9.9 EV in 0.1 step increments. (See → P11 for details about how to input the value.)

4. Touch [OK] Button.

The display returns to the Measuring Screen, and the (ADJ) icon and the compensation value are displayed on the status bar.

When you touch [Cancel] Button, the display returns to the Measuring Screen without setting the Exposure compensation.



6-4 Filter Compensation Function

This function registers a filter compensation value in the light meter. Setting this value enables you to obtain the measurement result to which the filter compensation value is applied.

If the filter is used in front of camera lens, the light coming into the camera is decreased, so this "decreased" light value should be compensated for the exposure value measured with the light meter.

The input value range is +/-20.0 EV in 0.1 EV step increments.

You can select the desired Filter Compensation Mode from the following three options:

- 1. Input Filter Comp. Value Enter the numeric value. Filter Compensation () is displayed on the status bar.
- 2. Filter Pack in Use
 You can select up to four pre-registered filter names. Filter Compensation () is
 displayed on the status bar.
- 3. No Filter
 Filter Compensation () disappears from the status bar.



Note that this Filter compensation is applied in the incident light system and the reflected light system, and also in Ambient Mode and Flash Mode at the same time.



- Selecting the plus compensation decerases the exposure (the meter displays a higher shutter speed or F-stop). Selecting the minus compensation increases the exposure (the meter displays a lower value of shutter speed or F-stop).
- Enter a minus value for filter compensation. Pre-registered filter names and values can be customized in Edit Filter in Menu list. (Up to 30 filter names can be registered.)



In case that the Filter Compensation is assigned to Function Button -1 or -2. (⇒ P166)

Button	Description						
Disabled when Filter compensation is not set.							
Filter Displayed when Filter compensation is OFF.							
Filter	Displayed when Filter compensation is ON.						

6-4-1 Input Filter Comp. Value

Directly enter a filter compensation value using a numeric value. The input value range is +/-20.0 EV in 0.1 EV step increments.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Filter Compensation] Button on the Tool Box Screen.

The Filter Compensation Screen is displayed.

3. Touch [Input Filter Comp. Value] radio button or an area around an item name.

The Filter Comp. Value Screen is displayed.



4. Input the compensation value on the Filter Comp. Value Screen. (See → P11 for details about how to input the value.)


5. Touch [OK] Button.

The value is applied, and the display returns to the Filter Compensation Screen. Then, the entered filter compensation value is displayed.


To return to the Filter Compensation Screen without changing the value, touch [Cancel] Button

6. Touch [OK] Button on the Filter Compensation Screen.

The value is applied, and the display returns to the Measuring Screen. Then, the Filter Compensation Icon () and the compensation value are displayed on the status bar.



Measuring Screen



6-4-2 Selecting a Filter

You can select up to four pre-registered filter name (⇒ P210).


Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Filter Compensation] Button on the Tool Box Screen.

The Filter Compensation Screen is displayed.

3. Touch [Filter Pack in Use] radio button or an area around an item name.

The Filter Pack in Use Screen is displayed.



4. Touch any of four [Filter Name] Buttons on the Filter Pack in Use Screen.

The Select User Filter Screen is displayed.

5. Touch the radio button on the Filter Pack in Use Screen to select the desired filter.

The selected filter is registered, and the display returns to the Filter Pack in Use Screen.



6. Repeat Steps 4 and 5 to register other filters.

Up to four filters listed on the Filter Pack in Use Screen are compensated all at once.



- In this Filter Pack in Use, you can select the same filter more than once.
- To deselect the listed in Filter Pack in Use, select "No Filter".

7. Touch [Close] Button.

The display returns to the Filter Compensation Screen.


8. Check that the selected filter name is displayed.

Check that the selected filter name is registered.

9. Touch [OK] Button on the Filter Compensation Screen.

The value is applied, and the display returns to the Measuring Screen. Then, the Filter Compensation Icon () and the compensation value are displayed on the status bar.

To return to the Measuring Screen without changing the value, touch [Cancel] Button.







- See "9-6 Filter Names and Compensation Values" for details about the filters that are pre-registered in Factory Setting. (₱ P210)
- The pre-registered filter name can be customized in Edit Filter in Menu list. (Up to 30 filter names can be registered.)

6-4-3 User-defined Filter Compensation Settings

You can register up to 30 user-defined filter compensation values in addition to the standard filter compensation values. The registered filter name and compensation values can be edited freely.





Operation

1. Press the Menu Button 9 on the meter.

The Menu Screen is displayed.


2. Touch the [Edit Filter] Button.

The Edit Filter Screen is displayed.




3. Touch [Filter Name] Button of the desired filter.

The Edit Filter Screen is displayed.



4. Touch the [Filter Name] Button on the Edit Filter Screen.

The Filter Name Screen is displayed.




5. Input the filter name. (⇒ P12)

You can input the filter name using up to 31 characters.

6. Touch [OK] Button.

The display returns to the Edit Filter Screen.

To return to the Edit Filter Screen without changing the name, touch the [Cancel] Button.



7. Touch the [Filter Comp. Value] Button on the Edit Filter Screen. The Filter Comp. Value Screen is displayed.



8. Input the filter compensation value. (⇒ P11)


The input value range is +/-20.0 EV in 0.1 EV step increments.

9. Touch [OK] Button.

The display returns to the Edit Filter Screen.

To return to the Edit Filter Screen without changing the value, touch [Cancel] Button.








Selecting the plus compensation decreases the exposure (the meter displays a higher value of shutter speed or F-stop). Selecting the minus compensation increases the exposure (the meter displays a lower value of shutter speed or F-stop).

10. Touch [Close] Button on the Edit Filter Screen.

The display returns to the Edit Filter Screen.

Edit Filter Screen



11. Touch the check box of the filter name.

Touch the box (\square) to check \checkmark (check mark \boxtimes) to display the filter name in the Select User Filter Screen on the Tool Box. (\Rightarrow P135) When the box is unchecked, it is not listed.




Check Box [Filter Name] Button

12. Touch [Close] Button on the Edit Filter Screen.

The display returns to the Menu Screen.

13. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.





- Filter compensation No. 1 to 24 have preset values. (→ P210)
- User settings can be added to filter compensation No. 25 to 30, and if necessary, No. 1 to 24 can be edited.

6-4-4 Deselecting a Filter


If "No Filter" is selected, any filter compensation is not applied to the measured value.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Filter Compensation] Button on the Tool Box Screen.


 The Filter Compensation Screen is displayed.
- 3. Touch [No Filter] radio button or an area around an item name.

 "No Filter" is selected.



4. Touch [OK] Button on the Filter Compensation Screen.

The filter compensation is released, and the display returns to the Measuring Screen. Then, the Filter Compensation Icon on the status bar disappears.



6-5 Mid. Tone Function

This function is used to specify a measured value as the standard of light measurements and put it at the center of EV scale.

The Mid. Tone Function has four modes:

Setting name	Description			
Set from Current Measurement	Specify the measured value as the Mid. Tone value.			
Set from Memory	Select the desired one from up to nine measured values saved in the memory, and set it as the Mid. Tone value.			
Modify Current Mid. Tone	Modify the specified Mid. Tone value.			
Mid. Tone Recall	Allows you to check the Mid. Tone value on the Mid. Tone Recall Screen.			



In case that the Mid. Tone is assigned to Function Button -1 or -2. (⇒ P166)

Button	Description						
Mid. Tone	Disabled when no measured value is taken.						
Displayed when the Mid. Tone setting is OFF.							
Mid. Tone	Displayed when the Mid. Tone setting is ON.						

6-5-1 Mid. Tone Setting

1) Set from Current Measurement


Set the measured value as the Mid. Tone value.

Operation

1. Press the Measuring Button 6.

Press this button to make a measurement.

- 2. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 3. Touch the [Set Mid. Tone] Button on the Tool Box Screen.
 The Set Mid. Tone Screen is displayed.
- 4. Touch the [Set from Current Measurement] Button on the Set Mid. Tone Screen.




2) Set from Memory

Set the memorized value as the Mid. Tone value.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Mid. Tone] Button on the Tool Box Screen.
 The Set Mid. Tone Screen is displayed.
- 3. Touch the [Set from Memory] Button on the Set Mid. Tone Screen. This displays the Mid. Tone Set from Memory Screen, which shows memory information (memory number, incident light () or reflected light (), and measured value). Measured values that are saved in the memory are displayed as dots on the analog scale.
- **4.** Touch one of the memorized values to set as the Mid. Tone value. The selected value is registered, and the display returns to the Measuring Screen. The newly set Mid. Tone value is then displayed on the analog scale.




3) Modify Current Mid. Tone

Fine-tune the currently set Mid. Tone value.

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Mid. Tone] Button on the Tool Box Screen.
 The Set Mid. Tone Screen is displayed.
- 3. Touch the [Modify Current Mid. Tone] Button on the Set Mid. Tone Screen.

The Modify Current Mid. Tone Screen is displayed.




4. Touch the arrow icon (or) or slide the number on the Modify Current Mid. Tone Screen.

Select the desired Mid. Tone value.

5. Touch [OK] Button.

The change is applied and the display returns to the Measuring Screen.

To return to the Measuring Screen without changing the value, touch [Cancel] Button.



Mid. Tone Value (After selected from the memory and edited)



(Select the Mid. Tone value from memory.) Newly set Mid. Tone value is displayed on the Analog Scale.



You cannot make a change if no Mid. Tone value is set.

6-5-2 Mid. Tone Recall

Recall the set Mid. Tone value to view details.



- 1. Touch the [Tool Box] Icon () on the Measuring Screen on which the Mid. Tone value is specified.
 - The Tool Box Screen is displayed.
- 2. Touch the [Mid. Tone Recall] Button on the Tool Box Screen.

The current Mid. Tone setting is displayed on the Measuring Screen.

3. Touch [Close] Button.

The display returns to the Measuring Screen.



6-5-3 Mid. Tone Clear

Clear the set Mid. Tone value.

Operation


- 1. Touch the [Tool Box] Icon () on the Measuring Screen on which the Mid. Tone value is set.
 - The Tool Box Screen is displayed.
- 2. Touch the [Mid. Tone Clear] Button on the Tool Box Screen.

The Mid. Tone Clear Screen is displayed, and the message of "A Mid. Tone value is cleared. Are you sure?" is displayed.

3. Touch [OK] Button.

The Mid. Tone value is cleared, and the analog scale that shows the Mid. Tone value is also cleared. Then, the display returns to the Measuring Screen.

To return to the Measuring Screen without clearing the Mid. Tone, touch [Cancel] Button.



6-6	Exposure Profile Function
6-6-1	Overview of Exposure Profile Function

1. What is a Exposure Profile?

- 1) It can be used to display on a light meter the unique dynamic range and clipping point of the digital camera you are using.
 - ◆ Transfers the unique sensor characteristics of the digital camera to the light meter. The dynamic range and clipping point differ depending on the camera you are using, so it is necessary to pay careful attention to how well the color and detail are captured in the highlight and shadow areas when you take a picture. By creating a camera exposure profile in Data Transfer Software and transferring it to the light meter, you can display the unique sensor characteristics as the dynamic range and clipping point, which makes it possible to instantly check whether or not a subject falls within the exposure range.
- 2) To display more accurate exposure values on the light meter, it records unique variations in the camera, lens shutter speed, aperture, etc. that you are using and reflects them in the exposure display.


Achieves more accurate exposure by matching the camera you are using with the light meter display

Even if you set exposure values measured on a light meter in the camera, you may not obtain the standard exposure due to variations in the camera, lens shutter speed and aperture you are using. If this happens, you can use Data Transfer Software to match the values on the light meter with the camera variations by correcting the display in the light meter so that it is possible to obtain the standard.

* This function takes the characteristics of the camera you are using into account and achieves better correction compared to prescribed correction functions that correct the measured results uniformly.

2. Main functions of Data Transfer Software

Data Transfer Software is application software for creating and editing camera exposure profiles, editing light meter settings (custom setting and user setting, etc.) and updating light meter firmware, transferring camera exposure profiles to the light meter unit as well as for implementing all other related settings.




For details, refer to the Software Guide of Data Transfer Software. (downloadable from the website, www.sekonic.com)

Operation

- 1. Touch the [Tool Box] Icon () on the Measuring Screen.
 The Tool Box Screen is displayed.
- 2. Touch the [Set Exposure Profile] Button on the Tool Box Screen.

 The Set Exposure Profile Screen is displayed.



3. Touch the exposure profile name to select it.

Touch the exposure profile name to select it. The display returns to the Measuring Screen and the Exposure Profile Icon (P) is displayed on the status bar.






You can display only the items for which you have selected ☑ in the check boxes on the Edit Exposure Profile Screen. (➡ P153)

6-6-3 Edit Exposure Profile

You can specify whether to display or not in the list on the "Set Exposure Profile" Screen of the Tool Box Screen.

You can also edit exposure profiles created using Data Transfer Software on the meter side (about setting values and names) or create exposure profiles manually using this meter only. (The meter can store up to 10 exposure profiles.)




1) Display or not on the Set Exposure Profile Screen (Tool Box)

Operation

- 1. Press the Menu Button ② on the meter.

 The Menu Screen is displayed.
- 2. Touch the [Edit Exposure Profile] Button.
 The Edit Exposure Profile Screen is displayed.






Close

3. Touch the check box of the exposure profile name.

Touch the box (\square) to check it \checkmark (check mark \square). The selected item can be displayed (registered) on the screen as an option on the Set Exposure Profile Screen. If the check mark (\square) is cleared, the option on the Set Exposure Profile Screen is disabled, and is not displayed on the screen.

* Only the check box (☑) of "Default Profile" is selected by default.

Edit Exposure Profile Screen



4. Touch [Close] Button.

The display returns to the Menu Screen.



5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.

2) Edit Exposure Profile

Although you can create an exposure profile using Data Transfer Software and transfer it to the meter, you can edit the stored exposure profile or directly enter an exposure profile into the meter manually.

Operation

1. Touch the [Edit Exposure Profile] Button.

The Edit Exposure Profile Screen is displayed.

* To always display the selected item as an option on the Set Exposure Profile Screen, touch the check box (□) to mark ✓ (check mark ☑).

2. Touch the [Exposure Profile Name] Button you want to select.

The Edit Exposure Profile Screen is displayed.

Edit Exposure Profile Screen




3. Touch the [Exposure Profile Name] Button on the Edit Exposure Profile Screen.

The Exposure Profile Name Screen is displayed.

4. Input the name.

Input the name on the Exposure Profile Name Screen. (⇒ P12)



156

5. Touch [OK] Button.

The display returns to the Edit Exposure Profile Screen, and the profile name you input is displayed.

Touch [Cancel] Button to return to the Edit Exposure Profile Screen without applying the edit made to the exposure profile name.


Edit Exposure Profile Screen



6. Touch the icon for the desired light receiving method and light source in "Edit Exposure Profile Data" on the Edit Exposure Profile Screen.

The ISO Sensitivity of Edit Exposure Profile Data Screen is displayed.

Edit Exposure Profile Screen






△ ‡	Incident light system, Ambient Mode		Incident light system, Flash Mode
♦	Reflected light system, Ambient Mode	4 4	Reflected light system, Flash Mode


7. Touch the [ISO Sensitivity] Button of the Exposure Profile Data to edit.

Touch the arrow icon (or) on the screen, or slide the scroll bar upward or downward using fingers to select the ISO sensitivity.

Three buttons of ISO sensitivity that are able to be selected are displayed.



8. Edit the camera sensitivity characteristics.



(1) Compensation value cursor

The compensation value can be set between -5 EV and +5 EV in 0.1 EV step increments.

While touching the compensation value cursor, slide the cursor to set the compensation value.

You can also touch the Minus or Plus Icon (or +) to change the value in 0.1 EV step increments each time it is clicked.

2 Dynamic range and clipping point

The dynamic range and clipping point can be set between -10 EV and +10 EV in 0.1 EV step increments. However, the clipping point cannot be set over the dynamic range.

Dynamic range (-) \leq Clipping point (-) \leq Clipping point (+) \leq Dynamic range (+)

While touching each cursor, slide the cursor to set the dynamic range (-), clipping point (-), clipping point (+), and dynamic range (+).

To edit the dynamic range, touch the Minus or Plus Icon (____ or ____).

To edit the clipping point, touch the Minus or Plus Icon (or).

③ Default

If you touch [Default] Button, the profile of the selected ISO sensitivity is reset to the default. To reset all the profiles to their defaults, use "Data Transfer Software", which is a convenient tool

9. Touch [OK] Button.

The display returns to the ISO sensitivity selection on Edit Exposure Profile Data Screen.


Touch [Cancel] Button to return to the ISO sensitivity selection on Edit Exposure Profile Data Screen without changing any data.

10. Touch [Close] Button on the ISO sensitivity selection on Edit Exposure Profile Data Screen.

The display returns to the Edit Exposure Profile Screen.

11. Repeat steps 6 to 9.

Edit another light receiving method and light source as needed.



12. Touch [Close] Button on the Edit Exposure Profile Screen.

The display returns to the profile name selection on the Edit Exposure Profile Screen.

13. Touch [Close] Button on the Edit Exposure Profile Screen.

The display returns to the Menu Screen.


14. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.



6-7 Custom Setting

The meter can be customized to desired measuring and display preferences.



^{*1 &}quot;Radio System Preference" in Custom Setting is only displayed when a transmitter (sold separately) is installed.

^{*} The screens may differ depending on the setting of meter or optional accessory installed.

6-7-1 Custom Setting List


Setting No.	Custom Setting Name	Item					Default Setting	
1	Function Button -1	Average/ Contrast Function ON/OFF	Incident/ Spot Selection	Exposure Compensation ON/OFF	Filter Compensation ON/OFF	Mid. Tone ON/OFF	All Memory/ Multi Clear	Average/ Contrast Function ON/OFF
2	Function Button -2	Average/ Contrast Function ON/OFF	Incident/ Spot Selection	Exposure Compensation ON/OFF	Filter Compensation ON/OFF	Mid. Tone ON/OFF	All Memory/ Multi Clear	Incident/ Spot Selection
3	Increments of T+F	1 step*1	1/3 (0.3) step	1/2 (0.5) step	-	-	-	1 step*1
4	Display of 1/10 Step Increments ²	ON	OFF	-	-	-	-	ON
5	Compensation +/- Preference	Exposure Level (+: Brighter, -: Darker)	Measured Value (+: Darker, -: Brighter)	-	-	-	-	Exposure Level (+: Brighter, -: Darker)
6	Switching Measuring/ Memory Buttons ^{'3}	Standard (Left: Memory Button/ Right: Measuring Button)	Reverse (Left: Measuring Button/ Right: Memory Button)	Auto (Incident: Standard, Spot: Reverse) *3	-	-	-	Standard (Left: Memory Button/ Right: Measuring Button)
7	Ambient Mode ^{*4,*5}	ON	OFF	-	-	-	-	ON
a)	T Priority Mode ^{*4}	ON	OFF	-	-	-	-	ON
b)	F Priority Mode ^{*4}	ON	OFF	-	-	-	-	ON
c)	TF Priority Mode ^{*4}	ON	OFF	-	-	-	-	ON
d)	HD CINE Mode ^{*4}	ON	OFF	-	-	-	-	ON
e)	CINE Mode*4	ON	OFF	-	-	-	-	ON
f)	Illuminance/ Luminance Mode ^{*4}	ON	OFF	-	-	-	-	ON
8	Flash Mode*4, *5	ON	OFF	-	-	-	-	ON
a)	Cordless Mode ^{*4}	ON	OFF	-	-	-	-	ON
b)	Cord Mode*4	ON	OFF	-	-	-	-	ON


Setting No.	Custom Setting Name	Item					Default Setting	
c)	Radio Triggering Mode ^{*4, *7}	ON	OFF	-	-	-	-	ON
d)	Multi Mode*4,*6	ON	OFF	-	-	-	-	ON
9	HSS Flash Mode ^{*5}	ON	OFF	-	-	•	-	ON
a)	Cordless Mode ^{*4}	ON	OFF	-	-	•	-	ON
b)	Radio Triggering Mode ^{*4, *7}	ON	OFF	-	-	-	-	ON
10	Flash Duration Analysis Mode ^{*5}	ON	OFF	-	-	-	-	ON
a)	Cordless Mode ^{*4}	ON	OFF	-	-	-	-	ON
b)	Cord Mode*4	ON	OFF	-	-	-	-	ON
c)	Radio Triggering Mode ^{*4, *7}	ON	OFF	-	-	-	-	ON
11	Additional Data	None	EV	Illuminance / Luminance	-	-	-	None
12	Illuminance/ Luminance Unit	Lux or cd/m²	Foot-candle or Foot-lambert	-	-	-	-	-
13	Color Theme	Black	White	Rose	Blue	-	-	Black
14	Auto Power Off	5 min	10 min	20 min	No auto power off	-	-	5 min
15	Backlight Brightness	Bright	Normal	Dark	-	-	-	Bright
16	Auto Dimmer	20 sec	40 sec	60 sec	No dimmer	-	-	20 sec
17	Memory Button	ON	OFF	-	-	-	-	OFF
18	Radio System Preference ^{*7}	Elinchrom: EL-skyport Normal	Elinchrom: EL-skyport Speed	Phottix: Strato II	-	-	-	Elinchrom: EL-skyport Normal
		ControlTL	Standard	ControlTL + Standard	-	-	-	ControlTL + Standard
19	Reset Custom Setting*8	Select [OK] Button or [Cancel] Button to apply or cancel reset processing.					-	

 $^{^{^{*1}}}$ The fraction is indicated in 1/10 steps in all modes. $^{^{*2}}$ The fraction display can only be set to ON or OFF in 1/3 or 1/2 step.

- ^{*3} Auto: The Measuring Button **⑤** and Memory Button **⑦** are placed in the standard configuration in the incident light system, and they are automatically switched to the reverse configuration in the reflected light system.
- ^{*4} When all the Measuring Modes are set to "OFF", the Ambient T Priority Mode is selected.
- *5 When the Ambient Mode, Flash Mode and Flash Duration Analysis Mode are set to OFF, the alphabet items that follow the modes are hidden.
- When the Multiple Mode is set to "ON", the Cordless Multiple (Cumulative) Flash Mode, Cord Multiple (Cumulative) Flash Mode, and Radio Triggering Multiple (Cumulative) Flash Mode are available on the Measuring Mode Screen.
- Displayed if a transmitter RT-EL/PX (sold separately) is installed. The contents may differ depending on the transmitter installed. See the transmitter operating manual for details.
- *8 All the items in Custom Setting are reset to the factory settings.


6-7-2 Custom Setting Procedure





1) Function Button -1 Setting

Assign the Function Button -1 on the Measuring Screen.



Operation

1. Touch the [Function Button -1] Button on page 1 of the Custom Setting Menu Screen.

The Function Button -1 Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

Close

The display returns to the Custom Setting Menu Screen.



Close

4. Touch [Close] Button on the Custom Setting Menu Screen.

Close

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.


The display returns to the Measuring Screen.

The selected item (Exposure Compensation ON/OFF) has been set to Function Button -1 on the Measuring Screen.



2) Function Button -2 Setting

Assign the Function Button -2 on the Measuring Screen. Items are common to Function Button -1.



Operation

1. Touch the [Function Button -2] Button on page 1 of the Custom Setting Menu Screen.


The Function Button -2 Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.

The selected item (Filter Compensation ON/OFF) has been set to Function Button -2 on the Measuring Screen.



3) "Increments of T+F" Setting

Set the increments of T+F for the shutter speed and f-stop value. See "9. Various Setting Values" for the increments of T+F setting. (▶ P208)

Operation

1. Touch the [Increments of T+F] Button on page 1 of the Custom Setting Menu Screen.


The Increments of T+F Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.


The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.




4) "Display of 1/10 Step Increments" Setting

Set the display of 1/10 step increments of the measured value. When 1/3 or 1/2 step is selected, you can select to hide the 1/10 step increments.

Measuring Screen

Display of 1/3 step with 1/10 increments ON

Display of 1/3 step with 1/10 increments OFF



Viewfinder Display





Viewfinder Display



Operation

1. Touch the [Display of 1/10 Step Increments] Button on page 1 of the Custom Setting Menu Screen.

The Display of 1/10 Step Increments Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

Custom Setting Menu Screen Display of 1/10 Step Increments Screen




4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen, and the updated content is applied to the Measuring Screen.



5) Compensation +/- Preference

Set the plus or minus direction of Exposure Compensation Value Function.

Operation

1. Touch the [Compensation +/- Preference] Button on page 1 of the Custom Setting Menu Screen.

The Compensation +/- Preference Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

Custom Setting Menu Screen Compensation +/- Preference Screen




4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.





Exposure Level: Selecting the plus (+) sign carries out compensation so that the exposure is increased (the image becomes brighter). Selecting the minus (-) sign carries out compensation so that the exposure is decreased (the image becomes darker).


Measured Value: Selecting the plus (+) sign carries out compensation so that the measured value is increased (the exposure is reduced, which means that the image becomes darker). Selecting the minus (-) sign carries out compensation so that the measured value is decreased (the exposure is increased, which means that the image becomes brighter).

6) Setting for Switching the Measuring Button 6 and Memory Button 7


To improve the operability, you can interchange the button functions between the incident light system and reflected light system.



• Standard: Used for measurement in the incident light system.



· Reverse: Used for measurement in the reflected light system.



 Auto: The button arrangement is set to "Standard" when the incident light system is selected, and to "Reverse" when the reflected light system is selected.

The positions of the Measuring Button and Memory Button are displayed for two seconds on the Measuring Screen just after Custom Setting has been changed and also just after the power has been turned on.

Operation

1. Touch the [Switching Measure/Memory Buttons] Button on page 1 of the Custom Setting Menu Screen.


The Switching Measure/Memory Buttons Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



7) Ambient Mode Setting

You can select Measuring Modes to be displayed on the Measuring Mode Screen. Display of all of Ambient Modes can be switched ON or OFF collectively, or Measuring Mode can be switched ON/OFF individually.

Measuring Mode Screen Default (All ON)



Measuring Mode Screen
All OFF in Ambient Mode



Measuring Mode Screen Individually OFF in Ambient Mode



Operation


1. Touch the [Ambient Mode] Button on page 2 of the Custom Setting Menu Screen.

The Ambient Mode Screen is displayed.






Ambient Mode Screen



2. Touch the check boxes of the Measuring Modes to display or not.

To display, select their check boxes (\boxdot). To hide, clear the check boxes (\Box).

If you clear the "Ambient Mode" check box, all the Ambient Modes are hidden collectively, and you will not be able to select any Measuring Mode under "Ambient Mode". To individually display or hide each Measuring Mode, select the desired modes under "Ambient Mode" without clearing the "Ambient Mode" check box.



3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



8) Flash Mode Setting

You can select Measuring Modes to be displayed on the Measuring Mode Screen. Display of all Flash Modes can be switched ON or OFF collectively, or Measuring Mode can be switched ON/OFF individually.

Measuring Mode Screen Default (All ON)



Measuring Mode Screen All OFF in Flash Mode




Measuring Mode Screen Individually OFF in Flash Mode



Operation

1. Touch the [Flash Mode] Button on page 2 of the Custom Setting Menu Screen.


The Flash Mode Screen is displayed.



2. Touch the check boxes of the Measuring Modes to display or not.

To display, select their check boxes (\square). To hide, clear the check boxes (\square).

If you clear the "Flash Mode" check box, all the Flash Modes are hidden collectively, and you will not be able to select any Measuring Mode under "Flash Mode". To individually display or hide each Measuring Mode, select the desired modes under "Flash Mode" without clearing the "Flash Mode" check box.




3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



9) HSS Flash Mode Setting

You can select Measuring Modes to be displayed on the Measuring Mode Screen. Set the HSS (High Speed Synchro) Mode to ON or OFF.

Measuring Mode Screen Default (All ON)



Measuring Mode Screen HSS Flash Mode OFF



Operation

1. Touch the [HSS Flash Mode] Button on page 2 of the Custom Setting Menu Screen.

The HSS Flash Mode Screen is displayed.





2. Check the HSS Flash Mode check box.

To display, select their check boxes (\square). To hide, clear the check boxes (\square).

HSS Flash Mode Screen




3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



10) Flash Duration Analysis Mode Setting

You can select Measuring Modes to be displayed on the Measuring Mode Screen. Display of all Flash Duration Analysis Modes can be switched ON or OFF collectively, or Measuring Mode can be switched ON/OFF individually.

Measuring Mode Screen Default (All ON)



Measuring Mode Screen Flash Duration Analysis Mode All OFF




Measuring Mode Screen Each Flash Duration Analysis Mode OFF individually



Operation

1. Touch the [Flash Duration Analysis Mode] Button on page 2 of the Custom Setting Menu Screen.

The Flash Duration Analysis Mode Screen is displayed.




2. Touch the check boxes of the Measuring Modes you want to display or hide.

To display, select their check boxes (\square). To hide, clear the check boxes (\square).

If you clear the "Flash Duration Analysis Mode" check box, all the Flash Duration Analysis Modes are hidden collectively, and you will not be able to select any Measuring Mode under "Flash Duration Analysis Mode". To individually display or hide each Measuring Mode, select the desired modes under "Flash Duration Analysis Mode" without clearing the "Flash Duration Analysis Mode" check box.

Flash Duration Analysis Mode Screen



3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.

4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



11) Additional Data Setting

Set the contents of additional data to be displayed on the lower right of the measurement value on the Measuring Screen.

Measuring Screen
Default
(No additional data)



Measuring Screen Additional data for EV value



Measuring Screen
Additional data for
illuminance/luminance



Operation

1. Touch the [Additional Data] Button on page 2 of the Custom Setting Menu Screen.


The Additional Data Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.




4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen, and the updated content is applied to the Measuring Screen.





The additional data is not displayed in the viewfinder in the reflected light system.

12) Illuminance/Luminance Unit SettingColor Theme Setting

Set the unit of illuminance and luminance.

You can select the unit of "lux or cd/m2" or "Foot-candle or Foot-lambert".

Measuring Screen Lux (Ix)



Measuring Screen Foot-lambert (fl)



Measuring Screen Foot-candle (fc)



Measuring Screen
Additional Data



Measuring Screen Candela per square meter (cd/m2)



Additional Data

Operation

1. Touch the [Illuminance/Luminance Unit] Button on page 2 of the Custom Setting Menu Screen.


The Illuminance/Luminance Unit Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.




4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen, and the updated content is applied to the Measuring Screen.



13) Color Theme Setting

Set the color theme of the Measuring Screen.

You can select the screen background color from black, white, rose, and blue.

Black (Default)











The viewfinder background color in the reflected light system cannot be changed.

Operation

1. Touch the [Color Theme] Button on page 3 of the Custom Setting Menu Screen.

The Color Theme Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.


3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.



- 4. Touch [Close] Button on the Custom Setting Menu Screen.
 - The display returns to the Menu Screen.
- 5. Touch [Close] Button on the Menu Screen.

The setting is applied, and the display returns to the Measuring Screen.



14) Auto Power Off Time Setting

Set the auto power off time.

You can select "5 min", "10 min", "20 min", or "No auto power off" as the length of the period from the time when the last operation on the meter was carried out to the time when the Auto Power Off Function is activated. When "No auto power off" is selected, the power is not turned off automatically.

Operation

1. Touch the [Auto Power Off] Button on page 3 of the Custom Setting Menu Screen.

The Auto Power Off Screen is displayed.

2. Touch the desired item.


Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.



15) Backlight Brightness Setting

Set the backlight brightness.

You can select "Bright", "Normal", or "Dark" as the backlight brightness of the screen. "Bright" is set as the default. For longer battery life, set this item to "Normal" or "Dark".

Operation

1. Touch the [Backlight Brightness] Button on page 3 of the Custom Setting Menu Screen.

The Backlight Brightness Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.




4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.

The display returns to the Measuring Screen.



16) Auto Dimmer Setting

Set the time to dim the LCD backlight.

You can select "20 sec", "40 sec", "60 sec", or "No dimmer" as the length of the period from the time when the last operation on the meter was carried out to the time when the backlight dims.

Operation

1. Touch the [Auto Dimmer] Button on page 3 of the Custom Setting Menu Screen.

The Auto Dimmer Screen is displayed.

2. Touch the desired item.

Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.


The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

5. Touch [Close] Button on the Menu Screen.



17) Memory Button

Set the Memory Button function.

You can set it ON to memorize the measured value. Set it OFF if you don't use this function. If the Memory Button is disabled, (is displayed at memory count area on the status bar. (→ P43)

Operation

1. Touch the [Memory Button] Button on page 3 of the Custom Setting Menu Screen.


The Memory Button Screen is displayed.

2. Touch the desired item.


Touch the desired radio button or an area around the item name to select.

3. Touch [Close] Button.

The display returns to the Custom Setting Menu Screen.



4. Touch [Close] Button on the Custom Setting Menu Screen.



18) Radio System Preference Setting

Select the radio system used in Radio Triggering Flash Mode and Flash Duration Analysis Radio Triggering Mode.

This Custom Setting menu is only displayed when RT-EL/PX transmitter (for Elinchrom/ Phottix, sold separately) is installed on the meter.

For details, see the manual of the transmitter (sold separately).



Custom Setting Menu Screen

19) Reset Custom Setting

Reset each setting value in Custom Setting to the default value.

You can only reset the "custom setting item" in the meter setting. To reset all the meter settings to the factory settings, perform the procedure from the hardware setting. (⇒ P206)

Operation


1. Touch the [Reset custom setting] Button on page 4 of the Custom Setting Menu Screen.

The Reset Custom Setting Screen is displayed.

The "Reset the contents of Custom Setting. Are you sure?" message is displayed. Touch [Yes] Button.

2. All of the custom setting items are reset to the default, and the display returns to the Custom Setting Menu Screen.


Touch [No] Button to return to the Custom Setting Menu Screen without reset of all custom setting items.



3. Touch [Close] Button on the Custom Setting Menu Screen.

The display returns to the Menu Screen.

4. Touch [Close] Button on the Menu Screen.



7. Hardware Setting

7-1 Hardware Setting Screen

The following settings can be made on the Hardware Setting Screen.

- User calibration of measured value
- · Adjustment of touch panel display position
- Reset to factory settings (default settings)
- · User information editing


Operation

1. Ensure that the power is turned off, press the Power Button 5 while holding down the Menu Button 9 of the meter.

The Hardware Setting Screen is displayed.



Do not release the Menu Button 9 until the Hardware Screen is displayed.



2. Touch the item on the Hardware Setting Screen.

Hardware Setting Screen



No.	Item	Description
1	User Calibration	Allows you to preset a compensation value for a measured value and apply it to the measurement result. (Setting range: -1.0 EV to 1.0 EV)
2	Adjust Touch Panel	Touch the white cross cursor displayed on the screen, and adjust the touch panel position.
3	Factory Setting	Allows you to reset various parameters and settings in the meter to their factory settings.
4	Edit User Information	Allows you to edit user information.

7-1-1 User Calibration

The meter is calibrated to Sekonic standards. However, if necessary, you can change the measurement standard using the User Calibration Function. The compensation value can be set +/- 1.0 EV in 0.1 EV step increments. If you know the compensation value in advance, you can directly enter the value. Also, you can adjust the meter based on a measured value obtained using another light meter.

Operation

<When you know the compensation value in advance>

1. Touch the [User Calibration] Button.

The User Calibration Screen is displayed.

User Calibration Screen



2. Adjust the calibration value.

Use the Adjustment Button (-0.1EV) or (-0.1EV) to adjust the calibration value in increments of +/-0.1 EV.

3. Touch [Close] Button.


Finish the setting, and return to the Hardware Setting Screen.

<When adjusting the meter based on a measured value obtained using another light meter>

1. Touch the [User Calibration] Button.

The User Calibration Screen is displayed.





2. Press the Measuring Button 6.

The User Calibration Screen allows you to make measurements, thus you can equalize measured values obtained using another light meter under the same light source.

3. Adjust the calibration value.

Touch the Adjustment Button () or () to adjust the calibration value in increments of +/-0.1 EV.

4. Touch [Close] Button.

Finish the setting, and return to the Hardware Setting Screen.



- User calibration carried out in Hardware Setting is not displayed on the status bar.
- Note that the individual compensation is possible in the incident light system and reflected light system while uniform compensation is applied in Ambient Mode and Flash Mode.

7-1-2 Adjust Touch Panel

This function allows you to adjust the coordinate position that is recognized by the touch sensor of the touch panel.

Operation

1. Touch the [Adjust Touch Panel] Button.

The Adjust Touch Panel Screen is displayed.


The white cross cursor appears on the screen.

The "Touch center of the cursor." message is displayed.

2. Touch the white cross cursor.

A red cross cursor is displayed at the position you touched.

Adjust Touch Panel Screen



3. Perform this procedure twice at each of four positions.

After being touched, the white cross cursor is displayed at another position.

The cursor is displayed twice in four corners in the following order: top left \rightarrow bottom right \rightarrow top right \rightarrow bottom left \rightarrow bottom right \rightarrow top right \rightarrow bottom left. Repeat this procedure in sequence.


Adjust Touch Panel Screen



4. Check the adjustment result.

When you have touched the cursor in all the corners, the "Data is determined by pressing the "OK"." message is displayed.

Adjust Touch Panel Screen



5. Touch [OK] Button.

Finish the setting, and the display returns to the Hardware Setting Screen.

Touch [Cancel] Button to return to the Hardware Setting Screen without applying the touch panel adjustment.

7-1-3 **Factory Setting**

This function resets all the parameters and settings related to measured values, setting values, custom settings, user information, etc. to the factory settings. See "6-7 Custom Setting" for the factory default of custom settings only. (→ P161)

Operation

1. Touch the [Factory Setting] Button.

The "Reset to factory default settings. Are you sure?" message is displayed on the Factory setting Screen.

2. Touch [Yes] Button.

To perform this operation, touch the [Yes] Button.


The "All measurements will be lost when you perform this operation. Are you sure?" message is displayed on the Factory Setting Confirmation Screen.

Touch [No] Button to return to the Hardware Setting Screen without performing the factory setting.

Factory Setting Screen



Factory Setting Confirmation Screen



[No] Button [Yes] Button

3. Touch [Yes] Button.

The factory settings are initialized, and the display returns to the Hardware Setting Screen.

Touch [No] Button to return to the Hardware Setting Screen without performing the factory setting.

7-1-4 Edit User Information


This function allows you to edit user information. The input user information is displayed on the Product Information Screen of the Menu.

Operation

1. Touch the [Edit User Information] Button.

The User Information Screen is displayed.

User Information Screen



2. Input user information.

User information can be input using up to 31 characters. (See → P12 for details about how to input the value.)

3. Touch [OK] Button.

After inputing user information, touch the [OK] Button.

The display returns to the Hardware Setting Screen.

Touch [Cancel] Button to return to the Hardware Setting Screen without changing the User information.

4. Touch [Close] Button on the Hardware Setting Screen.

Finish the setting, and return to the Measuring Screen.

8. Optional Accessories

Synchro Cord

This is a five-meter (16.4 feet) long cord with three plugs. An exposure meter, a camera and a flash can all be connected at the same time without having to plug or unplug the cord during shooting. Also, the connection terminal (male) on the light meter side of the synchro cord has a locking mechanism to ensure it remains connected to the meter.



(1 male terminal on the light meter side, 1 male terminal and 1 female terminal)

Exposure Profile Target II

Simpler to use, this is the test target used to create camera exposure profiles. One side consists of a central 18% gray patch that is surrounded by 24 patches arranged in 1/6th stop values that are successively brighter and darker, while the other side is 18% gray card, so it can be used to determine digital camera white balancing and spot metering.



(Size: 350 mm × 210 mm = 13.8" x 8.3")

Exposure Profile Target

This is more economical test target used to create camera exposure profiles. One side is nine gray patches including black and white, and the other side is an 18% gray card for digital camera white balancing and spot metering.






Step-up Ring

You can attach the step-up ring (30.5 mm \rightarrow 40.5 mm) to the objective lens side to use a commercially available filter. This allows you to determine the exposure without troublesome correction calculation of the PL filter. PL filters have the circular polarized light and polarized light types, however, only the circular polarized light type can be used. The step-up ring can also be used as a lens hood to protect the spot lens from damage or dirt and avoid lens glare which could cause incorrect light measurements etc.




RT-20PW

This transmitter, compatible with 344MHz frequency of PocketWizard radio system, separately requires a receiver for the relevant system on the flash side. Installing the transmitter in the L-858D enables to trigger the electronic flash units wirelessly with radio signal for measurement. With ControlTL system, it allows you to control the power of flash units and turn the power ON/OFF of modeling lamps



RT-3PW


This transmitter, compatible with 433MHz frequency of PocketWizard radio system, separately requires a receiver for the relevant system on the flash side. Installing the transmitter in the L-858D enables to trigger the electronic flash units wirelessly with radio signal for measurement. With ControlTL system, it allows you to control the power of flash units and turn the power ON/OFF of modeling lamps.



RT-BR


This transmitter, compatible with 2.4GHz frequency of broncolor radio system, separately requires a receiver for the relevant system on the flash side.

Installing the transmitter in the L-858D enables to trigger the electronic flash units wirelessly with radio signal for measurement. With broncolor RFS2/2.1/2.2 system, it allows you to control the power of flash units and turn the power ON/OFF of modeling lamps.




RT-EL/PX

This transmitter, compatible with 2.4GHz Elinchrom radio system (EL-Skyport) and Phottix radio system (Strato II protocol), separately requires a receiver for the relevant system on the flash side. Installing the transmitter in the L-858D enables to trigger the electronic flash units wirelessly with radio signal for measurement. With EL-Skyport system, it allows you to control the power of flash units and modeling lamps as well as turn the power ON/OFF of modeling lamps.



RT-GX

This transmitter, compatible with 2.4GHz Godox radio system, separately requires a receiver for the relevant system on the flash side. Installing the transmitter in the L-858D enables to trigger the electronic flash units wirelessly with radio signal for measurement. With Godox system, it allows you to control the power of flash units and modeling lamps as well as turn the power ON/ OFF of modeling lamps.



9. Various Setting Values

9-1 ISO Sensitivity

Setting values are basically defined in 1/3 step increments. However, ISO850 used in Cine camera is displayed between ISO800 and ISO1000.

3, 4, 5, 6, 8, 10, 12, 16, 20, 25, 32, 40, 50, 64, 80, 100, 125, 160, 200, 250, 320, 400, 500, 640, 800, 850, 1,000, 1,250, 1,600, 2,000, 2,500, 3,200, 4,000, 5,000, 6,400, 8,000, 10,000, 12,800, 16,000, 20,000, 25,600, 32,000, 40,000, 51,200, 64,000, 80,000, 102,400, 128,000, 160,000, 204,800, 256,000, 320,000, 409,600, 512,000, 640,000, 819,200, 1,024,000, 1,280,000, 1,638,400, 2,048,000, 2,560,000, 3,276,800, 4,096,000, 5,120,000, 6,553,600, 8,192,000, 10,240,000, 13,107,200

9-2 Shutter Speed

"m" denotes "minutes", and "s" denotes "seconds". Numbers without a unit are in "second" units. You can select the desired value in Custom Setting to suit the camera settings.

In Ambient Mode, the fastest shutter speed setting is 1/64,000 sec. In Flash Mode, the fastest shutter speed setting is 1/16,000 sec. The shutter speed from 1/75 which appears after the fastest shutter speed is old shutter speed. The displayed old shutter speeds differ between ambient light and flash light.

1 step increments (Default)	30m, 15m, 8m, 4m, 2m, 1m, 30s, 15s, 8s, 4s, 2s, 1s, 1/2, 1/4, 1/8, 1/15, 1/30, 1/60, 1/125, 1/250, 1/500, 1/1,000, 1/2,000, 1/4,000, 1/8,000, 1/16,000, 1/32,000, 1/64,000, 1/75, 1/80, 1/90, 1/100, 1/200, 1/400
1/2 step increments	30m, 20m, 15m, 10m, 8m, 6m, 4m, 3m, 2m, 1.5m, 1m, 45s, 30s, 20s, 15s, 10s, 8s, 6s, 4s, 3s, 2s, 1.5s, 1s, 0.7s, 1/2, 1/3, 1/4, 1/6, 1/8, 1/10, 1/15, 1/20, 1/30, 1/45, 1/60, 1/90, 1/125, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1,000, 1/1,500, 1/2,000, 1/3,000, 1/4,000, 1/6,000, 1/8,000, 1/12,000, 1/16,000, 1/24,000, 1/32,000, 1/50,000, 1/64,000, 1/75, 1/80, 1/90, 1/100, 1/200, 1/400
1/3 step increments	30m, 25m, 20m, 15m, 13m, 10m, 8m, 6m, 5m, 4m, 3.2m, 2.5m, 2m, 1.6m, 1.3m, 1m, 50s, 40s, 30s, 25s, 20s, 15s, 13s, 10s, 8s, 6s, 5s, 4s, 3.2s, 2.5s, 2s, 1.6s, 1.3s, 1s, 0.8s, 0.6s, 0.5s, 0.4s, 0.3s, 1/4, 1/5, 1/6, 1/8, 1/10, 1/13, 1/15, 1/20, 1/25, 1/30, 1/40, 1/50, 1/60, 1/80, 1/100, 1/125, 1/160, 1/200, 1/250, 1/320, 1/400, 1/500, 1/640, 1/800, 1/1,000, 1/1,250, 1/1,600, 1/2,000, 1/2,500, 1/3,200, 1/4,000, 1/5,000, 1/6,400, 1/8,000, 1/10,000, 1/13,000, 1/16,000, 1/20,000, 1/26,000, 1/32,000, 1/40,000, 1/50,000, 1/64,000, 1/75, 1/80, 1/90, 1/100, 1/200, 1/400
HD CINE Mode only	The following special shutter speeds appear after the fastest shutter speed setting. 1/6, 1/6.25, 1/7.5, 1/12, 1/12.5, 1/15, 1/24, 1/25, 1/30, 1/48, 1/50, 1/60, 1/96, 1/100, 1/120, 1/192, 1/200, 1/240

9-3 F-stop (Aperture)

You can select the desired value in Custom Setting to suit the camera settings.

<incident light="" system=""></incident>		
1 step increments (Default)	0.5, 0.7, 1.0, 1.4, 2.0, 2.8, 4.0, 5.6, 8.0, 11, 16, 22, 32, 45, 64, 90, 128	
1/2 step increments	0.5, 0.6, 0.7, 0.8, 1.0, 1.2, 1.4, 1.7, 2.0, 2.4, 2.8, 3.4, 4.0, 4.8, 5.6, 6.7, 8.0, 9.5, 11, 13, 16, 19, 22, 27, 32, 38, 45, 54, 64, 76, 90, 108, 128, 152	
1/3 step increments	0.5, 0.56, 0.63, 0.7, 0.8, 0.9, 1.0, 1.1, 1.3, 1.4, 1.6, 1.8, 2.0, 2.2, 2.5, 2.8, 3.2, 3.6, 4.0, 4.5, 5.0, 5.6, 6.3, 7.0, 8.0, 9.0, 10, 11, 12.7, 14, 16, 18, 20, 22, 25, 28, 32, 35, 40, 45, 51, 57, 64, 72, 81, 90, 102, 114, 128, 144, 161	

9-4 Frame Rate

The available frame rate (f/s) settings are as follows. In addition to these values, you can register up to 20 frame rates.

1, 2, 3, 4, 6, 8, 10, 12, 14, 15, 16, 18, 20, 23.976, 24, 25, 29.97, 30, 32, 36, 40, 47.952, 48, 50, 59.94, 60, 64, 72, 75, 90, 96, 100, 120, 125, 128, 150, 180, 200, 240, 250, 256, 300, 360, 375, 500, 625, 750, 1,000

9-5 | Shutter Angle

The available shutter angle settings are as follows. In addition to these values, you can register up to 20 shutter angles.

 $1,\,2,\,3,\,4,\,5,\,6,\,7,\,8,\,9,\,10,\,11,\,11.25,\,12,\,15,\,17,\,20,\,22,\,22.5,\,25,\,30,\,35,\,40,\,43.2,\,45,\,50,\,55,\,60,\\65,\,69,\,70,\,72,\,75,\,80,\,85,\,86.4,\,90,\,95,\,100,\,105,\,108,\,110,\,115,\,120,\,125,\,130,\,135,\,140,\,144,\\145,\,150,\,155,\,160,\,165,\,170,\,172,\,172.8,\,175,\,180,\,185,\,190,\,195,\,200,\,205,\,210,\,215,\,216,\,220,\\225,\,230,\,235,\,240,\,245,\,250,\,255,\,260,\,262,\,265,\,270,\,288,\,316,\,358$

9-6 Filter Names and Compensation Values

The following table shows the L-858D's default filter names and compensation values that are displayed when a filter name is selected. In addition to these values, you can register up to 30 filter names.

No.	Filter Name	Compensation value (EV value)
1	ND0.3	-1.0
2	ND0.6	-2.0
3	ND0.9	-3.0
4	CTO Double	-2.1
5	CTO Full	-1.1
6	CTO Three-Quarter	-0.8
7	CTO Half	-0.5
8	CTO Quarter	-0.3
9	CTO Eighth	-0.1
10	No.85	-0.8
11	CTB Double	-3.3
12	CTB Full	-1.5
13	CTB Three-Quarter	-1.3
14	CTB Half	-0.9
15	CTB Quarter	-0.4
16	CTB Eighth	-0.3
17	Minusgreen Full	-0.9
18	Minusgreen Half	-0.5
19	Minusgreen Quarter	-0.3
20	Minusgreen Eighth	-0.2
21	Plusgreen Full	-0.4
22	Plusgreen Half	-0.2
23	Plusgreen Quarter	-0.1
24	Plusgreen Eighth	-0.2

10. Specifications

Туре			
Digital light meter for flash and ambient light			
Light Receiving Method			
 Incident light and reflected 	Incident light and reflected light		
Light Receptor			
Incident light		e convertible to retracted lumisphere of functions as a retracted lumisphere into the meter)	
Reflected light	Single-eye spot with receiving angle: 1 de Measuring distance:		
Light Receptor Element			
 Silicon photo diodes 			
Measuring Mode			
Ambient light	T (shutter speed) priority F (f-stop) priority TF (shutter speed and aperture) priority HD CINE CINE Illuminance (lux or foot-candle) Luminance (cd/m² or foot-lambert)		
Flash light	Cord Mode (with/without multiple cumulative) Cordless Mode (with/without multiple cumulative) Radio Triggering (with/without multiple cumulative) * Available when a transmitter (sold separately) is installed		
HSS flash	Cordless Mode (without multiple cumulative) Radio Triggering (without multiple cumulative) * Available when a transmitter (sold separately) is installed		
Flash duration analysis (for incident light only)	Cord Mode (without multiple cumulative) Cordless Mode (without multiple cumulative) Radio Triggering (without multiple cumulative) * Available when a transmitter (sold separately) is installed		
Repeat Accuracy			
 0.1EV or less (Incident light: from EV-2, Reflected light: from EV1) 0.2EV or less (Incident light: under EV-2, Reflected light: under EV1) 			
Measuring Range (ISO100)			
Ambient light	Incident light Reflected light	EV-5 to EV+22.9 EV-1 to EV+24.4	

Flash light	Incident light	F0.5 to F128.9 (= F161.2)
	Reflected light	F1.0 to F128.9 (= F161.2)
Illuminance (in two significant digits)	Incident light	0.10 lx to 2,000,000 lx 0.01 to 180,000 fc
 Luminance (in two significant digits) 	Reflected light	0.10 cd/m² to 980,000 cd/m² 0.03 to 290,000 fl
Calibration Constant		
Incident light	Lumisphere C = 340	Flat diffuser (retracted lumisphere) C = 250
Reflected light	K = 12.5	
Display Range		
• ISO	ISO 3 to ISO 13,107,	200 (in 1/3 steps), ISO 850
Shutter speed	Ambient light	30 min to 1/64,000 sec, 1/200, 1/400 (in 1, 1/2, and 1/3 steps)
	Flash light	30 min to 1/16,000 sec, 1/75, 1/80, 1/90, 1/100, 1/200, 1/400 (in 1, 1/2, and 1/3 steps)
Flash duration time	1/40s to 1/55,500 sec (25 ms to 18 us) t0.1 to t0.9 (in 0.1 steps)	
Aperture	F0.5 to F128.9 (in 1 steps) F0.5 to F152.4 (in 1/2 steps) F0.5 to F161.2 (in 1/3 steps)	
• EV	Incident light	EV-73.9 to EV+103.8
	Reflected light	EV-69.9 to EV+105.3
• Frame rate (f/s)	1f/s to 1,000f/s Plus 20 other user settings from 0.001f/s to 99,999.999f/s	
Shutter angle	1° to 358° Plus 20 other user settings from 0.001° to 360°	
Analog display	T scale 4s to 1/2000s (in 1/3 steps) F scale F1.0 to F90 (in 1/3 steps) EV scale -3EV to +3EV (incident light, in 1/3 steps) -7EV to +7EV (reflected light, in 1/3 steps)	
	Illuminance lux	0 to 50,000 lx
	Luminance cd/m² (candela per square ı	0 to 2,500 cd/m ² meter)
Contrast function	-9.9EV to +9.9EV (in 0.1 steps)	
Multiple cumulative count	0 to 99 times (Maximum of 99 times for display, the number of measurement is infinite)	

Filter compensation value	-20.0EV to +20.0EV (in 0.1 steps)
Filter name compensation selection	Up to four types can be used simultaneously Plus 30 user settings
Exposure compensation	-9.9EV to +9.9EV (in 0.1 steps)
User calibration	-1.0EV to +1.0EV (in 0.1 steps)

Other Functions

• Flash Analyzing Function 0 to 100% (in 10% steps)

Memory Function
 Up to 9 measurements can be memorized

Memory Clear and Memory Recall Functions

Average Function Calculates an average of up to nine memorized values

 Out of display or measurement range Under, Over warning display

Battery power indicator display

Four levels

• Auto power OFF function

Can be selected in Custom Setting

LCD backlight

Backlight brightness and dimmer time can be selected in the Custom Setting

...

• Touch Panel Lock Function

• Custom settings 17 items (18 items when RT-EL/PX transmitter (sold

separately) is installed) + Reset

Tripod socket
 1/4 in, 20 threads

LCD

LCD panel
 2.7-inch color dot matrix LCD with Touch panel function

Power Supply

• Two 1.5V AA batteries (Alkaline and manganese batteries are recommended)

Operating Ambient Temperature

-10°C to 50°C (no condensation)

Operating Ambient Humidity

• 85% RH or less (at 35°C) (no condensation)

Transportation and Storage Conditions

• Ambient temperature -20°C to 60°C (no condensation)

* Depends on the specification of batteries in use.

Ambient humidity
 85% RH or less (at 35°C) (no condensation)

Dimensions

• Approx. 94 (W) × 176 (H) × 49 (D) mm (excluding light receptor)

* Excluding the buttons and other protrusions

Weight

• Approx. 240 g (without batteries)

Standard Accessories

- Soft case, strap, lens cap (installed on the meter), anti-glare sheet for LCD screen Startup Guide, Safety Precautions
- * For improvement reasons the specifications and external appearance in this manual may be subject to future changes without prior notification.

11. Legal Requirement

This product complies with the following legal requirements.

Destination	Star	ndard	Details
Europe	CE	SAFETY	EN 62368-1
	(ϵ)	EMC	EMS: EN55024, EN55035 EMI: EN55032
		Wireless	EN 300 220-2 EN 301 489-1 EN 301 489-3 EN 301 489-17 EN 62479
		Environmental	WEEE, RoHS
North America	FCC (US)	EMC	FCC Part15 SubpartB ClassB
America	P	Wireless	FCC Part15 SubpartC
	IC (Canada)	EMC	ICES-003
	(Gariada)	Wireless	RSS-210
Japan	Environmental Standard		Containers and Packaging Recycling Act
	Radio Act		Certification of construction type prescribed in Article 38-24 paragraph (1) of the Radio Act
Korea	KC		This symbol mark indicates the registration of RRA. MSIP-REM-SK0-L-858D.
			Class B Equipment (For Home Use Broadcasting & Communication Equipment) Class B equipment is equipment suitable for use in locations in residential environments for domestic purposes. Class B equipment shall meet class B limits.
UK (Great	UKCA	SAFETY	Electrical Equipment (Safety) Regulations 2016
Britain)	UK	EMC	Electromagnetic Compatibility Regulations 2016
		Wireless	Radio Equipment Regulations 2017
	T	Environmental	RoHS Regulations 2012

12. Troubleshooting

If your meter is not operating properly, as you expect, please consult the following conditions and attempt the suggested solutions before contacting Sekonic. Non-operation can be due to incorrect, mis-setting of the meter or battery condition. Should your meter be malfunctioning, please contact place where meter was purchased or Sekonic for service and repair.

Condition	Possible reasons	What to do
The power does not turn on. (No display)	Was the Power Button 5 pressed and held in for more than one second?	Hold the Power Button 5 down for more than one second.
	Batteries installed properly (+/-)?	Check the display (+/-). (▶P4)
	Batteries dead?	Replace the batteries. (▶P8)
	Battery terminals dirty?	Wipe them with a dry cloth.
	Correct batteries being used?	Check the batteries. (⇒P4)
The LCD screen doesn't respond.	Is the screen locked?	Hold down the Menu Button ② to release the screen lock. (→ P13)
The viewfinder does not show the measured value.	Is the light receiving method Incident Light Mode? (The display of measurement in the viewfinder is available in Reflected Light Mode only.)	Set the meter to Reflected Light Mode with Function Button or Tool Box Screen. (⇒ P37, P39)
Can not measure.	Is it connected to a PC with the USB cable?	Remove the USB cable. (⇒ P23)
	Have Measuring Button and Memory Button Functions been switched?	Check the Custom Setting Function and switch the buttons if necessary. (⇒ P5, ⇒ P41, ⇒ P162)
	Is the measured flash duration time longer than the input shutter speed?	Slower the shutter speed than the flash duration time and measure again. (➡ P99)
	Are the meter transmitter and receiver set for the same number of channel/zone (group)?	Set the same channel number and zone (group) on the transmitter and receiver. For details, see the operating manual of the transmitter (sold separately). (♣ P206)

Condition	Possible reasons	What to do
Measured value does not look correct.	Is the lumisphere retracting ring at an intermediate position?	Rotate the lumisphere retracting ring until it clicks into place. (→ P129)
	Is the light receiving method between Incident light and reflected light wrong?	Make sure if the light receiving method (incident or reflected) is correct, and set it with Function Button or Tool Box to take a measurement correctly.
	+/- values in ADJ (Exposure Compensation) or Filter area of Information Screen in use?	Check the exposure compensation (➡ P129) or filter compensation (➡ P132) are set correctly in Tool Box.
	Exposure Profile in use?	Check if correct exposure profile is selected in Tool Box, or properly created (₱ P151)
	Is a user calibration set with the Hardware Setting Function?	Check the user calibration (⇒ P198), and check whether the set value is correct or not.
	Measuring Mode set for type of light being measured?	Check Measuring Mode Icon. To change, touch Icon to go to Measuring Mode Selection Screen.
	Flash being measured in Cordless Mode set for TTL or Auto? (Pre-flash being measured instead of exposure flash.)	Select manual modes for flash in use. Exposure meters cannot measure TTL flash. Set the number of pre-flash in Tool Box to measure the exposure flash correctly.
	Does the flash unit being used have the Pre-flash Function?	Set the number of pre-flash in Tool Box to measure the exposure flash correctly. (→ P102)
In HD CINE Mode, cannot set lower shutter speed.	Normal function. Shutter speeds cannot be set lower than the selected frame rate. (For example, if the frame rate is set to 15 f/s, the shutter speed can only be set up to 1/15 s.)	Select lower frame rate. Increase brightness to get desired F-number.
Displayed shutter speed and aperture values do not look like camera's settings.	Are display steps set for full or 1/2 or 1/3 equal to your camera?	Press Menu Button ② . Select 3. Custom Setting. Select Increments of T+F to set display properly.

Condition	Possible reasons	What to do
Can not use the memory	The Memory Function can't be used in the following Measuring Modes Cord Multiple (Cumulative) Flash Mode - Cordless Multiple (Cumulative) Flash Mode - Radio Triggering Multiple (Cumulative) Flash Mode - Illuminance/Luminance Measuring Mode	Use the Memory Function in modes other than those on the left.
	Is "Memory Full" displayed when you press the Memory Button ? ? The memory can be used 9 times.	If you can't put the 10th or later measured value into the memory, clear unnecessary memory values on the Memory Clear Screen, and then measure and store the value again.
	Is Memory Button 7 set to OFF?	Press the MENU Button ③ . Select 3. Custom Setting. Select ON for Memory Button. (→ P43, → P194)
The EV is not displayed.	The EV value is displayed in the following Measuring Modes. - Ambient T Priority Mode - Ambient F Priority Mode - Ambient TF Priority Mode - Ambient HD CINE Mode - Ambient CINE Mode	Use a Measuring Mode which displays the EV value.
The EV scale is not displayed even though it is selected.	The EV scale can't be displayed in the following Measuring Modes Cord Multiple (Cumulative) Flash Mode - Cordless Multiple (Cumulative) Flash Mode - Radio Triggering Multiple (Cumulative) Flash Mode	Use the EV scale in a Flash Mode other than a Cumulative Mode. The measuring value scale (f-stop value) can be used in Cumulative Modes.
Can not trigger the flash in HSS Mode.	Is the synchro cord used to connect and measure?	HSS measurements are only available with Cordless Flash Mode and Radio Triggering Mode (with RT-GX only). In Cordless Flash Mode, press the camera's shutter release button to trigger and measure the HSS flash.

Condition	Possible reasons	What to do
Error 10 is displayed.	Did you turn the power supply off or remove the USB cable while updating the firmware on the data transfer software "Update" screen?	Overwrite the firmware on the data transfer software "Update" screen.

13. After-sales Services

- Contact your local distributor or camera store that you purchased from for warranty and service.
- Even within the warranty period, repair services may be provided on a paid basis. Check the conditions of warranty provided by local distributor or retailer.
- The warranty is not valid unless the copy of proof of purchase with the date of purchase and the retailer name. Be sure to store such information (bill of purchase or receipt) in a safe location.
- We will retain performance parts for repairs for approximately seven years after production is discontinued. Therefore, we may not be able to carry out repairs after this period has elapsed.
- When requesting repairs, please provide us with as much detail as possible about the failure or specific failure locations that you are able to identify. In certain cases, some products that are returned to us for repairs are not malfunctioning, and begin to operate normally again when we simply replace the batteries. Before requesting repairs, please confirm that the batteries are installed in the correct polarities, contain sufficient charge, and that they match the rating.

FCC & IC Compliance Information

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

FCC Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

IC Warning

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

SEKONIC CORPORATION

7-24-14, Oizumi-Gakuen-Cho, Nerima-Ku, Tokyo 178-8686 Japan

Tel +81-3-3978-2335 Fax +81-3-3978-5229 https://www.sekonic.com

JY1L97634 December 2021