



WOODFORCE® OMU 50 Finish

durable polyurethane finish

Spartan's WOODFORCE OMU 50 Finish provides a strong, extremely durable coating. WOODFORCE OMU 50 Finish has a sweet resinous aroma and is made of top grade, oil modified polyurethane. The 50% high solid content of OMU 50 Finish provides a deep, mirror-like gloss with good color reflection and slip resistance. It resists black marks, making it an ideal coating for sports and multi-activity wood floors.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

PRODUCT FEATURES

WOODFORCE OMU 50 Finish is a solvent based urethane finish designed for professional use in commercial, institutional and sports applications.

MULTIFUNCTIONAL APPLICATION

WOODFORCE OMU 50 Finish is an excellent finish for natural wood floors. Exceptional product performance is achieved on gymnasium and other athletic floors, stage floors, multi-activity wood floors, and other commercial and residential wood floors.

RAPID FLOOR TURNOVER

High solids content and coverage of 500-600 square feet per gallon provides a strong, durable coating with just one coat. Under normal conditions (75°F, 50% Relative Humidity), finish will be tack-free (dry to touch) in 3-5 hours, available for light traffic in 2-3 days and heavy traffic or athletic events in 5-7 days.

EASY APPLICATION

Easy application is achieved with WOODFORCE OMU 50 Finish and heavy weighted T-Bar, such as the Padco® "Big Foot Floor Coater", or an on-board tank release type applicator, such as an E-Z Way. Always apply thin coats. Work out puddles and ridge lines.

DIRECTIONS FOR USE

See product label for detailed floor preparation, product application and routine maintenance instructions. Professional technicians or experienced personnel are ideal for fully sanding floors. Floors must be screened to ensure adhesion prior to re-coating. See additional Informative Bulletins for important notes and trouble shooting.

KEEP OUT OF REACH OF CHILDREN

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATION DATA

Total Active Ingredients: 50%

Appearance: Clear light tan

Odor: Sweet resinous

Weight Per Gallon: 7.23 lbs. (0.868 density)

Flash Point (T.C.C.): 110°F

Coverage: 500-600 ft.² per gallon

NOTE: Typical high school basketball court (playing area) is 4,200 ft.² outside court boundaries will add to this significantly.



Distributed by:

PACKAGING

582405	5 Gallon Pail
582404	1 Gallon (4 per case)



GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.

For institutional and industrial use only.

© SCC 09/15 L5824