

Jones Stephens' PlumBite® Push to Connect Reducing Tee Stop

Job Name	_____
Location	_____
Engineer	_____
Contractor	_____
Tag	_____ PO# _____

Specifications

Jones Stephens' PlumBite® Push to Connect Reducing Tee Stops are a heat-free method of joining Copper, CPVC, PE-RT or PEX tubing, designed to save time on installation and to connect piping with relative ease and confidence. No soldering, glue, heat or external tools are required to join the pipe. Just insert the pipe and the stainless steel gripper ring, bite down, and hold the pipe tightly while the EPDM o-ring seals against leakage. Disassembly is just as fast using the optional disassembly tool, so fittings can be easily removed and re-used.

Applications

Jones Stephens' PlumBite® Push to Connect Reducing Tee Stops are approved for use with commercial and residential potable and non-potable water applications.

Materials

Gasket- EPDM, Peroxide Cured

Valve Body- Brass

Dimensions and Product Offering

PART NO. INDIVIDUAL	A NOMINAL (IN.)	B NOMINAL (IN.)	C NOMINAL (IN.)	D NOMINAL (IN.)	D TOLERANCE +/- (IN.)
C77445LF	0.75	0.75	0.25 OD COMP	3.04	0.12

Performance Specifications

Maximum Temperature - 180°F

Maximum Pressure - 200 PSI

Service: Potable Water

Exposure to water with elevated levels of inorganic materials (including but not limited to Cl, Na, Mg, Ca, K), especially in high temperatures and high water velocity areas, could quicken the corrosion process.

Certifications/Listings/Approvals

NSF/ANSI/CAN 61: Q

NSF/ANSI/CAN 372

NSF/ANSI 14

ASME A112.18.1/CSA B125.1

SDWA Compliant

Lead Law Compliant

MASS Approved

Vermont Act 193 Compliant

