

Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-3626-4	Version Number:	9.02
Issue Date:	02/08/18	Supercedes Date:	02/02/16

SECTION 1: Identification

1.1. Product identifier

3M[™] MSP Seam Sealer – White, PN 08369

Product Identification Numbers 60-4550-5013-2, 60-9800-2682-1, 60-9800-2687-0, 60-9800-3611-9

1.2. Recommended use and restrictions on use

Recommended use Automotive, Seam Sealer

1.3. Supplier's details	
MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number 1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Skin Sensitizer: Category 1. Reproductive Toxicity: Category 1B. Carcinogenicity: Category 1A.

2.2. Label elements Signal word Danger

Symbols Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

May cause an allergic skin reaction. May damage fertility or the unborn child. May cause cancer.

Precautionary Statements

General: Keep out of reach of children.

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear protective gloves. Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Limestone	1317-65-3	15 - 40 Trade Secret *
Calcium Carbonate	471-34-1	10 - 30 Trade Secret *
Silyl Terminated Polyether NJ Trade Secret Registry No. 04499600-6009P	Trade Secret*	10 - 30 Trade Secret *
Plasticizer - NJ Trade Secret Registry No. 04499600-	Trade Secret*	7 - 13 Trade Secret *
5988P		
Diisodecyl Phthalate	68515-49-1	1 - 5 Trade Secret *
Hydrotreated Heavy Naphtha (Petroleum)	64742-48-9	1 - 5 Trade Secret *
Stearic Acid	57-11-4	0.5 - 5 Trade Secret *
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	1760-24-3	< 1 Trade Secret *
1-Methyl-2-Pyrrolidinone	872-50-4	< 1 Trade Secret *
Dibutyltin bis(acetylacetonate)	22673-19-4	< 1 Trade Secret *
Quartz Silica	14808-60-7	< 0.5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

3M[™] MSP Seam Sealer – White, PN 08369 02/08/18

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide <u>Condition</u> During Combustion During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

3M [™] MSP Seam Sealer – White, PN 08369	02/08/18	

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Limestone	1317-65-3	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable	A2: Suspected human
			fraction):0.025 mg/m3	carcin.
Quartz Silica	14808-60-7	OSHA	TWA Table Z-	
			1(respirable):0.05	
			mg/m3;TWA Table Z-	
			3(respirable):0.1 mg/m3	
TIN, ORGANIC COMPOUNDS	22673-19-4	ACGIH	TWA(as Sn):0.1	SKIN, A4: Not class. as
			mg/m3;STEL(as Sn):0.2	human carcin
			mg/m3	
TIN, ORGANIC COMPOUNDS	22673-19-4	OSHA	TWA(as Sn):0.1 mg/m3	
Limestone	471-34-1	OSHA	TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
STEARATES	57-11-4	ACGIH	TWA(inhalable fraction):10	A4: Not class. as human
			mg/m3;TWA(respirable	carcin
			fraction):3 mg/m3	
Naphtha	64742-48-9	OSHA	TWA:400 mg/m3(100 ppm)	
1-Methyl-2-Pyrrolidinone	872-50-4	AIHA	TWA:40 mg/m3(10 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Solid
Specific Physical Form:	Paste
Odor, Color, Grade:	White thick paste
Odor threshold	No Data Available
рН	Not Applicable
Melting point	Not Applicable
Boiling Point	No boiling point
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	Not Applicable
Vapor Density	Not Applicable
Density	1.68 g/cm3
Specific Gravity	1.68 [<i>Ref Std</i> :WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available

Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	15,000 - 20,000 poise [Test Method:Brookfield]
	[Details:CONDITIONS: Spindle #7, 2 rpm]
Hazardous Air Pollutants	0.0009 lb HAPS/lb solids [<i>Test Method</i> :Calculated]
Molecular weight	No Data Available
Volatile Organic Compounds	100 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	6 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	6 % weight
VOC Less H2O & Exempt Solvents	100 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat Sparks and/or flames

10.5. Incompatible materials Strong acids

Strong actus

10.6. Hazardous decomposition products

<u>Substance</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Condition

Page 6 of 13

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYS AIRRESP	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Quartz Silica	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Additional Information:

This product contains a form of crystalline silica. Occupational exposure to inhaled crystalline silica has been associated with silicosis and lung cancer. No exposure to crystalline silica is expected during the normal handling and use of this product. Therefore, the health effects associated with crystalline silica are not expected during normal use of this product.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE >50 mg/l
	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		
	(4 hours)		
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Calcium Carbonate	Dermal	Rat	LD50 > 2,000 mg/kg
Calcium Carbonate	Inhalation-	Rat	LC50 3 mg/l
	Dust/Mist		
	(4 hours)		
Calcium Carbonate	Ingestion	Rat	LD50 6,450 mg/kg
Silyl Terminated Polyether NJ Trade Secret Registry No.	Dermal		LD50 estimated to be > 5,000 mg/kg
04499600-6009P			
Silyl Terminated Polyether NJ Trade Secret Registry No.	Ingestion	Rat	LD50 > 20,000 mg/kg

04499600-6009P			
Plasticizer - NJ Trade Secret Registry No. 04499600-5988P	Dermal	Rabbit	LD50 > 5,000 mg/kg
Plasticizer - NJ Trade Secret Registry No. 04499600-5988P	Ingestion	similar compoun ds	LD50 estimated to be 300 - 2,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation- Vapor		LC50 estimated to be 20 - 50 mg/l
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	Rabbit	LD50 > 3,000 mg/kg
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Diisodecyl Phthalate	Dermal	Rabbit	LD50 > 3,160 mg/kg
Diisodecyl Phthalate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 12.5 mg/l
Diisodecyl Phthalate	Ingestion	Rat	LD50 > 9,700 mg/kg
Stearic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Stearic Acid	Ingestion	Rat	LD50 > 5,000 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Inhalation- Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Ingestion	Rat	LD50 1,897 mg/kg
1-Methyl-2-Pyrrolidinone	Dermal	Rabbit	LD50 4,000 mg/kg
1-Methyl-2-Pyrrolidinone	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
1-Methyl-2-Pyrrolidinone	Ingestion	Rat	LD50 4,320 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dibutyltin bis(acetylacetonate)	Dermal	Rat	LD50 > 2,000 mg/kg
Dibutyltin bis(acetylacetonate)	Ingestion	Rat	LD50 1,864 mg/kg

 $\overline{\text{ATE}}$ = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	Irritant
Diisodecyl Phthalate	Rabbit	Minimal irritation
Stearic Acid	Rabbit	No significant irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Mild irritant
1-Methyl-2-Pyrrolidinone	Rabbit	Minimal irritation
Quartz Silica	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Dibutyltin bis(acetylacetonate)	Rat	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Calcium Carbonate	Rabbit	No significant irritation
Hydrotreated Heavy Naphtha (Petroleum)	Rabbit	No significant irritation
Diisodecyl Phthalate	Rabbit	Mild irritant
Stearic Acid	Rabbit	No significant irritation
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Rabbit	Corrosive
1-Methyl-2-Pyrrolidinone	Rabbit	Severe irritant
Dibutyltin bis(acetylacetonate)	In vitro	Corrosive
	data	

Skin Sensitization

Name	Species	Value

3MTM MSP Seam Sealer – White, PN 08369 02/08/18

Hydrotreated Heavy Naphtha (Petroleum)	Guinea	Not classified
	pig	
Diisodecyl Phthalate	Guinea	Not classified
	pig	
1,2-Ethanediamine, N1-[3-(trimethoxysilyl)propyl]-	Multiple	Sensitizing
	animal	
	species	
1-Methyl-2-Pyrrolidinone	Human	Not classified
	and	
	animal	
Dibutyltin bis(acetylacetonate)	Guinea	Sensitizing
	pig	

Respiratory Sensitization For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrotreated Heavy Naphtha (Petroleum)	In vivo	Not mutagenic
Hydrotreated Heavy Naphtha (Petroleum)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Diisodecyl Phthalate	In Vitro	Not mutagenic
Diisodecyl Phthalate	In vivo	Not mutagenic
Stearic Acid	In Vitro	Not mutagenic
1-Methyl-2-Pyrrolidinone	In vivo	Not mutagenic
1-Methyl-2-Pyrrolidinone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Dibutyltin bis(acetylacetonate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dibutyltin bis(acetylacetonate)	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrotreated Heavy Naphtha (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Stearic Acid	Ingestion	Rat	Not carcinogenic
1-Methyl-2-Pyrrolidinone	Inhalation	Rat	Not carcinogenic
Quartz Silica	Inhalation	Human and animal	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Calcium Carbonate	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesi s

Diisodecyl Phthalate	Ingestion	Not classified for female reproduction	Rat	NOAEL 927 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Not classified for male reproduction	Rat	NOAEL 929 mg/kg/day	2 generation
Diisodecyl Phthalate	Ingestion	Toxic to development	Rat	NOAEL 38 mg/kg/day	2 generation
1-Methyl-2-Pyrrolidinone	Inhalation	Not classified for development	Rat	LOAEL 0.68 mg/l	during gestation
1-Methyl-2-Pyrrolidinone	Ingestion	Toxic to female reproduction	Rat	LOAEL 50 mg/kg/day	2 generation
1-Methyl-2-Pyrrolidinone	Ingestion	Toxic to male reproduction	Rat	LOAEL 50 mg/kg/day	2 generation
1-Methyl-2-Pyrrolidinone	Dermal	Toxic to development	Rat	NOAEL 237 mg/kg/day	during organogenesi s
1-Methyl-2-Pyrrolidinone	Ingestion	Toxic to development	Rat	NOAEL 160 mg/kg/day	2 generation
Dibutyltin bis(acetylacetonate)	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	premating into lactation
Dibutyltin bis(acetylacetonate)	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Calcium Carbonate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Hydrotreated Heavy Naphtha (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Stearic Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1,2-Ethanediamine, N1-[3- (trimethoxysilyl)propyl]-	Inhalation	respiratory irritation	May cause respiratory irritation	similar health hazards	NOAEL Not available	
1-Methyl-2-Pyrrolidinone	Inhalation	respiratory irritation	Not classified	Human	NOAEL 0.05 mg/l	8 hours
Dibutyltin bis(acetylacetonate)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Calcium Carbonate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks

3MTM MSP Seam Sealer – White, PN 08369 02/08/18

Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Hydrotreated Heavy Naphtha (Petroleum)	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Diisodecyl Phthalate	Inhalation	respiratory system hematopoietic system liver	Not classified	Rat	NOAEL 0.5 mg/l	2 weeks
Diisodecyl Phthalate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.5 mg/l	2 generation
Diisodecyl Phthalate	Ingestion	endocrine system	Not classified	Rat	NOAEL 686 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	liver kidney and/or bladder heart	Not classified	Rat	NOAEL 500 mg/kg/day	90 days
Diisodecyl Phthalate	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 320 mg/kg/day	90 days
Stearic Acid	Ingestion	blood	Not classified	Rat	NOAEL Not available	6 weeks
1-Methyl-2-Pyrrolidinone	Inhalation	bone marrow immune system respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.5 mg/l	4 weeks
1-Methyl-2-Pyrrolidinone	Ingestion	endocrine system	Not classified	Rat	NOAEL 250 mg/kg/day	90 days
1-Methyl-2-Pyrrolidinone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,060 mg/kg/day	4 weeks
1-Methyl-2-Pyrrolidinone	Ingestion	nervous system	Not classified	Rat	NOAEL 1,057 mg/kg/day	90 days
1-Methyl-2-Pyrrolidinone	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 300 mg/kg/day	90 days
1-Methyl-2-Pyrrolidinone	Ingestion	liver	Not classified	Mouse	NOAEL 150 mg/kg/day	3 months
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Dibutyltin bis(acetylacetonate)	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrotreated Heavy Naphtha (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards Not applicable

Health Hazards	
Carcinogenicity	
Reproductive toxicity	
Respiratory or Skin Sensitization	

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	<u>C.A.S. No</u>	Regulation	<u>Status</u>
1-Methyl-2-Pyrrolidinone	872-50-4	Toxic Substances Control Act (TSCA) 6	Proposed
		Banned or Restricted Use Chemicals	

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

Ingredient	C.A.S. No.	Listing
SILICA, CRYSTALLINE (AIRBORNE	None	Carcinogen
PARTICLES OF RESPIRABLE SIZE)		
Arsenic	7440-38-2	Carcinogen
Cadmium	7440-43-9	Male reproductive toxin
Cadmium	7440-43-9	Carcinogen
Cadmium	7440-43-9	Developmental Toxin
Mercury	7439-97-6	Developmental Toxin
Nickel	7440-02-0	Carcinogen
Lead	7439-92-1	Female reproductive toxin
Lead	7439-92-1	Male reproductive toxin
Lead	7439-92-1	Carcinogen
Lead	7439-92-1	Developmental Toxin

Cobalt	7440-48-4	Carcinogen
Diisodecyl Phthalate	68515-49-1	Developmental Toxin
1-Methyl-2-Pyrrolidinone	872-50-4	Developmental Toxin

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard ClassificationHealth: *2Flammability: 1Physical Hazard: 0Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	07-3626-4	Version Number:	9.02
Issue Date:	02/08/18	Supercedes Date:	02/02/16

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued.3MMAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.User is responsible for determining whether the 3Mproduct is fit for a particular purpose and suitable for user's method of use or application.Given the variety of factors that can affect the use and application of a3Mproduct, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3Mproduct to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3Mprovides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information,3Mmakes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from3M

3M USA SDSs are available at www.3M.com