Defcon®-2 Industrial Cleaner Degreaser HILOO45509





Defcon® 2 is a concentrated industrial degreaser designed for everyday grease and grime. Defcon 2 is versatile enough to be used in an autoscrubber, mop buckets and spray bottles. Defcon 2 is concentrated to be cost effective in use. Simply dilute Defcon 2 at a rate of 4 to 8 oz. per gallon of water and you have an effective degreasing solution. Defcon 2, packed in a 55 gallon drum, is designed to be the starter drum for Defcon®-2R. When your Defcon 2 drum runs out, simply mix a 5 gallon bag- in-box of Defcon-2R SUPER Concentrate with 50 gallons of water in the drum and you have a full drum of concentrated degreaser ready to be diluted.

Features & Benefits

Designed to remove everyday grease and grime Concentrated Cost-Effective.

Can be used in autoscrubber, mop bucket and spray bottle.

Concentrated and Cost-Effective.

Item Number & Unit of Measure

Item Number	HIL0045509
Unit of Measure	55 gal Drum

Specifications

Color	Amber
Appearance	Colorless to light
Fragrance	Non-Objectionable
Formula Type	Liquid

Dilution Ratio	1:16 - 1:32
PH	11.00 - 12.50
Non-Volatile Matter	3.00 - 4.00%
NSF_Certified	Yes

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Formulated to accelerate the removal of oil, dirt, grease, and grime from floors, walls, equipment, vehicles, metal buildings and more. Apply diluted Defcon 2 with an automatic scrubber, sprayer, brush, mop, or sponge. Defcon 2 may also be used with high pressure cleaning equipment. Remains stable up to 180°F for use with hot water for improved cleaning efficiency. Excellent for cleaning and degreasing floors, air filters, exhaust hoods, conveyors, walls, metal equipment, and basically any hard surface not damaged by water. A potable water rinse after product use.

Light Cleaning (with autoscrubbing equipment): Dilute: 4 oz Defcon 2 per gallon of water.

Heavy Cleaning: Dilute: 6 oz Defcon 2 per gallon of water. Heavy Duty Degreasing: Dilute: 8 oz Defcon 2 per gallon of water.

NOTICE: Test solution on inconspicuous area when using on a surface for first time. DO NOT PROCEED if adverse effects occur on paint, metal, or other surfaces. Rinse vehicles and glass thoroughly after use.