



TRENDSETTER™

sealer/finish

The Trendsetter formulation is a synergistic blend of modified acrylic polymers coupled with durable, high-pressure, emulsified polyolefin waxes. Trendsetter is 20% solids, burnishable sealer/finish for use with high speed machines. It provides a wet look gloss, level finish and extended durability.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
1110 Spartan Drive
Maumee, OH 43537
1-800-537-8990
www.spartanchemical.com

PROACTIVE SYNERGY:

The Trendsetter formula represents breakthrough finish technology in that it combines high gloss through its modified acrylic polymers with the durability provided by high pressure polyolefin waxes. The end result is a highly burnishable finish with high shine and long life.

SEAL AND FINISH WITH ONE PRODUCT:

Trendsetter is its own seal. Users only need to stock one product instead of two, eliminating employee confusion.

“WET LOOK” SHINE:

Trendsetter creates a clear, bright, non-yellowing gloss on flooring. Not only is initial gloss impressive, but high shine and depth of gloss actually builds after repeated burnishings. Trendsetter stays glossy even after numerous scrubs with a neutral cleaner.

EASY TO APPLY AND MAINTAIN:

Trendsetter levels easily with no mop drag or cut-in and Trendsetter resists soil and scuff marks. Maintenance is easy. Simply dry buff as necessary depending upon traffic.

TREMENDOUS LABOR SAVINGS:

Since Trendsetter extends the time between strip-outs and eliminates the need to seal or use restorers, users benefit from low in-use costs due to the labor savings. In fact when compared to leading competitive products, market tests have shown Trendsetter can extend the time between strip-outs a minimum of 20%...as high as 50%!

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before use, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

Time Saving Ultra High Speed System:

Completely strip all floor finish. Depending upon build-up, use warm or room temperature water (80°F-120°F or 27°C-49°C) and a Spartan Stripper. Remove the stripping solution and either follow with Shinline Floor Prep or two to three clear-water rinses. Allow to dry.

Seal and Finish:

Apply Trendsetter in a uniform, thin coat. Let dry thoroughly (twenty to 40 minutes depending upon temperature, humidity and ventilation). Apply subsequent coats in the same manner. Five coats are recommended for initial application.

Maintain:

Dust mop and damp mop. High speed burnish as necessary depending upon traffic to repair minor scratches and enhance gloss. Deep scrub as required and rinse with clear water prior to recoating. Depending upon machine type and speeds, experiment with buffing pads for quick touch ups of high traffic or “first impression” areas.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 26.65%
Non-Volatile Solids – 20.0%
Specific Gravity – 1.0245 @ 24°C/75°F
pH (Concentrate) – 8.5 - 9

Stability

- a. Storage @ 24°C/75°F – One year minimum
- b. Accelerated @ 49°C/120°F – 30 days minimum
- c. Freeze/Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 90
- b. 2 coats – 95

Static coefficient of friction meets or exceeds 0.5 as determined by ASTM method D 2047.

COVERAGE:

2,500 to 3,000 square feet per gallon depending on application method and porosity of floor.

NOTE: For best maintenance results, always use Spartan floor cleaners and strippers.

PACKAGING

401065	330-gallon totes
401060	275-gallon totes
401055	55-gallon drum
401030	30-gallon drum
401015	15-gallon drum
401005	5-gallon pail
401004	1-gallon (4 per case)



Distributed by:

Label copy is available in English, Spanish and French. Secondary labels are also available.

GUARANTEE: Spartan’s modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 5/11 L4010