

**HOLDRITE**

14284 Danielson Street Poway
CA 92064

Phone: 800-321-0316

Email: sales@holdrite.com

Website: www.holdrite.com

Item # 40-S-34-U, Holdrite - 40-S-34-U

The QUICKSTAND™ #40-S-34-U stands safely elevates water heaters and other equipment above the floor (2,000 lbs rating).



Specifications | Features

Specifications

Configuration	Unassembled
Top Material	11 gage CRS, galvanized
Leg Material	16 gage CRS, galvanized
Safety Clip Material	14 gage CRS, galvanized
Attachment Bracket Material	11 gage CRS, galvanized
Load Capacity	2000 lb
Use With	typical 100 to 120 U.S. gallon plus

Includes

Attachment Bracket
Hex Bolts - #1/4-20 x 5/8"L (36)
Legs (5)
Nut, Hex - #1/4-20 (40)
Safety Clips (2)
Screw, Machine - #1/4-20 x 5/8"L, SST, 100° Phillips Flat Head (4)
Top
Washers - #1/4, External Tooth, Lock (40)

Weight

61 lb

Features

Available in unassembled configuration ONLY.
Engineered and lab tested to meet Uniform Plumbing Code (UPC) and International Plumbing Code (IPC) requirements, including elevation of water heater's ignition source 18" above the floor.