



MEDIUM DUTY GRADE GUM PAPER TAPE

TYPICAL APPLICATIONS

• For light- to medium-weight packaging applications such as inner carton sealing or palletized loads

PRODUCT FEATURES

- Conformable
- Strong and durable 60-pound paper backing
- Aggressive water activated adhesive becomes part of the carton

CONSTRUCTION

Overall Grade/Function: Medium Duty Backing: Non-reinforced kraft paper Adhesive: Water activated

STANDARD WIDTH(S)

2 ½ in 3 in

STANDARD LENGTH(S)

600 ft Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES	STANDARD	METRIC
Thickness	5.6 mils	0.14 mm
MD Tensile Strength	45 lbs/in	78.8 N/10 mm
CD Tensile Strength	23 lbs/in	40.3 N/10 mm
Paper Sheet Weight	60 lbs	27.21 kg

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

