

GENERAL PURPOSE GRADE CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- General purpose packaging, bundling, holding, splicing, masking and labeling for industry


ADVANTAGES AND BENEFITS

- Economical, with good performance on a variety of substrates
- Excellent quick stick and holding power
- Higher adhesion than CP 105

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Crepe paper
Adhesive: Thermoplastic rubber adhesive

COLOR(S)



STANDARD WIDTH(S)

12 mm 18 mm 24 mm
36 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	19 lbs/in width	33.2 N/10 mm
Adhesion to Stainless Steel	38 oz/in width	4.16 N/10 mm
Thickness	4.8 mils	0.12 mm
Elongation	8%	8%
Service Temperature Range	60 F to 150 F	16 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC
Form# TDS-CP-106-01/30/2014

