

CP 399



FROGTAPE® HIGH BOND EXTERIOR PAINTER'S TAPE



TYPICAL APPLICATIONS

- For exterior use on surfaces such as painted wood, vinyl, aluminum, steel, brick, stucco, and concrete, and for keeping poly in place for spraying during paint projects

PRODUCT FEATURES

- Very high adhesion
- 3-day clean removal
- Conformable crepe paper
- Engineered to stick to self-cleaning paint technology

CONSTRUCTION

Overall Grade/Function: Exterior Specialty

Backing: Crepe paper

Adhesive: Rubber-based

STANDARD WIDTH(S)

36 mm

STANDARD LENGTH(S)

55 m

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



NATURAL
(NAT)

PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength

24 lbs/in width

42.0 N/10 mm

Adhesion to Stainless Steel

62 oz/in width

6.79 N/10 mm

Thickness

6.7 mils

0.17 mm

Elongation

10%

10%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape

TECHNOLOGIES

Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtape.com

ISO 9001 CERTIFIED QUALITY SYSTEM

High Bond Exterior Painter's Tape™ is a trademark of Shurtape Technologies, LLC. FrogTape® and Shurtape® are registered trademarks of Shurtape Technologies, LLC. Form# TDS-CP-399-MMC00344-05/31/2022