

**GENERAL PURPOSE  
DOUBLE-FACED FLAT PAPER TAPE**

**TYPICAL APPLICATIONS**

- Mounting, holding, splicing, tabbing and fastening of a variety of substrates when an aggressive adhesive is needed

**ADVANTAGES AND BENEFITS**

- Good tensile strength
- Superior, aggressive adhesion to a variety of substrates
- Durable
- Both tape and release liner are wrinkle-resistant
- Hand tearable

**CONSTRUCTION**

Overall Grade/Function: General Purpose  
 Backing: Flat paper  
 Adhesive: Aggressive rubber-based  
 Liner: Non-contaminating, siliconized, flat paper release liner



**COLOR(S)**

White (WHI)

**STANDARD WIDTH(S)**

**STANDARD LENGTH(S)**

½ in	18 mm	24 mm	36 yd	33 m
36 mm	48 mm	72 mm		

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	<b>STANDARD</b>	<b>METRIC</b>
Tensile Strength	33 lbs/in width	57.8 N/10 mm
Adhesion to Stainless Steel	66 oz/in width	7.22 N/10 mm
Thickness	5 mils	0.13 mm
Elongation	2.5%	2.5%
Service Temperature Range	50 F to 225 F	10 C to 107 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE STANDARDS**

CID A-A-180C, Type II, Grade B

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-DF-65-10/24/2014