

P205UCPDQ | HOME OFFICE SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The CyberPower P205UCPDQ brings you power, protection, and versatility - all in one compact unit. Featuring two AC power outlets with 1,500J of surge protection, 1 USB-A charging port, 1 USB-C charging port, and a 10W wireless Qi charging pad that works with iPhone and Android phones. It's perfect for desktops, tabletops or other high-traffic areas of the home or office.



TYPICAL APPLICATIONS

- Personal Electronics
- Wireless Speakers
- Cell Phones
- Tablets

FEATURES

- Surge suppression: 1,500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 2
- Total USB Output: 20W PD
- USB-C charge ports: 1
- USB-C charge output: 20W
- USB-A charge ports: 1
- USB-A charge output: 2.4A
- Wireless Charging: Qi 10W

- Power cord length: 5 ft
- Power cord type: braided
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000

SPECIFICATIONS

INPUT	
Cord Length	5 ft (1.5 m)
Input Voltage	125 VAC
Input Plug Type	NEMA 5-15R
Input Voltage	110 - 125 VAC
Maximum Input Current	15A
Plug Style	Right Angle - 45° Offset

OUTPUT	
Outlet Type	2 - NEMA 5-15R
Outlets - Total	2
USB Charge Port	Yes
USB Charge Port Amperage	2.4 A (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A, 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	20 Watts
Wireless Charging	Yes
Wireless Charging Output	10 W
Wireless Charging Type	Qi Certified

P205UCPDQ

HOME OFFICE SURGE PROTECTOR

SPECIFICATIONS - CONT.

SURGE PROTECTION & FILTERING		SHIPPING DIMENSIONS	
Clamping Voltage	600V (H-N, H-G, N-G)	Shipping Dimensions - Width/Height/Depth (cm)	13.34 x 16.26 x 8.38 cm
Maximum Surge Current	15,000 A	Shipping Dimensions - Width/Height/Depth (mm)	133.35 x 162.56 x 83.82 mm
PHYSICAL		Shipping Dimensions - Width/Height/Depth (in)	5.25 x 6.4 x 3.3 in.
Maximum Surge Current H-N	15,000 A	Weight (kg)	0.68 kg
Maximum Surge Voltage	6,000 V	Weight (lb)	1.50 lbs.
Response Time	<1 Nanosecond	CERTIFICATIONS	
Surge Suppression (Joules)	1,500 J	Environmental	RoHS Compliant
PHYSICAL DIMENSIONS		Safety	
Physical Dimensions - Width/Height/Depth (cm)	8.41 x 4.29 x 8.41 cm	UL1449 UL2738 UL1310 FCC cUL DOE VI	
Physical Dimensions - Width/Height/Depth (mm)	84 x 43 x 84 mm	WARRANTY	
Physical Dimensions - Width/Height/Depth (in.)	3.31 x 1.69 x 3.31 in.	CEG Amount	\$100,000
Weight (kg)	0.54 kg	Connected Equipment Guarantee	Lifetime
Weight (lb)	1.20 lbs.	Product Warranty	One-Year Limited Warranty