

1082 series surface mount contacts

screw mount magnetic contacts with wire leads

The 1082 series surface mount contacts are designed for use in installations where a larger sealed unit is required. The reed switch is totally encapsulated in GE Security's exclusive polyurethane potting compound, which prevents moisture from entering the switch and causing false alarms.

The 1 inch standard gap distance allows for fast, easy installation and prevents false alarms due to loose-fitting doors.



Specifications

Voltage:	1082: 100 VAC/VDC max. 1084: 30 VAC/VDC max.
Current:	1082: 0.5 A max. 1084: 0.25 A max.
Power:	1082: 7.5 W max. 1084: 3.0 W max.
Loop type:	1082: Closed 1084: Open or Closed
Electrical configuration:	1082: Normally open 1084: SPDT 1084D: DPDT
Gap distance:	1082/1084: Up to 1 in. 1084D: Up to 3/4 in.
Lead type:	1 ft. #22 wire
Dimensions (WxHxD):	2.56 x 0.56 x 0.50 in. (53 x 14 x 13 mm)
Housing:	Flame retardant ABS plastic
Color:	White, brown, gray
Regulatory:	UL

- Sealed switch assembly
- Mounting hardware included
- Several models available, including wide gap, SPDT, and DPDT
- Long gap distance helps prevent false alarms caused by loose-fitting doors

Ordering information

1082N-10PKG	Surface screw mount contact with wire leads, long gap series, 1 in. gap size, closed loop, white, pk/10
1082G-10PKG	Surface screw mount contact with wire leads, long gap series, 1 in. gap size, closed loop, gray, pk/10
1084M-10PKG	Surface screw mount contact with wire leads, long gap series, 1 in. gap size, SPDT, brown, pk/10
1084DN-10PKG	Surface screw mount contact with wire leads, 3/4 in. gap size, DPDT, white, pk/10

