



CRC Industries NZ, Auckland NZ

I. Product Description

CRC NOXY is a multipurpose high strength lubricant and CC3 based anti-corrosion formula, which is safe to use on almost any surface and application, being non-toxic, non-staining, non-static and non-conductive. It will not dry out or wash off with water, making it ideal for industrial applications as well as recreational and home use.

CRC NOXY utilises a specific grade of oil with unique properties that makes it the ideal product for applications requiring oilier lubrication. Its long lasting properties leaves a colourless coating where it has been applied. The applied film has no odour.

CRC NOXY will stay in place for long periods of time without drying out or becoming sticky - Penetrating corrosion whilst displacing moisture. Containing NO silicone, acid, kerosene or dieselene, it will not harm any plastics, metals, paints, enamels, fibreglass, Formica or neoprene seals.

II. Features & Benefits

- Permastraw™ dual-action spray system
- Displaces, penetrates, lubricates, and protects
- Contains no silicone, acid, kerosene, or dieselene
- Won't dry out, gum up, become gooey or sticky, or wash off with water
- Non-conductive, Non-static, Non-toxic, Non-corrosive, and Non-staining
- MPI Approved C14 - Food Grade

III. Typical Properties and Characteristics

Colour (ASTM D1500)	0.5 Max
Flash Point	205°C (TCC)
Boiling Point	+215°C Initial
Propellant	Hydrocarbon
Viscosity	28-30 cSt @ 40°C
Acid Number	<0.05 mg KOH
Type of film	Thin, oily film
Dry Time	Non-drying wet oil
Temperature Range	-20°C to +150°C (continuous), +170°C (intermittent)

IV. Application and Directions

- 1) Shake can well before using
- 2) Spray when required
- 3) Extend Permastraw™ for those hard to reach places

V. Package Description

Part Number	Size
3027	400ML Aerosol



CRC Industries NZ, Auckland NZ

VI. *Special Precautions*

Read label before use.

General:

Use with adequate ventilation. Store in a cool, well-ventilated area. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

First Aid:

Swallowed – Not considered a normal route of entry.

Skin – Remove contaminated clothing and wash skin thoroughly with soap and water. Remove any adhering solids with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation. Wash contaminated clothing before reuse.

Eyes – Immediately hold the eyelids apart and flush the eye continuously for at least 15 minutes with fresh running water.

Inhaled – Remove to fresh air. Lay patient down. Keep warm and rested.

In Case of Emergency - Phone 09 278 7913

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version **08/2016**

PRODUCT WARRANTY: CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

DISCLAIMER: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.