



P504UC HOME OFFICE SURGE PROTECTION

Protect home and office computers, electronics, and home theater equipment

The CyberPower Surge Protector P504UC prevents spikes in energy caused by storms and electrical power surges from reaching your home electronics such as audio/video equipment, laptops and desk top computers, household appliances and small electronics. The P504UC provides 500 joules of surge protection, 5 AC outlets, 1 USB-C charging port, 1 USB-A charging port, and a braided 4-foot power cord with a right-angle plug.

Features of the P504UC include automatic shutdown, an EMI/RFI noise filter, metal oxide varistor (MOV) technology, an On/Off switch with integrated 15-Amp circuit breaker, LED indicator, low profile plug, keyhole mounting slots, and damage-resistant construction. This surge suppressor comes with a One-Year Limited Warranty and a \$25,000 Connected Equipment Guarantee.



TYPICAL APPLICATIONS

- Gaming Systems
- Consumer Electronics
- Chargers
- Laptop Computers

FEATURES

- Surge suppression: 500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 5
- Total USB Output: 15W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 2
- USB charge output: 2.4A
- Power cord length: 4 ft
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Circuit breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$25,000

SPECIFICATIONS

INPUT	
Circuit Breaker	15 A
Cord Length	4 ft (1.2 m)
Input Plug Type	NEMA 5-15P
Maximum Input Current	15 A
Plug Style	Low Profile

OUTPUT	
Outlet Type	5 - NEMA 5-15R
Outlets - Total	5
USB Charge Port	Yes
USB Charge Port Amperage	2.4 Amps (Shared)
USB Charge Port Quantity	2
USB Charge Port Type	1 Type A 1 Type C
USB Charge Port Voltage	5 VDC
USB Charge Port Watts	15 Watts

P504UC

HOME OFFICE SURGE PROTECTION

SPECIFICATIONS - CONT.

SURGE PROTECTION AND FILTERING

Clamping Voltage	800V (H-N)
EMI/RFI Filtration	150 KHz 100 MHz Yes
Maximum Surge Current	15,000 A
Maximum Surge Current H-N	15,000 A
Maximum Surge Voltage	6,000 V
Surge Suppression (Joules)	500 J

PHYSICAL

Color	White
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)
Material of Construction	Plastic

PHYSICAL DIMENSIONS

Physical Dimensions - Width/Height/Depth (cm)	4.55 x 3.81 x 24.79 cm
Physical Dimensions - Width/Height/Depth (mm)	45 x 38 x 248 mm
Physical Dimensions - Width/Height/Depth (in.)	1.79 x 1.50 x 9.76 in.
Weight (kg)	0.34 kg
Weight (lb)	0.75 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - Width/Height/Depth (cm)	4.55 x 7.04 x 24.69 cm
Shipping Dimensions - Width/Height/Depth (mm)	45.47 x 70.36 x 246.89 mm
Shipping Dimensions - Width/Height/Depth (in)	1.79 x 2.77 x 9.72 in.
Weight (kg)	0.38 kg
Weight (lb)	0.837 lbs.

CERTIFICATIONS

Environmental	RoHS Compliant
Safety	UL1449 3rd Edition UL1363 UL1310 FCC cUL DOE VI

WARRANTY

CEG Amount	\$25,000
Connected Equipment Guarantee	Lifetime
Product Warranty	One-Year Limited Warranty