



A water emulsion finish formulated to protect synthetic sports floors, enhance their appearance, and make them easier to clean and maintain. Protective Coating stands up to scuffing, scratching, rubber burns, and heel marks. And Protective Coating retains its gloss even after months of wear in the busiest of gyms. It not only helps protect the floor, but makes cleaning, dust mopping, and periodic damp mopping much easier. Rubber burns, scuffs, and dirt are held in the surface of the film where they can be easily removed.

Features & Benefits

- 18% solids clear acrylic copolymer for enhanced appearance.
- Self-leveling for easy application.
- Minimum maintenance required which reduces labor cost.
- Excellent black heel mark and scratch resistance.

Item Number & Unit of Measure

Item Number	HIL0029107
Unit of Measure	5 gal BIB

Specifications

Color	White
Appearance	Milky Emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
PH	8.00-9.00
Non-Volatile Matter	17.50 - 18.50%

Solids Content	18
Coverage SqFt/Gallon	1500-2000
Dry Time (hrs.)	2-4
Sheen	Gloss

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Always check with the flooring manufacturer's warranty concerning the use of maintenance products on your floor. Once warranty has expired or, at your discretion, you decide to use Protective Coating, follow the steps below.

Preparation: Uncoated floors: Scrub with a solution of Hillyard Salvation, following label directions, and a blue pad. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour.

Scrub and recoat: Scrub the existing floor polish with a solution of Hillyard Salvation, following label directions, and a blue pad. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour.

Stripping: Strip Protective Coating from the floor with a solution of Hillyard Salvation, following label directions. Pick up scrubbing solution with an automatic scrubber or wet vacuum. Flood rinse with a solution of Hillyard Nutra-Rinse and pick up solution with an automatic scrubber or wet vacuum. Damp mop rinse twice with water and allow to dry for at least 1 hour.

Application: Apply a minimum of 2 coats of Protective Coating at a rate of 1500-2000 ft²/gallon with a microfiber flat finish mop or Multi-Flo XP. Allow each coat to dry a minimum of 30 minutes before applying the next. If needed, additional coats may be applied. **NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C). For best results, do not apply more than 3-4 coats per day.

Maintenance: Use a cotton dust mop, treated with Hillyard Super Hil-Tone, daily to remove loose dirt and grit. Damp mop or autoscrub, as scheduled, with Hillyard Clean Scrub. Scrub and recoat, as scheduled, with a minimum of 2 coats of Protective Coating.

FLOOR PAD RECOMMENDATIONS:
 Stripping: black; Scrub and Recoat: blue; Autoscrubbing: red.
NOTICE: Do not use an ammoniated cleaner for daily care. Do not pour unused finish or seal back into the original container.

