



Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	1:1 - 1:6
PH	> 13 - < 14
Non-Volatile Matter	7.39%

### Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

### Directions for Use

**DIRECTIONS:** Do not use on asphalt tile, linoleum, synthetic sports floors, or rubber, painted, or varnished surfaces. (DO NOT USE ON WOOD.) **Pretest:** Test in an inconspicuous area using a 1:1 dilution. Allow to stand on the floor for 10 minutes. Wipe off with a towel, rinse, and examine the floor for bleeding or softening. Do not continue use of product if any bleeding or softening is observed. **Application:** Do not use with hot water or spray method. Apply with a clean mop to a small area (less than 200 sq ft) at a 1:6 dilution (may be increased to 1:1 for heavy buildup). Allow to stand for 3 to 5 minutes, then agitate with a mop. Do not allow solution to dry on the floor. Stripper may be agitated with a floor machine for extremely heavy buildup. Use the least abrasive pad possible for stripping. (Do not use abrasive pads on tile containing asbestos.) Work small areas, keeping floor wet at all times. Pick up the stripping solution with a wet vac, mop, or autoscrubber. Rinse thoroughly with Nutra-Rinse® solution. Pick up the solution and damp mop with clean water. Repeat if the polish is not removed. Apply polish after the floor is clean and dry. **NOTICE:** Floor may become slippery when stripper is present. Stripper vapors or liquid may cause discoloration on uncured, light-colored painted surfaces. **DISCLAIMER OF WARRANTY:** Seller makes no warranty of any kind, express or implied, except that this product shall be of seller's standard quality. **NOTICE: DO NOT USE ON POLISHED MARBLE**

Assault® XL is a premium stripper engineered for efficiency, featuring a low-odor formulation. This fast-acting formulation quickly cuts through built-up floor finish, even if the finish has been hardened by burnishing. The low-odor, non-butyl formulation makes this stripper an exceptional choice for healthcare applications and long-term care facilities where strong odors can impact occupants. Picking up emulsified floor finish is easy and efficient due to the low-foaming nature of this stripper. Additionally, Assault® XL is phosphate-free to lower environmental impact. Recommended for use on tough stripping jobs on quarry tile, paver brick, terrazzo, concrete, and vinyl composition flooring. Do not use Assault® XL on asphalt tile, linoleum, rubber, or painted surfaces.

### Features & Benefits

Low odor, butyl-free for reduced impact on building occupants

Highly effective and economical cost in use

Use with cold water, with or without a scrubbing machine

### Item Number & Unit of Measure

Item Number	HIL0015107
Unit of Measure	5 gal BIB

### Specifications

Color	Pale Yellow
Appearance	Clear, pale yellow

