

## FROGTAPE® HIGH BOND EXTERIOR PAINTER'S TAPE®

### TYPICAL APPLICATIONS

- For exterior use on surfaces such as painted wood, vinyl, aluminum, steel, brick, stucco and concrete, and for keeping poly in place for spraying during paint projects.

### PRODUCT FEATURES

- Very high adhesion
- 3-day clean removal
- Withstands direct outdoor sunlight for up to 1 day
- Conformable crepe paper backing
- Engineered to stick to self-cleaning paint technology
- DOES NOT contain PaintBlock® Technology

### CONSTRUCTION

Backing: Crepe paper

Adhesive: Rubber-based adhesive

### STANDARD WIDTH

1.41 in

36 mm

### STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

### STANDARD CORE SIZE

3 in

### APPLICABLE STANDARDS

NA

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR



Natural  
(NAT)

### PHYSICAL PROPERTIES

Adhesion to Stainless Steel

Elongation

Tensile

Thickness

### STANDARD

62 oz/in width

10%

24 lbs/in width

6.7 mils

### METRIC

6.79 N/10 mm

10%

42.0 N/10 mm

0.17 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of  
responsible forestry  
FSC® C154304