

Introducing the New

3M™ Hot Melt Applicator

The next generation of 3M™ Hot Melt Applicators for our AE Adhesives is here.

The comfortable, efficient design of our new 3M™ Hot Melt Applicator AE GEN II applicator in regular and low-temperature versions to ensure you can utilize our various adhesives. This new applicator delivers high quality and cost efficiency.

Improved features include a new soft-feel handle for more comfortable use and an illuminated on/off switch.

Heats up fast and even easier to use.

- Heats in just approximately 6 minutes from room temperature
- Adjustable trigger for different outputs per trigger pull, or to suit different hand sizes
- Narrow profile for better visibility to help with accuracy
- Sturdy base keeps the tool upright when not in use so glue doesn't melt back
- Wing tips can be added for side storage without adhesive dripping
- Nozzle easily wipes clean; base is also a nozzle adjustment tool
- PTC self-regulating heater allows models that operate on voltages from 110 V AC to 230 V AC



Basics at a glance.

Medium-size industrial 12.7mm (1/2") applicator with a cartridge header is easy to use for medium output. 6-minute warm-up time, with illuminated on/off switch.

Ideal for a range of light industrial applications:



Wide range of woodworking applications, with a good output and smooth operation.



Product assembly with a slim profile to help operators apply adhesive more accurately.



Carton closing and packaging applications, with a robust and reliable design that stands up to repeated use.

Ordering Information										
Product	Temp	SKU	Voltage	Plug Type	Glue Size	Heater	Temp Control	Operating Temp	Power Cable	Packaging
3M [™] Hot Melt Applicator AE LT – Gen II	Low	7100278635	110- 230V	US	1/2" (12.7mm)	PTC self-regulating heater	Self-regulating heater	265°F (129°C)	- 10 ft.	1/Case
3M [™] Hot Melt Applicator AE – Gen II	Regular	7100278995						380°F (193°C)		

For more products and information, visit 3M.com/HotMeltAdhesives or call 1-800-362-3550.



3M Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144-1000

Phone 800-362-3550 Fax 877-369-2923

Web 3M.com/HotMeltAdhesives

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for proper evaluation (including, but not limited to, fitness for purpose and suitability of application), election, and use of 3M products. Safety products should always be selected and used in accordance with all applicable regulations and standards (e.g., OSHA, ANSI, and others), after conducting a proper hazard assessment. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. Dispose of used atomizing heads, residual paint/locatings, used containers/materials, and PPS in accordance with local regulations. Arranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequenti

3M is a trademark of 3M. © 3M 2022. All rights reserved.