

Triple Treat

MSDS# SCM-120

March 2012

7 pages

1. PRODUCT AND COMPANY IDENTIFICATION Product Name Triple Treat Manufacturer Specialty Chemical Manufacturing 1633-B High Bridge Road, Quincy, FL 32351 EMERGENCY Phone No.: 1 800.255.3924 Chem-Tel (Chemical Emergencies) Phone (For Information): 1+580.875.1716 DATE REVISED: 03/12/2012 PREPARED BY: A. Jernigan

2. HAZARDS IDENTIFICATION

Emergency Overview: Corrosive! Poison! May cause respiratory tract, eye and skin burns. Harmful if absorbed through skin or if swallowed. Contains Materials Which Causes Damage To The Following Organs: Lungs, respiratory tract, skin, eye, lens or cornea.

Causes severe irritation and burns.

May be harmful if swallowed. Avoid breathing mist or spray.

Use with adequate ventilation. Avoid contact with eyes, skin, and clothes. Wash thoroughly after handling. Keep container closed when not in use.

Routes of entry: Inhalation. Ingestion.

Potential acute health effects

Eyes: Corrosive to eyes.

Skin: Corrosive to the skin.

Inhalation: Corrosive to the respiratory system.

Ingestion: Toxic if swallowed. May cause burns to mouth, throat and stomach.

Carcinogenic effects: No known significant effects or critical hazards.

Mutagenic effects: No known significant effects or critical hazards.

Teratogenicity/Reproductive toxicity: No known significant effects or critical hazards. **Medical conditions:**

Repeated skin exposure can produce local skin destruction or dermatitis.

Repeated or prolonged exposure to the substance can produce lung damage.

Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to the substance can produce damage to target organs.

Signs and Symptoms of Exposure:

Inhalation: Symptoms may vary from mild to severe irritation, sneezing, sore throat or runny nose. Severe pneumonitis may occur.

Ingestion: Symptoms may include burns of mouth, throat, and stomach, bleeding, vomiting, diarrhea, fall in blood pressure.

Skin Contact: Contact with skin can cause redness, irritation or severe burns and scarring with greater exposures.

MATERALSAETY DATASHET DIVERSITECH)

Triple Treat

Eye Contact: Contact with mist, spray or liquid causes redness, tearing, severe irritation or burning in eyes. Prolonged exposures can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure: Prolonged contact with dilute solutions or mists has a destructive effect upon tissue.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENT	CAS NO	EINECS NO.	%	Symbol	Risk Phrases
Water	7732-18-5		60-80		
Potassium hydroxide	1310-58-3	215-181-3	5-9	С	R22; R35
Sodium silicate	1344-09-8	231-130-8	5-9	С	R22; R34
COBRATEC(R) TT 100	29385-43-1	249-596-6	<1		R20/21/22;
					R36/37/38

Additional information: For the wording of the listed Risk phrases refer to section 15.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion: DO NOT INDUCE VOMITING! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. All the nearest poison control center or the National Poison Control Hotline at 1-800-222-1222 for advice.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse. **Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Note to Physician: Perform endoscopy in all cases of suspected potassium hydroxide ingestion. In cases of severe esophageal corrosion, the use of therapeutic doses of steroids should be considered. General supportive measures with continual monitoring of gas exchange, acid-base balance, electrolytes, and fluid intake are also required.

5. FIREFIGHTING MEASURES

Not considered to be a fire hazard.

Explosion: May cause fire and explosions when in contact with incompatible materials. **Fire Extinguishing Media:** Use any means suitable for extinguishing surrounding fire. **Special Information:** In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Contain and recover liquid when possible. Do not flush caustic residues to the sewer. Residues from spills can be diluted with water, neutralized with dilute acid such as acetic acid, hydrochloric acid or sulfuric acid. Absorb neutralized caustic residue on clay, vermiculite or other inert substance and package in a suitable container for disposal. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of 10,000 pounds. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. Remove contaminated clothing immediately. Remove unnecessary personnel from the area of the spill.

DOC27593 DiversiTech Corporation 6650 Sugarloaf Parkway Duluth, GA 30097 MATERIAL SAEEY DATA SHEET DIVERSITECH

Triple Treat

7. HANDLING AND STORAGE

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Store above 16C (60F) to prevent freezing. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do not store with aluminum or magnesium. Do not mix with acids or organic materials. Keep this and all chemicals out of the reach of children. Wash thoroughly after handling.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

OSHA Permissible Exposure Limit (PEL): 2ppm (Potassium hydroxide), 2ppm (Sodium hydroxide)

ACGIH Threshold Limit Value (TLV): 2ppm (Potassium hydroxide), 2ppm (Sodium hydroxide) **Ventilation System:** A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, <u>Industrial Ventilation, A Manual of</u> <u>Recommended Practices</u>, most recent edition, for details.

Personal Respirators (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection: Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities or a source of running water in the work area.

Work Hygienic Practices: Use proper industrial hygiene practices to minimize hazardous exposure. Wash hands after handling this material, and before eating or smoking.

9. PHYSICAL/CHEMICAL PROPERTIES

Appearance: Clear amber liquid Odor: Mild triazole odor Odor threshold: n.a. pH: >12.5 Melting point/freezing point: <0°C (32°F) Initial boiling point and boiling range: >100°C (212°F) Flash point: Not applicable Evaporation rate: n.a. Flammability limits %: Not applicable Vapor pressure: 17.5mm Hg@20°C n.a. Vapor density: n.a. Relative density: 1.08 Solubility: 100% water soluble

DOC27593 DiversiTech Corporation 6650 Sugarloaf Parkway Duluth, GA 30097

MAIERA SAETY DATA SHEET DIVERSITECH

Triple Treat

Partition Coefficient: n-octanol/water: Not applicable Auto-ignition temperature: Not applicable Decomposition temperature: n.a. Viscosity: n.a. Explosive properties: Not applicable Oxidizing properties: Not applicable n.a = not available

10. STABILITY AND REACTIVITY

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products: Reaction with non-ferrous metals releases flammable and explosive hydrogen gas.

Hazardous Polymerization: Will not occur.

Incompatibilities: Potassium hydroxide and sodium hydroxide, in contact with acids and organic halogen compounds, especially trichloroethylene, may causes violent reactions. Contact with metals such as aluminum, magnesium, tin, and zinc may cause formation of flammable hydrogen gas.

Conditions to Avoid: Heat, incompatibles.

11. TOXICOLOGICAL INFORMATION

Potassium hydroxide, CAS# 1310-58-3: LD50: 365 mg/kg oral-rat Inhalation LC 50: No Data Dermal LD 50: Believed to be > 2 g/kg. (Rabbit)

Inhalation will cause severe irritation, possible burns with pulmonary edema, which may lead to pneumonitis. **Skin contact** with this material may cause severe irritation and corrosion of tissue. **Eye contact** can cause severe irritation, corrosion with possible corneal damage and blindness. **Ingestion** may cause irritation, corrosion/ulceration, nausea, and vomiting. In general, chronic effects are due to long-term irritation.

This material may cause dermatitis on the skin, or recurrent corneal ulceration and visual disturbances of vision. In rare cases, reports have noted long-term inhalation causes bronchial inflammatory reaction or obstructive airway dysfunction.

Investigated as a mutagen.

NTP Carcinogen: No

12. ECOLOGICAL INFORMATION

Ingredient: Potassium hydroxide, CAS#1310-58-3 Environmental Fate: No information found. Environmental Toxicity: TLM96 – Gambusia Affinis (Mosquito-Fish) 80ppm Lethal Dose (24 hr. exposure): Trout – 50ppm Bluegills – 56ppm Lepomis Pallidus (minnows) – 28ppm MAILER ALSALE Y DATASHE DIVERSITECH

Triple Treat

Sodium silicate, CAS# 1344-09-8

The following data is reported for sodium silicates on a 100% solids basis: 96-hour median tolerance for fish (Gambusia affnis) of 2320 ppm 96-hour median tolerance for water fleas (Daphnia magna) of 247 ppm 96-hour median tolerance for snail eggs (Lymnea) of 632 ppm 96-hour median tolerance for Amphipoda of 160 ppm.

FISH TOXICITY:

FATE AND TRANSPORT: This material is not persistent in aquatic systems, but its high pH when undiluted or unneutralized is acutely harmful to aquatic life. It does not contribute to BOD. This material does not bioaccumulate except in species that use silica as a structural material such as diatoms and siliceous sponges. Where abnormally low natural silica concentrations exist (less than 0.1ppm), dissolved silica may be a limiting nutrient for diatoms and a few other aquatic algal species, however, the addition of excess dissolved silica over the limiting concentration will not stimulate the growth of diatom populations; their growth rate is independent of silica concentration once the limiting concentration is exceeded.

BIODEGRADATION: This material is inorganic and not subject to biodegradation.

PERSISTENCE: Diluted material rapidly depolymerizes to yield dissolved silica in a form that is indistinguishable from natural dissolved silica.

BIOCONCENTRATION: Neither silica or sodium will appreciably bioconcentrate up the food chain. **OTHER ECOLOGICAL INFORMATION:** This material has exhibited slight toxicity to terrestrial organisms.

13. DISPOSAL CONSIDERATIONS

Dispose of spill clean-up and other wastes in accordance with Federal, State, and local regulations. Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Treat empty containers as hazardous. Dispose of container and unused contents in accordance with federal, state and local requirements. State and local disposal regulations may differ from federal disposal regulations may differ from federal disposal regulations may

RCRA Hazard Class (if discarded): CORROSIVE D002.

14. TRANSPORT INFORMATION

UN Number: UN3266 UN Proper Shipping Name: Corrosive liquid, Basic , Inorganic, N.O.S. (contains potassium hydroxide) Transport Hazard Class(es): 8 Packing group: II Environmental Hazards: Not Environmentally Hazardous Substance; not a Marine Pollutant ADR/RID ROAD//CDG Transport Information: Transport category 3; Tunnel restriction code E SEA (IMDG) AIR (ICAO/IATA): ERG Code 8L ADR/RID Class: 8 ADR/RID Packing Group: II IMDG Hazard Class: 8 IMDG Packing Group: II IMDG Code Segregation Group: n.a.

MAIERA SAEEY DA ASHEED DIVERSITECH

Triple Treat

EmS: F-A S-B ADNR Item n.a. IATA Hazard Class 8 IATA Packing Group II Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

15. REGULATORY INFORMATION

Risk phrases:

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed .

R34: Causes burns.

R36/37/38: Irritating to eyes, respiratory system and skin .

Safety phrases

S1/2: Keep locked up. Keep out of reach of children

S24/25: Avoid contact with skin and eyes

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. **S45**: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.

Federal, State & International Regulations

U.S. REGULATIONS:

U.S. INVENTORY (TSCA): All components are listed on or are exempt from the inventory. TSCA 12(b) EXPORT NOTIFICATION: Not listed.

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES: 1000 LBS RQ (potassium hydroxide);

SARA TITLE III <u>SECTION 302</u> EXTREMELY HAZARDOUS SUBSTANCES: Not regulated. SARA TITLE III <u>SARA SECTIONS 311/312</u> HAZARDOUS CATEGORIES):

ACUTE: Yes; CHRONIC: No; FIRE: No; REACTIVE: No; SUDDEN RELEASE of Pressure: No SARA TITLE III SECTION 313: Not regulated.

OSHA PROCESS SAFETY: Not regulated.

STATE REGULATIONS:

California Proposition 65: Not regulated.

NEW JERSEY WORKER AND COMMUNITY RIGHT TO KNOW:

Reporting Requirement: Potassium hydroxide (1310-58-3), 5-9%; Sodium silicate (1344-09-8), 5-9%

Right To Know Hazardous Substance List: Potassium hydroxide (1310-58-3), 5-9%; Sodium silicate (1344-09-8), 5-9%

Special Health Hazard Substance List: : Potassium hydroxide (1310-58-3),5-9%; Sodium silicate (1344-09-8), 5-9%

PENNSYLVANIA RIGHT TO KNOW: Potassium hydroxide (1310-58-3), 5-9%; Sodium silicate (1344-09-8), 5-9%

Hazardous Substance List: Potassium hydroxide (1310-58-3), 5-9%; Sodium silicate (1344-09-8), 5-9%

ENVIRONMENTAL HAZARDOUS SUBSTANCE LIST: Potassium hydroxide (1310-58-3), 5-9%; Sodium silicate (1344-09-8), 5-9%

CANADIAN REGULATIONS:

MATERIAL SAETY DATA SHEET DIVERSITECH

Triple Treat

WHMIS CLASSIFICATION: E.

CANADA INVENTORY (DSL/NDSL): All components of this product are listed on the DSL. **Australian Hazchem Code:** 2R

Poison Schedule: Not scheduled

WHMIS: This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION:

NFPA/HMIS Ratings: Health: 3 Flammability: 0 Reactivity: 1

Label Hazard Warning:

Danger: Contains potassium hydroxide.

Corrosive to eyes, skin and respiratory organs.

Label Precautions:

Wear eye and skin protection when mixing and using this product.

Do not get in eyes, on skin or clothing

Wash thoroughly with soap and water after handling.

Consult the Safety Data Sheet for this product for additional storage handling and use and disposal information.

Label First Aid

For eye contact, flush eyes with water for 15 minutes. If irritation occurs, contact physician immediately.

For Skin contact, wash with soap and water until the area no longer feels "slick". If irritation persists, get medical attention.

Do not take internally. In case of accidental ingestion, do not induce vomiting; give 2-3 glasses of water and call the nearest poison control center.

If inhaled, remove the victim to fresh air. If breathing has not returned to normal within 15 minutes, get medical attention.

This information is, to the best of our knowledge and belief, accurate and reliable as of the date completed. However no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the completeness and suitability of such information for his own particular use. We do not accept liability for any loss ordamage that may occur from the use of this information, nor do we offer any warranty against patent infringement.