

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Use on utility line clearing and selective pruning of shade trees. Heavy cut capacity cuts branches up to 2 IN (50 mm). Trigger guard. Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

PRODUCT NAME –

Page Title

Utility Pruner, Open-Center

PRODUCT OVERVIEW –

Marketing Text 1

Use on utility line clearing and selective pruning of shade trees

Marketing Text 2

Heavy cut capacity cuts branches up to 2 IN (50 mm)

Marketing Text 3

Trigger guard

Marketing Text 4

Insulated fiberglass extension tubes, tested to meet OSHA Regulation 1910.269

Marketing Text 5

Heat-insulated handle

Marketing Text 6

Full power return

PRODUCT SPECIFICATION –

Product Specification 1

Accessory : 54923 HTMA Male Coupler, 54924 HTMA Female Coupler, 11660 Conversion Kit for Closed-Center hydraulic system

Product Specification 2

Application : For Use On Utility Line Clearing And General Tree Clearing Application

Product Specification 3

Cutting Capacity : 2.000 IN (50.000 MM)

Product Specification 4

Extension Type : Fiberglass - Tested To 100 KVA For 5 MINT

Product Specification 5

Flow Range : 4 - 6 GPM

Product Specification 6

Operating Pressure : 1000 - 2000 PSI

Product Specification 7

Overall Length : 86.000 IN (2159.000 MM)

Product Specification 8

Pressure Port Through : 9/16 - 18 SAE O-Ring

Product Specification 9

Return Port Through : 3/4 - 16 SAE O-Ring

Product Specification 10

Weight : 10.600 LB (4.800 KG)