

SENSORI® HIGH-FLOW CUSTOM SHOWERS

For more information about Sensori High-Flow Custom Showers, see page 333.

Limitless is an understatement with a Sensori High-Flow Shower—allowing for independent control of both temperature and volume for all shower components. It's a completely customizable, indulgent shower experience.



VALVE TRIM

ITEM	ITEM NO.	DESCRIPTION
	<p>TRIM ONLY</p> <p>T66T098-PCLHP T66T098-PNLHP T66T098-NKLHP T66T098-GLLHP T66T098-SLLHP</p>	<ul style="list-style-type: none"> Thermostatic cartridge ships with trim High temperature limit stop - 120°F Maximum flow rate guide available in the Custom Shower section MUST ORDER ROUGH SEPARATELY RP72604 extension kit extends rough installation up to 1 3/4" MUST ORDER HANDLE SEPARATELY

SENSORI® THERMOSTATIC VALVE TRIM - LESS HANDLE

HANDLE KITS: SENSORI® THERMOSTATIC VALVE TRIM

ITEM	ITEM NO.	ITEM	ITEM NO.	DESCRIPTION
	<p>HL6698-PC HL6698-PN HL6698-NK HL6698-GL HL6698-SL</p>		<p>HX6698-PC HX6698-PN HX6698-NK HX6698-GL HX6698-SL</p>	<ul style="list-style-type: none"> All handles are ADA compliant Model number = one handle

VOLUME CONTROL TRIMS

ITEM	ITEM NO.	DESCRIPTION
	<p>TRIM ONLY</p> <p>T66697-PC T66697-PN T66697-NK T66697-GL T66697-SL</p>	<ul style="list-style-type: none"> Volume control has a recommended working pressure of 45-80 psi Maximum flow rate guide available in the Custom Shower section MUST ORDER ROUGH SEPARATELY Rough accommodates up to 2 1/8" - 2 3/4" wall thickness depending on trim. RP100304 extends rough installation to 3 1/4".
	<p>TRIM ONLY</p> <p>T66698-PC T66698-PN T66698-NK T66698-GL T66698-SL</p>	<ul style="list-style-type: none"> Volume control has a recommended working pressure of 45-80 psi Maximum flow rate guide available in the Custom Shower section MUST ORDER ROUGH SEPARATELY Rough accommodates up to 2 1/8" - 2 3/4" wall thickness depending on trim. RP100304 extends rough installation to 3 1/4".

SENSORI® VOLUME CONTROL TRIM WITH CROSS HANDLE