



Southwire™

SPECIFICATION GRADE TEMPORARY CORDS

Southwire offers the broadest range of temporary power cords and extension cords available on the market. In addition to our range of molded extension cords sets, we have the ability to assemble power cords with any configuration of wiring device, size, and length of cord. These power cords are used as a power supply cable for many tools and equipment. The cords can also be personalized with your name and logo through our custom cord labeling procedure.



3201



1035



6410

 **WE'VE GOT IT
MADE IN AMERICA™**

 **CUSTOMIZATION
AVAILABLE**

**HEAVY-DUTY RUBBER,
INDUSTRIAL DUTY, TYPE SOOW
CABLE FOR YEARS OF USAGE
AND ZERO COMPLIANCE
ISSUES**




**CORDSETS HAVE FEDERAL
SPECIFICATION (WC596)
GRADE DEVICES**

**EXCELLENT RESISTANCE TO OIL
AND MOISTURE**

**HIGH FLEXIBILITY, EXCELLENT
ABRASION RESISTANCE**

**NOT SEEING WHAT YOU LIKE?
VIEW OUR EXTENSIVE MOLDED
EXTENSION-CORD SELECTION
HERE:**



PART#	WEIGHT (LBS)	CONNECTOR NEMA	LENGTH	VOLTAGE	AMPS	POLES	WIRES	GAUGE / NO.OF CONDUCTORS	TYPE	JACKET
3105	24	 5- 15	50	125	15	2	3	10/3	SOW STW Yellow	Rubber
3101	39		100							
3205	25		50							
3201	32		100							
1235	24	 L5-20	50		20	3	12/3			
1230	32		100							
1005	24	 L5-30	50		30	2	3	10/3		
1001	39		100							

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**









1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.



Southwire™

SPECIFICATION GRADE TEMPORARY CORDS CONTINUED

PART#	WEIGHT (LBS)	CONNECTOR NEMA	LENGTH	VOLTAGE	AMPS	POLES	WIRES	GAUGE / NO.OF CONDUCTORS	TYPE	JACKET
1225	24		50	250	20	2	3	12/3	SOW STW Yellow	Rubber
1220	32	L6-20	100							
1035	15		50							
1030	30	L6-30	100							
1381	7.6		25	125/250V	20	3	4	10/4	STW Yellow	
6416	28		50						SOW	
6411	45		100							
6413	24		50							
6412	38		100							
1493	8.5		25	125/250V	30	3	4	10/4	STW Yellow	
6415	18		50						SOW	
6410	35		100							
1250	26		50	120/208	20	4	5	12/5	SOW	
1251	43		100							
1050	31		50	125/250V	30	3	4	10/5	SOW	
1051	52		100							
1245	24		50	250	20	3	4	12/4	SOW	
1240	38		100							
1045	28		50							30
1040	45		100							

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**





1-855-798-6657 | SOUTHWIRE.COM





©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.



Southwire™

SPECIFICATION GRADE TEMPORARY CORDS CONTINUED

PART#	WEIGHT (LBS)	CONNECTOR NEMA	LENGTH	VOLTAGE	AMPS	POLES	WIRES	GAUGE / NO. OF CONDUCTORS	TYPE	JACKET
1246	24	 L16-20	50	480	20	3	4	12/4	SOW	Rubber
1241	38		100							
1046	28	 L16-30	50		10/4					
1041	45		100							
19178806	10.15	 6-50	25	250V	50	2	3	8/3	STW	Blue - Thermplastic
19228806	22.2		50							
1034	2	 L6-30	3	250V	30	2	3	10/4	---	---
1043	2									

PART #	MALE DEVICE	MALE DEVICE DWG	FEMALE DEVICE	FEMALE DEVICE DWG	LENGTH	GAUGE/ # OF CONDUCTORS	TYPE
1010	L14-20	 L14-20 x 1	4 x 125V 20A 2P3W 'T-Slot' Receptacles	*5-20	4	12/4	SOOW
1011	125/250V				50		
1012	3P4W 20-Amp				100		
1034	L6-30 250V 2P3W 30-Amp	 1 x L6-30	L6-30 250V 2P3W 30-Amp	2 x L6-30	3	10/3	SOOW
1043	L14-30 125/250V 3P4W 30-Amp	 1 x L14-30	L14-30 125/250V 3P4W 30-Amp	2 x L14-30	3	10/4	SOOW
100475	8165 480V 3P4W 50-Amp	 8165	8164 480V 3P4W 50-Amp	2 x 8164	3	8/4	W

**BUILT FOR DURABILITY.
BUILT FOR RELIABILITY.
BUILT FOR WORK.™**

1-855-798-6657 | SOUTHWIRE.COM

©2023 Southwire Company, LLC. All rights reserved.
*Registered Trademark & ™Trademark of Southwire Company, LLC.