


# Locking Forks - Non-Insulated Brazed Seam 16-14 AWG




Product Number†	UPC (054007-)	Wire Range (AWG)	Stud Size	Max. Lock Width	W	C	L	E	Thickness	Barrel Length	Barrel I.D.	Terminals per: Carton	Case
M14-4FLK	13765	16-14	4	0.27	0.25	0.25	0.68	0.50	0.030	0.25	0.090	—	1000
M14-6FLX	13773	16-14	6	0.27	0.25	0.25	0.68	0.50	0.030	0.25	0.090	100	500
M14-6FLK	13775	16-14	6	0.27	0.25	0.25	0.68	0.50	0.030	0.25	0.090	—	1000
M14-8FLX	13781	16-14	8	0.34	0.30	0.25	0.68	0.50	0.030	0.25	0.090	100	500
M14-8FLK	13782	16-14	8	0.34	0.30	0.25	0.68	0.50	0.030	0.25	0.090	—	1000
M14-10FLX	13799	16-14	10	0.35	0.32	0.25	0.68	0.50	0.030	0.25	0.090	100	500
M14-10FLK	13800	16-14	10	0.35	0.32	0.25	0.68	0.50	0.030	0.25	0.090	—	1000
M14-14FLX	13807	16-14	1/4	0.48	0.43	0.40	0.90	0.65	0.030	0.25	0.090	100	500
M14-14FLK	13808	16-14	1/4	0.48	0.43	0.40	0.90	0.65	0.030	0.25	0.090	—	1000



M14-4FL


Stud Size  
Wire Range

4  
16-14




M14-6FL

6  
16-14




M14-8FL

8  
16-14



M14-10FL

10  
16-14



M14-14FL

1/4  
16-14