

USER'S MANUAL

BRRF40

REFLEX SERIES
BLUETOOTH® | 40" SIDE x SIDE | AMPLIFIED OVERHEAD SYSTEM

QUICK START GUIDE



40 INCH



BOSS
AUDIO SYSTEMS

REBEL
POWER SPORTS

USER'S MANUAL

BRRF40

REFLEX SERIES
40" SIDE x SIDE | AMPLIFIED OVERHEAD SOUND SYSTEM
WITH BLUETOOTH REMOTE CONTROLLER

BOSS
AUDIO SYSTEMS

BOSS Audio Systems
3451 Lunar Court • Oxnard, CA 93030

www.bosssaudio.com | 805-322-8794

Tech Support: www.bosssaudio.com/support/technical-support



iPod, iPhone are trademarks of Apple Inc. registered in the U.S. and other countries.
Android is a trademark of Google Inc. registered in the U.S. and other countries.
BOSS Audio Systems is not affiliated with Apple Inc. or Google Inc.

All rights reserved. No part of this publication may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of BOSS AUDIO INC.

Copyright © 2017 BOSS AUDIO INC.

317 VER:1.1 EN



PRINTED IN CHINA

1 Thank you for purchasing this BOSS AUDIO SYSTEMS BRRF40 Soundbar System

Please read through these instructions carefully so you will know how to operate your model properly. After you have finished reading the instructions, keep this document in a safe place for future reference.

THIS PACKAGE CONTAINS

- 1 - BRRF40 Overhead Speaker System
- 1 - Bluetooth Multi-Function Controller Kit
- 2 - 1.75" / 2.00" Rollbar Cage Mounting Kit
- 1 - Quick Connect Power Cable
- 1 - User Manual Quick Start Guide / Poster
- 1 - Warranty Card / Facebook Card

INFORMATION TO THE USER

Bluetooth
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks is under license. Other trademarks and trade names are those of their respective owners.

5 BLUETOOTH OPERATION

PAIRING & DISCOVERING A NEW BLUETOOTH CONNECTION

- Power on the **MFC** by long-pressing the **3 Power** button for 3 seconds, long-press the **6 Bluetooth** button for 3 seconds, the **BLUE LED** will start to rapidly flash, signalling that the **MFC** is now ready for **Bluetooth** pairing

NOTE: You have 2 minutes before you must restart this procedure over again.

- The **MFC** is now in pairing mode:

ANDROID users:

- Go into the **Settings Menu** of your device
- Enter the **Bluetooth Menu**
- TURN ON Bluetooth** and press **SCAN**
- "BOSS REBEL UTV"** will now be displayed under **AVAILABLE DEVICES**
- If prompted, enter passcode: **"0000"**

iOS users:

- Go into the **Settings Menu** of your **iOS** device
- Enter the **Bluetooth Menu**
- TURN ON Bluetooth**
- "BOSS REBEL UTV"** will now be displayed
- If prompted, enter passcode: **"0000"**

- If **BOSS REBEL UTV** is not seen, repeat the above steps to refresh the **"Device List"**
- When the connection is successful a tone will be heard, and the **Bluetooth** LED indicator will light solid, you are now ready to stream music from your favorite media player to the **MFC**

9 BEFORE YOU START INSTALLATION

To avoid potential shorts in the electrical system, be sure to disconnect the (-) battery cable before installation. Use this unit with a 12-Volt battery and negative grounding only. Failure to do so may result in a fire or malfunction.

CAUTION!

When replacing the fuse, be sure to only use a fuse of the rating specified on this product. To avoid short-circuiting, cover any disconnected leads with insulating tape. It is especially important to insulate any unused wires, which if left uncovered may cause a short circuit. When connecting other devices to this product, refer to the manual for the product to be connected. The black cable is ground, make sure to connect the ground wire first. Ensure that the ground wire is properly connected to metal parts of the vehicles body frame or direct to the battery if your vehicle does not have a grounded chassis frame. The ground wire of this units power amp and a second powered system must be connected to the frame separately with different screws. If the screw for the ground wire loosens or falls out, it could result in fire or malfunction.

ONBOARD CONTROL PANEL

MUTE - ON/OFF STATUS INDICATOR WHITE = ON RED = STANDBY LED DOME - ON/OFF

NOTE!!
To conserve battery life, the LED Dome light will automatically turn off after 10 minutes when MFC ACC is turned OFF

2 INFORMATION TO THE USER

FCC COMPLIANCE STATEMENT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) this device may not cause interference, and
- (2) this device must accept any interference, including interference that may cause undesired operation of this device.

This transmitter must not be co-located or operated in conjunction with any other antenna or transmitter. The Bluetooth antenna cannot be removed (or replaced) by user. This equipment complies with FCC/IC radiation exposure limits set forth for an uncontrolled environment and meets the FCC radio frequency (RF) Exposure Guidelines and RSS-102 of the IC radio frequency (RF) Exposure rules. This equipment has very low levels of RF energy that it deemed to comply without maximum permissive exposure evaluation (MPE). But it is desirable that it should be installed and operated keeping the radiator at least 20 cm or more away from person's body (excluding extremities: hands, wrists, feet and ankles). Alteration or modifications carried out without appropriate authorization may invalidate the user's right to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Relocate or reorient the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

CAUTION!!
ADJUSTMENT OR ALTERATIONS OF THIS DEVICE MAY RESULT IN HAZARDOUS RADIATION EXPOSURE.

6 BLUETOOTH OPERATION

RECONNECTION

- Power on the **MFC** and your last paired device Bluetooth.
- Ensure you are within range of the **MFC**, the unit will now automatically reconnect
- If the device is out of range from the **MFC**, it will disconnect automatically:
 - The **MFC** will reconnect automatically to your device when in range
- If your device was previously paired with the **MFC**, but it wasn't the last paired device:
 - Ensure no other devices are currently paired
 - Enter the **Bluetooth Menu** on your device being paired
 - "BOSS REBEL UTV"** will display under **AVAILABLE DEVICES**
 - Choose the **"BOSS REBEL UTV"** to reconnect
- To clear all previously paired devices from memory, press and hold the **MFC Bluetooth** button for 10 seconds

NOTE: Some devices may require a manual **Bluetooth** reconnection once the devices **Bluetooth** is powered **OFF / ON** and/or back in range, repress the **BOSS REBEL UTV** button in **BLUETOOTH** settings on your device

Tips: Using this product without running the engine can drain the battery. To avoid battery exhaustion, be sure to occasionally run the vehicles engine while using this product.

10 MOUNTING THE OVERHEAD SOUNDBAR

3mm Allen Head **Fender Washer** **Rubber Bushing** **Your Rollbar**

BRACKET OPTIONS

- Determine the best location on your **rollbar** for your vehicle, install **rubber bushings** on the **rollbar**, ensure there is **ample head space**
- Apply supplied **Loc-Tight** to **allen bolt** tips, let dry for 20 minutes
- Wrap **C-clamp** around rollbar, hand tighten the **allen-head bolts**
- Insert left/right slide rails into **REFLEX Soundbar**, some vehicles will require the use of the rotation bracket, allowing adjustments up to +/- 10 degrees
- Carefully set the **REFLEX Soundbar** on top of the **C-clamp**, hand tighten the **allen head screws**
- Center the **REFLEX Soundbar**, permanently tighten all the **allen bolts and nuts**

ROTATE

Some applications may require optional friction tape between rubber bushings for a secure, tight fit, this can be found at most local hardware stores

CAUTION!!
Mounting brackets should be periodically checked to be sure they are tight and secure before use of the vehicle.

3 BEFORE YOU START

IMPORTANT SAFETY PRECAUTIONS

- Do not operate mobile equipment while driving a motorized vehicle – safe driving and safety consideration of others should always be your highest priority
- In the event you should notice smoke, strange noises or odor from this product, or any other abnormal signs, immediately turn off the power and consult your dealer or the nearest authorized **BOSS AUDIO** Service Center. Using this product in this condition may result in permanent damage to the system
- Set your volume control at a low setting, then slowly increase the sound until you can hear it comfortably without distortion, or ear discomfort
- BE SURE TO OBSERVE THE FOLLOWING GUIDELINES:**
 - Do not turn up the volume so high that you can't hear what's around you
 - Use caution or temporarily discontinue use in potentially hazardous situations

INSTALLATION PRECAUTIONS

WARNING - Always consult a professional installer

- Do not attempt to install or service this product by yourself. Installation or servicing of this product by persons without professional training and experience in electronic equipment and motorized vehicle accessories may be dangerous and could expose you to the risk of electric shock, injury or other hazards
- Refer any repairs to a qualified **BOSS AUDIO SYSTEMS** Service Center
- The **BRRF40** should be hard wired directly to the main vehicle battery
- When wiring directly to the vehicles battery, be sure to disconnect the batteries negative terminal wire before starting any wiring procedures
- The ground cable length should be short as possible (See wiring diagram)
- The **BRRF40** has a weather resistant design, it should not be under any circumstances be submerged in, or under water
- Use only the supplied installation parts provided with the **BRRF40**
- Wash with a mild detergent and lukewarm water using a clean sponge or a soft cloth
- Rinse well with clean water
- "DO NOT'S" - Very Important**
 - DON'T clean in hot sun or on very hot days
 - DON'T use abrasive or highly alkaline cleaners on the main body
 - DON'T scrape the main body with razor blades, or other sharp instruments
 - DON'T ever use, gasoline, acetone or carbon tetrachloride
 - DON'T ever use a pressure washer aimed at the speakers

CAUTION!! Using other mounting methods may void this warranty

7 STREAMING MUSIC

MULTIFUNCTION CONTROLLER BLUETOOTH OPERATION

- Press the **5 PLAY/PAUSE** once to start playing music or press the **PLAY** button from your devices touch screen
- To skip songs or advance, press the **4 NEXT TRACK** button
- To select the previous song, press the **7 PREVIOUS TRACK** button

VOLUME CONTROL

- To raise the volume press the **9 VOLUME UP** button or use your devices controls
- To lower the volume press the **8 VOLUME DOWN** button or use your devices controls

NOTE: If **BLUETOOTH** or **AUX** is disconnected for more than 10 minutes the **MFC** will automatically turn **OFF**, however, when not in use the **ACC** switch should be manually turned **OFF** to keep the vehicles main battery from draining

Tips: Make sure your device Bluetooth volume is set at 100% level before stowing your device

11 MULTI-FUNCTION CONTROLLER MOUNTING

OPTIONAL **MFC can rotate 90° for the best mounting position**

ROLLBAR / CAGE MOUNT

1.5" 1.75" 2.00" **3mm Allen Head**

FLUSH MOUNT

- Always check mounting depth before cutting
- Use the flush bezel as template
- Cutout hole exactly
- Insert flush mount bezel, push side tabs outwards
- Use optional silicon glue to give extra hold
- Insert **MFC**

SURFACE MOUNT

- Check mounting depth before drilling
- Use the flush bezel as template
- Drill or cut wire hole exactly
- Insert rubber trim around flush bezel, screw in **MFC**
- Insert **MFC**

TOOLS NEEDED:
- Crimp Tool
- Wrench or Pliers
- 3mm Allen Wrench

OPTIONAL TOOLS NEEDED:
- Hand saw or jigsaw

TOOLS NEEDED:
- Crimp Tool
- Wrench or Pliers
- 3mm Allen Wrench

OPTIONAL TOOLS NEEDED:
- Hand saw or jigsaw

4 GETTING TO KNOW YOUR BRRF40 MULTIFUNCTION CONTROLLER (MFC)

USB 1A CHARGING (NOT FOR AUDIO PLAYBACK)

ALWAYS CLOSE COVER WHEN NOT IN USE NEVER USE WHEN OPEN IN MUD and/or WATER

3.5mm AUX-INPUT (CABLE NOT INCLUDED)

MFC - MULTIFUNCTION CONTROLLER

- MFC RESET** (LONG PRESS BOSS LOGO FOR 10 SECONDS)
- POWER LIGHT ON/OFF** - (Auto 10 minute timer when MFC ACC is turned OFF)
- POWER ON** - Press and hold for 3 seconds
- EQ - EQ1 | EQ2 | EQ3 | FLAT** - EQ1 Default Press and hold for 3 seconds
- NEXT TRACK** - FF press and hold
- PLAY/PAUSE** - AUX MUTE
- BLUETOOTH PAIRING INDICATOR LED** - BLUE / AUX RED COLOR
- PREVIOUS TRACK** - FR press and hold
- VOLUME DOWN** - Ramp DOWN press and hold
- VOLUME UP** - Ramp UP press and hold

8 AUX-INPUT

YOUR DEVICE

Close USB cover when not in use

CAUTION!!
Never use **USB** or **AUX** while in mud and/or water

MFC can play audio from any device that has a 3.5mm headphone audio jack.

MULTIFUNCTION CONTROLLER AUX-IN OPERATION

- Power on the **MFC** by pressing and holding down the **3 POWER** button for 3 seconds
- Disconnect any paired **Bluetooth** device by turning off **Bluetooth** in your devices **Settings Menu**
- Connect your 3.5mm **AUX-IN** cable located on front side of the **MFC** to your devices headphone jack
- Route the wire back to **MFC**, secure your device in a safe location

VOLUME CONTROL

- To raise the volume press the **9 VOLUME UP** button
- To lower the volume press the **8 VOLUME DOWN** button
- To **MUTE** the volume press the **5 PLAY/PAUSE** button

Tips: Make sure your device headphone volume is set at 100% level before stowing your device

12 WIRE DIAGRAM

ALIGN CONNECTOR PINS, INSERT and HAND TIGHTEN

CAUTION: NEVER CONNECT THE MFC DIRECTLY TO THE BATTERY, ALWAYS USE AN ACCESSORY SWITCH

NEVER CONNECT +12V TO THE DOME WIRE

BOSS REBEL SERIES OPTIONAL SYSTEM EXPANSIBILITY

WIRE DIAGRAM

BLUETOOTH
- Version: 4.1
- A2DP / AVRCP / GATT
- Range: 33ft (10m) Class 2
- 20-band DSP + Preset EQ
- RCA Line Output: 2V RMS

SPEAKERS
- Dimension: 5.25" MID + 8" SUB
- MID Cone Type: PP Carbon
- Tweeter Size: 1" Titanium

AMPLIFIER
- Maximum Output Power: 1000 Watts
- Input Impedance: 16KΩ
- Frequency Response: 45Hz-25kHz

GENERAL
- Operational Power: 14.4VDC (10-16V allowable)
- MAX Current Draw: 12.3A
- USB Charging: 1A @ 5VDC +/- 5%
- Replacement Fuse: 15A/ATO TYPE
- Cabinet Material: High Impact ABS

Color: Black
- Weight: 25.3lbs / 11.9kg
- Dimensions Inches WxHxD: 40.70 x 4.09 x 10.33
- Dimensions cm WxHxD: 103.4 x 10.4 x 26.2
- Storage Temperature: 5°F to 175°F / -15°C to 80°C
- Operation Temperature: 32°F to 149°F / 0°C to 60°C

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE