

SCP PART#: 22/12P

Description : 12C/22 AWG STRANDED PLENUM - WHITE- 1000 FT SPOOL

02/22

General Specification of Product :

Final Diameter :	0.213 inches	5.410 mm
Total Cable Weight:	60.0 kg/km	40.3 lbs/1000 ft
Conductor :	12 Cond - 22 AWG 7x.0097 Bare Copper	
Insulation :	PVC	
Outer Jacket :	PVC	

Print Notes : Sequentially marked per 2FT (0 - infinity)
Standard Print : STRUCTURED CABLE PRODUCTS --- P/N 22/12P --- (UL) CL2P/CL3P
 E198137-SCP OR FPLP 75°C (UL) C(UL) CMP FT-6 UNSH 12/C 22 AWG STR
 BC --- ZONE/DEVICE A B C D E 0 1 2 3 4 5 6 7 8 9 RoHS

Electrical Characteristics :

DC Resistance 25°C:	16.5 Ohms / 1000 ft
Mutual Capacitance :	24.3 pF/ft
Impedance :	75 Ohms
Velocity of Prop :	59 %
Inductance. :	1.5 mH/km

Additional Information :

Cabled OD Avg: 0.183
Ins Thickness: 0.008
Jkt Thickness: 0.015
Certified: UL CL2P/CL3P OR FPLP / UL C(UL) CMP
Flame Rating: Plenum
Max Voltage: 300V
Packaging: Plywood Spool 12 x 10 x 5"
Packaging Weight: 41 lbs / 19 kgs

(All of the above values are approximated to within +/- 10%)