

HT1006U | HOME THEATER SURGE PROTECTOR

Protect home and office computers, electronics, and home theater equipment

The Home Theater Surge Protector HT1006U from CyberPower offers vital surge suppression for common home and office devices such as computers and electronics. It prevents spikes in energy caused by storms and electrical power surges and is ideal for safeguarding personal computers, phones/faxes/modems, and other consumer electronics. The HT1006U provides 3,600 joules of protection and ten surge-protected outlets. Its two USB charge ports (2.4 Amp shared) keep tablets, smartphones, and other rechargeable electronics ready to use. The 6 ft. power cord has a right-angle plug.

Features of the HT1006U include automatic shutdown, metal oxide varistor (MOV) technology, and an EMI/RFI noise filter. It also has an LED indicator (Protected), keyhole mounting slots, and impact-resistant casing. The HT1006U comes with a 1-Year Limited Warranty and a \$350,000 Connected Equipment Guarantee.

TYPICAL APPLICATIONS

- Home Theater Equipment
- Cable DSL/Modems
- Personal Computers
- Phone/Fax/Modem
- Cable and Satellite
- Consumer Electronics

FEATURES

- Surge suppression: 3,600 J
- Volts: 125 V
- Circuit breaker: 15 A
- Plug type: NEMA 5-15P (45° offset)
- Outlet type: 10 NEMA 5-15R (surge-protected)
- Power cord: 6 ft
- USB charge ports: 2
- LED indicator: Yes
- Keyhole slots: Yes
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$350,000



SPECIFICATIONS

INPUT		OUTPUT - CONT.	
Circuit Breaker	15 A	Outlets - Widely Spaced	4
Cord Length	6 ft (1.8 m)	USB Charge Port	Yes
Input Plug Type	NEMA 5-15P	USB Charge Port Amperage	2.4 Amps (Shared)
Plug Style	Right Angle - 45° Offset	USB Charge Port Quantity	2
OUTPUT		USB Charge Port Type	Type A
Outlet Type	10 NEMA 5-15R	USB Charge Port Voltage	5 VDC
Outlets - Total	10		

HT1006U

HOME THEATER SURGE PROTECTOR

SPECIFICATIONS CONT.

SURGE PROTECTION & FILTERING		DIMENSIONS	
Attenuation	43 dB	Physical Dimensions - WxHxD (cm)	10.01 x 3.71 x 29.69 cm
Clamping Voltage	500V (H-N, H-G, N-G)	Physical Dimensions - WxHxD (mm)	100 x 37 x 297 mm
Coax Protection RG6	None	Physical Dimensions - WxHxD (in.)	3.94 x 1.46 x 11.69 in.
EMI/RFI Filtration	150 KHz 100 MHz Yes	Weight (kg)	0.72 kg
Maximum Surge Current	135,000 A	Weight (lb)	1.60 lbs.
Maximum Surge Current H-G	30,000 A	SHIPPING DIMENSIONS	
Maximum Surge Current H-N	75,000 A	Shipping Dimensions - WxHxD (cm)	5.08 x 35.86 x 15.24 cm
Maximum Surge Current N-G	30,000 A	Shipping Dimensions - WxHxD (mm)	50.8 x 358.65 x 152.4 mm
Maximum Surge Voltage	6,000 V	Shipping Dimensions - WxHxD (in.)	2.0 x 14.12 x 6.0 in.
Response Time	<1 Nanosecond	Shipping Weight (kg)	0.82kg
Surge Suppression (Joules)	3,600 J	Shipping Weight (lbs.)	1.80 lbs.
PHYSICAL		CERTIFICATIONS	
Color	Black	Environmental	RoHS Compliant
Cord Management	No	Safety	UL1363
Form Factors Supported	Keyhole (Wall Mount or Under-counter Installation)	WARRANTY	
Material of Construction	Plastic	CEG Amount	\$350,000
Safety Covers	Yes	Connected Equipment Guarantee	Lifetime
		Product Warranty	1-Year Limited Warranty