

**UTILITY GRADE  
FIBERGLASS REINFORCED STRAPPING TAPE**

**TYPICAL APPLICATIONS**

- Non-critical strapping, packaging, bundling and palletizing

**ADVANTAGES AND BENEFITS**

- Resists moisture and solvents
- Good adhesion, quick stick and shock resistance
- Backing resists splitting and cracking
- High adhesion

**CONSTRUCTION**

Overall Grade/Function: Utility  
Backing: Fiberglass reinforced, biaxially oriented polypropylene film  
Adhesive: Hot melt, synthetic rubber

**COLOR(S)**



**STANDARD WIDTH(S)**

9 mm    12 mm    18 mm    24 mm    48mm

Contact your Shurtape sales representative for other available sizes.

**STANDARD LENGTH(S)**

55 m    330 m

**PHYSICAL PROPERTIES**

	<b>STANDARD</b>	<b>METRIC</b>
Tensile Strength	150 lbs/in width	262.7 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	5.2 mils	0.13 mm
Elongation	3.7%	3.7%
Service Temperature Range	-10 F to 150 F	-23 C to 66 C
Adhesion to Kraft	34 oz/in width	3.72 N/10 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE STANDARDS**

FDA Indirect Contact CFR 21, B, 175.105; FDA Indirect Contact CFR 21, 177.1520

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-GS500- 06/17/2014