Choose The Right 3M Floor Pad For The Job

Maintenance Operation	Equipment Speed	First Choice		Alternate Choices		System Procedures ⁺
Stripping To remove finish, sealer and contaminants from the floor surface. Done at the start of a maintenance program and at times when scrubbing will not achieve the desired results.	Rotary or Automatic	$\overline{\mathbf{\cdot}}$	3M[™] High Productivity Pad 7300 Our most aggressive stripping pad. Unique open construction resists loading and clogging. For fast removal of finish and proven consistent stripping.	3M [™] Black Stripper Pad 7200 Standard of the industry. Consistent proven performance. Long pad life.	3M [™] Brown Stripper Pad 7100 Conformable stripping pad for uneven floors. Strips prior to refinishing. Super heavy duty scrubbing for 2–4 coat removal prior to recoating.	 Dust mop Mask off delicate surface Apply properly diluted stripping solution Let solution dwell 5 minutes Strip with floor machine and pad Pick up dirty solution Detail damp mop Let dry and dust mop prior to applying finish
	Low Speed 175–600 RPM					
Scrubbing Done prior to replacing worn finish; provides a fresh new surface to maintain.	Rotary or Automatic		Scotch-Brite [™] Surface Prep Pad Heavy duty scrubbing for 2–4 coat removal prior to recoating.	3M [™] Blue Cleaner Pad 5300 Heavy duty scrubbing for 1–2 coat removal prior to recoating.		 Dust mop Apply properly diluted scrubbing solution Scrub with floor machine and pad Pick up dirty solution
	Low Speed 175–600 RPM					5. Detail damp mop6. Let dry, dust mop prior to buffing or applying finish
Cleaning To remove light soil and other contaminants.	Rotary or Automatic	Ø (•)	3M[™] TopLine Autoscrubber Pad 5000 Scrubs and cleans without dulling the finish. Open construction resists clogging. Ideal for use on an autoscrubber.	3M [™] Red Buffer Pad 5100 Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.	3M [™] White Super Polish Pad 4100 Used for light cleaning to help remove soil and scuff marks with minimal dulling of finish. Can also be used to polish wood floors.	 Dust mop Apply properly diluted cleaning solution Clean with floor machine and pad Pick up dirty solution Let dry prior to buffing
	Low Speed 175–600 RPM					
Buffing To remove scuffs and black heel marks and enhance floor appearance.	Rotary		3M[™] Red Buffer Pad 5100 Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.	3M [™] White Super Polish Pad 4100 Used for light cleaning to help remove soil and scuff marks with minimal dulling of finish. Can also be used to polish wood floors.		1. Dust mop 2. Buff only clean floors 3. Apply spray buff to floor
	Low Speed 175–600 RPM				4. B	4. Buff to a high gloss using overlapping passes5. Dust mop
Burnishing To repair finish and improve gloss and image clarity of floor surface.	Electric Battery Propane	•	3M [™] Eraser Burnish Pad 3600 Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.	3M [™] Natural Blend Tan Pad 3500 Blend of natural and synthetic fibers. For use on harder finishes and high traffic conditions. Removes marks and scuffs while polishing.	3M [™] Tan Burnish Pad 3400 Produces good gloss improvement while removing scuffs and marks. Exceptional	 Dust mop Burnish only clean floors Burnish to a high gloss using overlapping passes Dust mop
Scuff & Mark Removal	Ultra High Speed 1500 RPM & Above				durability and life. For use on harder finishes and high traffic conditions.	
Best Gloss	Electric Battery Propane		3M [™] TopLine Speed Burnish Pad 3200 Optimizes UHS burnishing on a wide variety of finishes. Combines black mark removal and gloss generation in one pad.	3M [™] Natural Blend White Pad 3300 Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Provides consistent high gloss while minimizing swirl marks.		
	Ultra High Speed 1500 RPM & Above					
Soft Finish	Electric Battery Propane	$\overline{\mathbf{\cdot}}$	3M [™] Sky Blue Hi-Performance Burnish Pad 3050 Restores gloss to dull floors. Designed for frequent burnishing with less dust, point build-up and burning, this pad is an excellent addition to 3M's high-performing line of burnishing pads.	3M [™] Aqua Burnish Pad 3100 Produces good gloss improvement. Exceptional durability and life. The soft finish problem solver.		
	Ultra High Speed 1500 RPM & Above					
Diamond-Coated Floor Pads Use to clean and condition worn and dull stone floors.	Rotary, Automatic, Electric, Battery or Propane	Souteflythere:	Scotch-Brite [™] Sienna Diamond Floor Pad Plus Diamond coated floor pads for cleaning and conditioning worn and dull marble, terrazzo, slate and polished concrete flooring.			 Dust mop 6–12 passes with Scotch-Brite[™] Sienna Diamond Floor Pad with automatic floor machine or burnisher 6–12 passes with Scotch-Brite[™] Purple Diamond Floor Pad Plus with automatic floor machine or burnisher Use 3M[™] TopLine Autoscrubber 5000 to maintain floor appearance When shine level begins to fade, use Scotch-Brite[™]
	Low to Ultra High Speed 175–1500 RPM & Above					
Diamond-Coated Floor Pads Use to clean and polish stone floors.	Rotary, Automatic, Electric, Battery or Propane	Scotch-Brite [™] Purple Diamond Floor Pad Plus Diamond coated floor pads for cleaning and polishing marble, terrazzo, slate and polished concrete flooring.				
	Low to Ultra High Speed 175–1500 RPM & Above				Purple Diamond Floor Pad Plus again	

3M Commercial Solutions Division 3M Center

Building 220-12E-04 St. Paul, MN 55144-1000 www.3M.com/SustainableSolutions 3M and Scotch-Brite are trademarks of 3M. Used under license in Canada. Please recycle. Printed in U.S.A. © 3M 2015. All rights reserved. 78-8134-0533-3 Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for user's particular purpose and suitable for user's method of application. Warranty and Limited Remedy: 3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.





Greener Solutions

The polyester fiber used to make a range of floor pads* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber used is third-party certified for post-consumer recycled content.



*3M[™] Brand Floor Pad families include 3200, 3300, 3400, 3500, 5000 and 5100.