

Red Rubber Full Face Gasket Kit

Job Name _____
 Location _____
 Engineer _____
 Contractor _____
 Tag _____ PO# _____

Specifications

Jones Stephens Red Rubber Full Face Gaskets are 1/16" thick. The kit contains ASTM A307 hex bolts and heavy hex nuts.

Do Not Use These Gaskets In High Chlorate or Chlorine Environments

Chlorate refers only to chlorine in the +5 oxidation state, or chlorate ion. The chlorate ion is a byproduct of the disinfection process used to treat drinking water. It is formed when sodium hypochlorite or chlorine dioxide are used in the treatment process. SBR is not recommended for environments with elevated levels of chlorates or chlorines. Chlorine chemically attacks SBR very aggressively. This can create a potential leak path.

Materials

Red Rubber, SBR

Dimensions and Product Offering

PART NO.	SIZE	# OF HOLES	BOLT SIZE	A	B	C	D
G51102	2.00"	4	0.62" x 2.75"	1.31"	4.25"	3.12"	0.62"
G51125	2.50"	4	0.62" x 3.00"	1.66"	4.62"	3.50"	0.62"
G51103	3.00"	4	0.62" x 3.00"	1.91"	5.00"	3.87"	0.62"
G51135	3.50"	8	0.62" x 3.00"	2.37"	6.00"	4.75"	0.75"
G51104	4.00"	8	0.62" x 3.00"	2.87"	7.00"	5.50"	0.75"
G51105	5.00"	8	0.75" x 3.25"	3.50"	7.50"	6.00"	0.75"
G51106	6.00"	8	0.75" x 3.25"	4.00"	8.50"	7.00"	0.75"
G51108	8.00"	8	0.75" x 3.50"	4.50"	9.00"	7.50"	0.75"
G51112	12.00"	12	0.87" x 4.00"	6.62"	11.00"	9.50"	0.87"

Certifications/Listings/Approvals

ASTM D1330

