

STACKABLE 16,000 LB. GVW VEHICLE RAMPS

STACKABLE DESIGN

Utilizes reinforced channels to nest and save space while in storage

MOLDED TRACTION TREADS

Plus raised stop end provides added strength and stability

17° INCLINE

Easy loading even for low clearance vehicles

SIDE OPENINGS

Allow for easy carrying, positioning, and hanging

HEAVY DUTY CONSTRUCTION

With slip-resistant rubber feet to resist sliding while loading

16,000 LB. TOTAL GVW CAPACITY

Strong enough for safe repair and maintenance underneath your vehicle

WARNING: Only use Ramps on hard, smooth, level surfaces.

Item #	Inner	Master	UPC	Packaging
W41014			039564155239	Color Box

- 16,000 lb. (7,272 kg) total gross vehicle weight capacity allows safe performance of repair and maintenance underneath your vehicle
- Patented stackable design utilizes reinforced channels to nest and save space while in storage
- Raised stop end provides added strength and stability
- Molded traction treads and gentle 17-degree incline provide easy loading even for low clearance vehicles

performancetool.com

- Heavy duty polypropylene construction with slip-resistant rubber feet to resist sliding while loading
- Specifications: maximum 4,000 lb. (1,818 kg) per ramp, 8,000 lb. (3,636 kg) per pair working load capacity; dimensions: 35-5/8 x 12-1/8 x 8-1/2 in. (90.5 x 30.8 x 21.6 cm); 6-5/8 in. (17 cm) maximum lift height



P.O. Box 88259 Tukwila, WA. 98138 1-800-426-1262 (USA & Canada) 1-800-352-9185 (Fax)