



Non-Volatile Matter	<1.0%
---------------------	-------

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Cleaning and Scrubbing in Preparation of Coating: Dilute Pre-Game 1:4 with clean water and apply solution to floor with a clean mop or other approved method. Abrade the floor using standard speed 175 rpm single brush floor machine equipped with suggested abrasive on product label. Work small areas and do not over wet floor. Pick up the scrubbing solution with a wet vacuum or autoscrubber. Tack the floor to remove scrubbing residue using fresh solution of Pre-Game diluted 1:4 with clean water. Pre-Game may also be used in automatic scrubbers for preparing gym floors for coating. Ensure proper down- pressure and change screen discs and pads at recommended intervals. 3M Surface Preparation Pads (SPP) may be used in place of screen discs for preparing floors to be coated with Hillyard water-based wood finishes. Tacking: Dilute Pre-Game 1:4 with clean water. Soak terry cloth towel in Pre-Game. Wring out towel so that it is saturated but not dripping. Place towel under broom or dust mop and begin tacking. After each pass, adjust towel in order to maintain a clean edge. Re-soak towel when it begins to dry out. Pre-Game can also be used with Quick Pass (HIL22300). Allow floor to dry at least 30 minutes before applying seal or finish. For best results, use non- linting towels and tack the floor a final time with a cleaning cloth similar to Hillyard Item No. CHI214. Maintenance Cleaning: Pre-Game can also be used for light cleaning of wood floors. Dilute Pre-Game 1:4 with clean water and tack, damp mop, Quick Pass, or autoscrub as needed to clean and maintain the floor surface. NOTICE: DO NOT use on raw wood. DO NOT use Pre-Game to tack membrane curing compounds. NOTICE: Saw dust from freshly sanded floors or dust from wood floors that have been abraded between coats will spontaneously catch fire if improperly discarded. Immediately after abrading or sanding wood floors, place dust waste in a sealed,

A special water-based formulation designed for scrubbing a wood floor in preparation for coating and tacking between coats of wood seals and finishes. Pre-Game helps remove dust, dirt and other contaminants in preparation for coating. Tacking with Pre-Game helps ensure a clean surface for coatings to bond with. Pre-Game leaves no greasy or oily residue to destroy gloss.

Features & Benefits

- No irritating fumes to bother occupants of the building
- Leaves no greasy or oily residue to destroy gloss
- Dries in 30 minutes under normal drying conditions

Item Number & Unit of Measure

Item Number	HIL0045206
Unit of Measure	1 gal Bottle

Specifications

Color	Blue
Appearance	Clear
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	1:4
PH	6.5 - 8.0

Pre-Game® Tacking Solution (continued)



water-filled metal container and immediately remove from building. NOTICE: Rags or applicators soaked in a combustible liquid will spontaneously catch fire if improperly discarded. Immediately after using rags or applicators soaked in a combustible liquid, place waste in a sealed, water-filled metal container and immediately remove from building.