

VISUAL COMFORT & Co.

2537204S-962: Four Light LED Track Light



Dimensions:

Length: 36.62"
Width: 5.0"
Height: 6.88"
Weight: 3.6 lbs.

Wire: 6.5" (color;Black/White)
Mounting Proc.: Cap Nuts
Connection: Mounted To Box
Bulb Type: Modules
Bulb Type: Integrated
Volts: 120
Watts: 5
Watts Consumed: 5
Watts Rated: 5
Hours Rated: 25000
Lumens: 350
Bulb Temp: 3000 °K
CRI: 90
Beam Spread: 120

Bulbs:

4 - LEDIntegrated Modules 5.0w Max. 120v included

Features:

- Fixture may be mounted on wall or ceiling.
- ENERGY STAR® Qualified
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Collection: Talida

Featured in the decorative Talida collection

LED

Fixture may be mounted on wall or ceiling.

ENERGY STAR® Qualified

This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

UPC #:785652067976

Finish: Brushed Nickel (962)

Material List:

1 Body - Steel - Brushed Nickel

Safety Listing:

Safety Listed for Dry Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (990C2_3720_S-TAL)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Shade	Steel	Brushed Nickel	4				6.25	4.5				

Backplate / Canopy Details:

Type	Height / Length	Width	Depth	Diameter	Outlet Box Up	Outlet Box Down
Canopy	1.38			5.0		

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	2530404-962	1	785652067976	38.58	8.18	6.38	1.16	4.9	0	Yes
Master Pack	2537204S-962	0	10785652067973							No
NJ Pallet		66		48.0	40.0	76.0	84.44	323.0		No
NV Pallet		66		48.0	40.0	76.0	84.44	323.0		No