

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Self-priming, compact, lightweight design with carrying handle. High impact strainer housing. Up to 275 gpm (1,041 lpm). Can draw water down to depth of 1-3/4 IN (45 mm)

PRODUCT NAME –

Page Title

Compact Submersible Pump

PRODUCT OVERVIEW –

Marketing Text 1

Self-priming, compact, lightweight design with carrying handle

Marketing Text 2

High impact strainer housing

Marketing Text 3

Up to 275 gpm (1,041 lpm)

Marketing Text 4

Can draw water down to depth of 1-3/4 IN (45 mm)

Marketing Text 5

Can run dry without damage

PRODUCT SPECIFICATION –

Product Specification 1

Accessory : F024772 2.000 IN Cam Lock Coupling For Discharge Hose, 156340 2.000 IN Diameter X 25.000 FT Discharge Hose Assembly, 54923 HTMA Male Coupler, 54924 HTMA Female Coupler

Product Specification 2

Capacity : Up To 275 GPM (1041 LPM) (At 7 GPM (27 LPM) And A 10.000 FT(3.000 MR) Head Height)

Product Specification 3

Discharge Size : 2.000 IN (44.000 MM) NPT Female

Product Specification 4

Flow Rate : 5 - 8 GPM (19 - 30 LPM)

Product Specification 5

Height : 12.500 IN (318.000 MM) Over Handle

Product Specification 6

Operating Pressure : 0 - 2000 PSI (0 - 138 BAR)

Product Specification 7

Pressure Port : 9/16 - 18 SAE O-Ring

Product Specification 8

Return Port : 3/4 - 16 SAE O-Ring

Product Specification 9

Strainer : 2-5/8 IN X 5-5/8 IN (67.000 MMX 143.000 MM) - 3/8 IN (9.500MM) Openings

Product Specification 10

Suction Size : 1-15/16 IN (49.000 MM)

Product Specification 11

System : Open and Closed Center System

Product Specification 12

Type : Compact, Water

Product Specification 13

Weight : 9.000 LB (4.000 KG)

Product Specification 14

Width : 7.500 IN (190.000 MM)