



# Aquaria®

## Floor Finish

A durable, multi-maintenance floor finish formulated without zinc or heavy metals.

### Features & Benefits

- Exceptional clarity with outstanding gloss
- Durable, proven polymer technology that is easy to apply and easy to strip
- Provides excellent buff response
- Formulated to work with Pro Strip™ SC Stripper, Attac® SC Stripper, Stride® Neutral Cleaner and other Diversey Green Seal® certified products
- Solids Content 20%
- Meets Green Seal® GS 40 standard and ASTM D-2047 requirement for slip resistance

### Applications

- For use on resilient and most hard surface flooring
- A sealer may be required for highly polished stone surfaces, glazed ceramic tile, luxury vinyl tile, and some rubber floors
- Not intended for use on cork, wood, or bamboo flooring





### Use Instructions

#### Preparation

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor, using a Diversey Green Seal® certified stripper or other recommended Diversey brand stripper

#### Coating

- Apply 3–4 coats uniform using a clean mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator Systems. If a higher gloss is desired, apply additional coats.
- Allow 40 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time.

#### Maintenance

- Dust mop or sweep
- Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to the label directions
- To enhance appearance, use any of the following methods: Spray buff with a Diversey brand spray buff, a red pad and 175–1500 rpm equipment
- Dry buff using a medium to aggressive pad and 1000–1500 rpm equipment
- Ultra High Speed burnish using a medium to aggressive pad and 2000 rpm equipment

#### Recoating

- Dust mop or sweep
- Clean the floor with a mop or automatic scrubber using the recommended Diversey brand cleaner according to label directions
- Blockade area and apply 2–3 uniform coats of finish using a clean mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator Systems

#### Removal

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- Strip floor, using a Diversey Green Seal® certified stripper or other recommended Diversey brand stripper

#### For Best Results

- Do not dilute
- Do not use on surfaces colder than 50° F (10° C) @ 15% RH
- To avoid contamination, do not return unused finish to original container
- Not intended for use on wood

**Note:** Floors can be slippery when contaminated with foreign materials. Promptly clean-up spills and foreign materials.  
Not intended for use in outdoor areas.

Technical data	Aquaria® Floor Finish
Certifications	Green Seal®, Ecologo®
Color/Form	Milky white, liquid
pH	7.6
Scent	Ammonia
Shelf Life	2 Years

Product	Pack size	Dilution	Product code
Aquaria® Floor Finish	1 x 5 gal. / 18.9 L Envirobox™/MC	Ready-to-use	5120870* 

\* Green Seal GS-40 Certified

### Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at [www.diversey.com](http://www.diversey.com) or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.

Green Seal® Certified mark is a registered certification mark owned by Green Seal, Inc.