



Resilience will help you make the most of your cleaning staff's efforts and your maintenance budget in high-traffic areas where high gloss is always a must. It is ideal for large retail outlets, malls, large supermarkets, or any facility where high traffic and high levels of appearance factor into the floor care program.

Features & Benefits

- Advanced polymer system provides a long lasting shine
- Floor shine will stand up to repeated propane burnishing
- High DOI (Distinctness of Image) provides a wet-look shine in high traffic areas

Item Number & Unit of Measure

Item Number	HIL0051907
Unit of Measure	5 gal Pail

Specifications

Color	White
Appearance	Milky emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
PH	8.00 - 9.00
Non-Volatile Matter	18.00 - 20.00%
Solids Content	19
Coverage SqFt/Gallon	1500-2000

Burnishable	Yes
Dry Time (hrs.)	1
Sheen	Gloss

Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

PREPARATION: Strip other finishes from the floor with Hillyard Devastator® following label directions. Use autoscrubber or floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with autoscrubber or wet vacuum. Heavy rinse with Hillyard Nutra-Rinse® and pick up with autoscrubber or wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry. **APPLICATION:** When using a sealer, apply a minimum of 5 coats of Resilience with a clean synthetic mop. Allow each coat to dry a minimum of 30 minutes before applying the next. When a sealer is not used, apply a minimum of 7 coats of Resilience. **NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60 °F (16°C). **MAINTENANCE:** Use a Hillyard Super Hil-Tone® treated dust mop daily to remove loose dirt and grit. Damp mop or autoscrub as scheduled with Hillyard Top Clean® or Arsenal® Heavy Duty Floor Cleaner. Restore gloss by dry burnishing after cleaning, and use Hillyard Restorer® as scheduled to repair and increase the gloss of the finish. Scrub and recoat as scheduled with a minimum of 2 coats of Resilience. **FLOOR PAD RECOMMENDATIONS:** Strip - black; **Scrub and Recoat** - blue or green; **Autoscrubbing** - Hillyard Red Pad, 3M 5000 TopLine Pre- Burnish, or 3M 5100 Red; **Burnishing** - Hillyard Light Blue Burnishing Pad. **NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is very porous, seal with Hillyard Hil-Tex+® or Seal 341® before applying Resilience. If stains are a problem, seal with Strong Guard®. Do not pour unused finish or seal back into the original

Resilience® Floor Finish (continued)



container.

Meets slip resistance using ASTM D2047 and Underwriters Laboratories, Inc's, Method 410.