

Buried Line Locator



PRODUCT FEATURES

- LED and LCD signal strength indicators make it quick and easy to find exact line location.
- Lightweight and ergonomically balanced.
- Automatic signal boost makes it easy to trace lines, even those with very weak signals.
- Receiver may be used in active or passive mode.
- Receiver locates multiple passive frequencies with a single setting.
- Receiver automatically locks out passive range when it detects a transmitter signal, reducing the chance of tracing other lines carrying weaker signals.
- Microprocessor-based circuitry delivers increased accuracy and features auto-gain control in all environments.
- Traces 20' (6 m) underground and provides depth readings up to 15'.
- Transmitter can be connected to live lines up to 600V.
- Lifetime limited warranty.
- Molded carrying case included.

SPECIFICATIONS

Transmitter	
Operating Voltage	0-600 VAC 0-300 VDC
Current	13mA (open line) 150mA (live or shorted line)
Frequency	33.3 kHz
Operating Temperature	0°F to 120°F (-17°C to 50°C)
Size	7.5" x 4" x 2.1" (190.5 mm x 101.6 mm x 53 mm)
Power	6 VDC (4 AA batteries)
Weight	15 oz. (425 g) (with batteries and clamp)

Receiver	
Depth Range	Measures: 0-15 ft. Traces: 0-20 ft. ±(10% reading + 0.2 ft.)
Depth Resolution	0.1 ft. increments
Passive Trace Frequency	12Hz - 24kHz
Operating Temperature	0°F to 120°F (-17°C to 50°C)
Size	4.1" x 8.5" x 38" (104.1 mm x 215.9 mm x 965.2 mm)
Power	6 VDC (4 AA batteries)
Weight	1 lb. 12 oz. (794 g)

ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION
BLL-200	07796	Buried Line Locator



USA 800-435-0786 Fax: 800-451-2632
 815-397-7070 Fax: 815-397-1865
 Canada 800-435-0786 Fax: 800-524-2853
 International +1-815-397-7070 Fax: +1-815-397-9247

4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070
 ©2004 Greenlee Textron • An ISO 9001 Company • Printed in USA
 Greenlee Textron is a subsidiary of Textron Inc.

www.greenlee.com

MA-4699

greenlee.com