



CRC Industries NZ, Auckland NZ

### ***I. Product Description***

CRC Dry Glide is a technically advanced multi-purpose dry film lubricant that cures to a non-staining micro thin film. It penetrates and bonds to metal, wood, rubber, glass and most other surfaces and provides long lasting lubrication where conventional wet film lubricants are difficult to apply or retain. Ideal for lubrication in dusty environments where contaminants might interfere with conventional wet lubricants.

The durable film seals out moisture, inhibits corrosion and resists oil, dust and dirt build-up to maintain clean operating conditions. It prevents sticking, reducing friction, heat and wear with a very low coefficient of friction over a wide temperature range. Everything works easier. Will not melt, freeze, run, pool or contaminate in-process materials.

Ideal for sliding mechanisms and on extreme heavy loads to reduce wear and prevent galling or seizing. For mechanisms that are operated at infrequent intervals or are lubricated for life.

### ***II. Application and Directions***

1. Shake can well before use.
2. Clean and dry surface area thoroughly.
3. Spray CRC Dry Glide directly onto contact surfaces or mechanisms.
4. Leave to dry for a minimum of 15 minutes.

Re-treat surfaces when needed for long-term dry film lubrication.

Note: May affect some painted surfaces; may discolour or damage some plastics. Always test on an inconspicuous area first.

### ***III. Features & Benefits***

- **PTFE-Based** – Excellent lubrication over a wide temperature range
- **Bonds to Most Surfaces** – Metal, wood, rubber and most surfaces
- **Micro-Thin Film** – Lubricates and prevents sticking, reducing friction and wear
- **Resists Dirt, Dust and Oil Build-Up** – Ideal for dirty environments
- **Non-Staining, Off-White Film** – No dusty surface powder
- **Wide Temperature Range** – Remains stable between -40°C and +230°C. Will not melt, freeze or wash-off
- **Fast Drying** – Allows in-process parts to be handled quickly
- **Seals Out Moisture** – Provides a barrier film that inhibits corrosion
- **Ultra Low Coefficient of Friction** – Ideal for sliding mechanisms and light load lubrication
- **MPI Approved C12**

### ***IV. Typical Properties and Characteristics***

Physical Properties:

<b>Appearance</b>	Hazy, white liquid
<b>Odour</b>	Ethereal
<b>Propellant</b>	Dimethyl Ether
<b>Flash Point (Aerosol)</b>	< 0°C
<b>Temperature Range</b>	-40°C to +220°C



CRC Industries NZ, Auckland NZ

**Performance Characteristics:**

<b>Type of film</b>	Dry film
<b>Recommended film thickness</b>	0.05-0.10 mm
<b>Dry to touch</b>	15 minutes
<b>Cure</b>	15 minutes
<b>Coverage</b>	0.5 to 1.0m <sup>2</sup> per can
<b>Clean up with</b>	Methylated spirits

**V. Package Description**

<b>Part Number</b>	<b>Size</b>
3040	150g Aerosol

**VI. Special Precautions****General:**

Flammable aerosol. Keep away from heat, sparks, open flames, hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Avoid breathing dust, fume, gas, vapours, spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Store in a well-ventilated place. Keep container tightly closed. Dispose of empty containers safely. All unused product should be disposed of in conformance with local and HSNO regulations, do not contaminate water supply.

**Aerosol Cans:**

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**First Aid:**

Swallowed – Do not give milk or oil. Do not give alcohol. Do not induce vomiting.

Skin – Flush skin and hair with running water (and soap if available). Remove any adhering solids with with industrial skin cleansing cream. Do not use solvents. Seek medical attention in the event of irritation.

Eyes – Immediately hold eyelids apart and flush eye continuously for at least 15 minutes with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Transport to hospital or doctor without delay.

Inhalation – Remove to fresh air. Lay patient down. Keep warm and rested. If breathing with difficulty, get medical attention immediately.

Refer to Material Safety Data Sheet for more details.

TECHNICAL DATA SHEET Version 08/2015

**PRODUCT WARRANTY:** CRC offers a conditional warranty of this product for the period of 2 years from the date of manufacture.

**DISCLAIMER:** All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries makes no representations or warranties of any kind concerning this data.