



Model ZPI Valve Position Indicator

- Positive visual indicator of current operating position
- Frictionless
- Leak proof
- Easy maintenance and cleaning
- Protected indicator rod
- Can be installed to replace the top plug on any Zurn Wilkins basic main valve

Model ZPI Size	Height Above Cover	NPT
1-1/4"	4-1/4"	1/2"
1-1/2"	4-1/4"	1/2"
2"	4-1/4"	1/2"
2 1/2"	4-1/4"	1/2"
3"	4-1/4"	1/2"
4"	4-1/4"	3/4"
6"	6"	3/4"
8"	6-3/8"	1"
10"	6-3/8"	1"
12"	8"	1"
14"	8"	1"
16"	8"	1"



Pressure Gauges

Standard Equipment on all Zurn Wilkins Pressure Reducing and Pressure Relief Automatic Control Valves

- Face Diameter:** 2 1/2"
Connection Size: 1/4" NPT bottom mount
Range: 0-300 psi for 150# Flange and grooved end connections, 0-400 psi for Threaded, 300# flange end connections
Accuracy: +/- 3-2-3% of Span
Bourdon Tube: Phosphor bronze
Window: Plastic
Movement: Brass



Model 40XL2 Check Valve

- Size:** 3/8" thru 3/4"
Body: Cast brass
Poppet: Polyetherimide
Seal Ring: NBR
Spring: Stainless steel



Model SXL Wye Strainer

- Size:** 3/8" thru 3/4"
Body and Cap: Cast bronze ASTM B584 or B806, lead-free
Screen: 20 Mesh stainless steel, 300 series